

VERT CLEAR: 16.84'

SIDEWALKS:

EXP JT MATL: 1st Polyurethane

DRAINS: 6" ϕ curb drain

[illegible]

STRINGERS - BEAMS OR GIRDERS

SPAN NO	MATL	SPAN C C BEARS	NO OF BEAMS	SPACING	SECTION		TYPE EXP	STD DWG	DESIGN RATING
					OUTR STRING	INR STRING			
1	conc I" Precast		8	varies	1'-10" $\pm$ 0'-7"	X 3'-9"	slide	special	HS20-44
2	Steel R Girder		9	"	web R 79" x $\frac{7}{16}$ "		"		
4	conc I" Precast		14	"	1'-10" $\pm$ 0'-7"	X 3'-9"	"		
5	"	"	7	"			"		
6-20	"	"	6	7'-0 $\frac{1}{2}$ "	1'-10" $\pm$ 0'-7"	X 3'-9"	Except span 12 has 2'-2" $\pm$ 0'-8" X 4'-6"		

TRUSSES

WHEN MADE,

YIELD POINT:

FABRICATED BY:

DESIGN RATING: FLOOR:

TRUSSES

SPAN NO	MATL - KIND TYPE - CONNS	SPAN C C BEARS	NO AND LGTH OF PANELS	DIST C C TRUSSES	DEPTH AT CENTER	TYPE EXP	STD DWG

SUBSTRUCTURE

BENT NO	TYPE AND MATL	HT GRADE TO TOP CAP	HT TOP CAP TO BOTT FOOT	NO AND LGTH PILES	FOUNDATION MATL	DIST GRADE TO GROUND
REAR ABUT	1 RC & steel Pile (Spill thr)	4'-10"		18 @		
FWD	21 " " " "	"		14 @		
PIER OR BENT:	2 3 col conc round (Pile flg)	6'-10 1/2"				
	3 4 col conc " "	"				
	4 5 col conc " "	"				
	5 3 col conc " "	4'-10"				
	6 2 col conc " "	"				
	7 " " " "	"				
	8 " " " "	"				
	9 " " " "	"				
	10 " " " "	"				
	11 " " " "	"				
	12 3 col conc " "	5'-7"				
	13 " " " "	"				
	14 2 col conc " "	4'-10"				
	15 " " " "	"				
	16 " " " "	"				
	17 " " " "	"				
	18 " " " "	"				
	19 " " " "	"				
	20 " " " "	"				

2651 m. BIN: 10664(+1)

[illegible]

