

BAYWAY WB SECTION

BAYWAY EB SECTION


STA. 598+02.66 TO STA. 605+29.00

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 38 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT EAST TUNNEL I-10 BAYWAY BRIDGE BRIDGE SECTION AT GORE 1 MOBILE COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (1 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			



TYPICAL BAYWAY WB SECTION

TYPICAL BAYWAY EB SECTION

STA. 605+29.00 TO STA. 610+98.19

STA. 616+18.19 TO STA. 623+94.19

STA. 625+09.19 TO STA. 659+13.19

STA. 705+36.77 TO STA. 710+91.28

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 39 OF 59  
REVISIONS

MOBILE RIVER BRIDGE  
AND BAYWAY PROJECT  
I-10 BAYWAY BRIDGE  
BAYWAY TYPICAL SECTION

MOBILE COUNTY, ALABAMA

BRIDGE SECTION  
(2 OF 20)

ESTIMATED QUANTITIES DESIGNED BY: DRAWN BY:

COMPUTED BY: CHECKED BY: DATE DRAWN:


VERIFIED BY: DATE CHECKED: SCALE: AS SHOWN

BIN:

LEFT LANE RIGHT LANE

PENTABLE: \$PENTBLS\$  
SCALE:\$SCALESHORT\$

PLOT DRIVER: \$PLTDRV\$  
USER: \$USER\$  
FILE: \$PWVARVAULTPATHDESC\$



TYPICAL BAYWAY WB SECTION

TYPICAL BAYWAY EB SECTION

STA. 610+98.19 TO STA. 616+18.19

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.


ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 40 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT EAST TUNNEL I-10 BAYWAY BRIDGE BAYWAY CROSSOVER I MOBILE COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (3 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			

PLOT DRIVER: \$PLTDRVS\$  
USER: \$USER\$  
FILE: \$PWVARVAULTPATHDESC\$

DATE: \$DATE\$  
DESIGNED BY: \$DESIGNED\_BY\$  
CHECKED BY: \$CHECKED\_BY\$  
DATE DRAWN: \$DATE\_DRAWN\$  
SCALE: \$SCALE\$

REFERENCE PROJECT NUMBER	FISCAL YEAR	SHEET NUMBER
	2022	582



TENSAW RIVER WB SECTION


TENSAW RIVER EB SECTION

STA. 623+94.19 TO STA. 625+09.19

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION					
BRIDGE SHEET NO. 41 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE TENSAW RIVER MOBILE COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (4 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			




STA. 659+13.40 TO STA. 662+11.37

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 42 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT I-10 BAYWAY BRIDGE BAYWAY SECTION AT GORE 2		
REVISIONS					
			BALDWIN COUNTY, ALABAMA		
			BRIDGE SECTION (5 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			



STA. 662+11.37 TO STA. 664+73.99

STA. 716+87.13 TO STA. 720+31.49

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 43 OF 59  
REVISIONS


MOBILE RIVER BRIDGE  
AND BAYWAY PROJECT  
I-10 BAYWAY BRIDGE  
TYPICAL BAYWAY SECTION  
(1 OF 20)

BALDWIN COUNTY, ALABAMA

BRIDGE SECTION  
(6 OF 20)

ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
COMPUTED BY:	CHECKED BY:	DATE DRAWN:
VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN

BIN: LEFT LANE RIGHT LANE



STA. 664+74.00 TO STA. 670+35.93

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 44 OF 59  
REVISIONS


MOBILE RIVER BRIDGE  
AND BAYWAY PROJECT  
I-10 BAYWAY BRIDGE  
BAYWAY SECTION AT GORE 3

BALDWIN COUNTY, ALABAMA

BRIDGE SECTION  
(7 OF 20)

ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
COMPUTED BY:	CHECKED BY:	DATE DRAWN:
VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN

BIN: LEFT LANE RIGHT LANE



STA. 671+6.40 TO STA. 677+02.46

STA. 723+31.64 TO STA. 731+92.48

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 45 OF 59  
REVISIONS

MOBILE RIVER BRIDGE  
AND BAYWAY PROJECT  
I-10 BAYWAY BRIDGE  
BAYWAY TYPICAL SECTION

BALDWIN COUNTY, ALABAMA

BRIDGE SECTION  
(8 OF 20)

BIN:

LEFT LANE

RIGHT LANE

ESTIMATED QUANTITIES

DESIGNED BY:

DRAWN BY:

COMPUTED BY:


CHECKED BY:

DATE DRAWN:

VERIFIED BY:

DATE CHECKED:

SCALE: AS SHOWN




STA. 677+02.17 TO STA. 680+78.81

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 46 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT I-10 BAYWAY BAYWAY SECTION AT GORE 4		
REVISIONS					
			BALDWIN COUNTY, ALABAMA		
			BRIDGE SECTION (9 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			



TYPICAL BAYWAY WB SECTION

TYPICAL BAYWAY EB SECTION

STA. 680+80.47 TO STA. 688+03.01 (WB)

STA. 680+80.47 TO STA. 687+52.37 (EB)

STA. 693+78.01 TO STA. 701+30.36 (WB)

STA. 693+66.83 TO STA. 701+30.36 (EB)

STA. 734+93.56 TO STA. 749+41.68

STA. 750+06.68 TO STA. 886+60.95


STA. 891+80.95 TO STA. 920+16.47

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 47 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT I-10 BAYWAY BRIDGE BAYWAY TYPICAL SECTION		
REVISIONS					
			BALDWIN COUNTY, ALABAMA		
			BRIDGE SECTION (10 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			



MIDBAY WB SECTION

MIDBAY EB SECTION

STA. 687+52.37 TO STA. 688+28.98 (EB)


STA. 688+13.01 TO STA. 688+68.00 (WB)

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 48 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (11 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
BIN:	LEFT LANE	RIGHT LANE	COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN



MIDBAY WB SECTION

MIDBAY EB SECTION

STA. 688+28.98 TO STA. 689+05.60 (EB)

STA. 688+68.00 TO STA. 689+18.52 (WB)

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION


BRIDGE SHEET NO. 49 OF 59  
REVISIONS

MOBILE RIVER BRIDGE  
AND BAYWAY PROJECT  
MIDBAY  
I-10 BAYWAY BRIDGE  
BAYWAY SECTION  
BALDWIN COUNTY, ALABAMA

BRIDGE SECTION

ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
COMPUTED BY:	CHECKED BY:	DATE DRAWN:
VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN

BIN: LEFT LANE RIGHT LANE



STA. 689+05.60 TO STA. 690+59.60 (EB)


STA. 689+18.52 TO STA. 689+69.02 (WB)

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 50 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (13 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN
BIN:	LEFT LANE	RIGHT LANE			



MIDBAY WB SECTION

MIDBAY EB SECTION

STA. 690+59.60 TO STA. 692+13.60 (EB)


STA. 689+69.02 TO STA. 692+76.79 (WB)

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 51 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (14 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN



STA. 692+13.60 TO STA. 692+89.11 (EB)


STA. 692+76.79 TO STA. 693+78.01 (WB)

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 52 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (15 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN




STA. 701+31.48 TO STA. 705+36.77

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 53 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION GORE AREA 5 BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (16 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN



NOTES:


- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 54 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT MIDBAY I-10 BAYWAY BRIDGE BAYWAY SECTION GORE AREA 6 BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (17 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
BIN:	LEFT LANE	RIGHT LANE	COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN

PENTABLE: \$PENTBLS\$  
SCALE:\$SCALESHORT\$

PLOT DRIVER: \$PLTDRV\$  
USER: \$USER\$  
FILE: \$PWVARVAULTPATHDESC\$



BAYWAY WB SECTION


BAYWAY EB SECTION

STA. 749+41.68 TO STA. 750+06.68

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION					
BRIDGE SHEET NO. 55 OF 59  REVISIONS			MOBILE RIVER BRIDGE AND BAYWAY PROJECT I-10 BAYWAY BRIDGE BAYWAY CROSSOVER 2 AND 3		
			BALDWIN COUNTY, ALABAMA		
			BRIDGE SECTION (18 OF 20)		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
BIN:	LEFT LANE	RIGHT LANE	COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN



BAYWAY WB SECTION

BAYWAY EB SECTION

STA. 928+11.58 TO STA. 944+07.30

NOTES:

- REFER TO ROADWAY DRAWINGS FOR SUPERELEVATION AND CROSS-SLOPE INFORMATION.
- MAINTAIN MINIMUM VERTICAL CLEARANCE TO LOW MEMBER AS FOLLOWS:
  - 1'-0" ABOVE 100-YEAR STORM SURGE ELEVATION (SEE NOTE FOR RAMP ENDS).
  - 17'-0" ABOVE ROADWAY LANES.
  - BOTTOM OF PRESTRESSED BEAMS OVER WATER - EL. 8.0' MINIMUM.
  - 3'-0" BOTTOM OF PRESTRESSED BEAMS OVER GRADE.
- RAMP ENDS - RAMP ENDS OVER WATER WHICH CANNOT MAINTAIN 1'-0" MINIMUM CLEARANCE ABOVE THE 100-YEAR STORM SURGE SHALL BE DESIGNED TO WITHSTAND THE STORM SURGE HYDRAULIC FORCES.
- PROVIDE DECK DRAINAGE SCUPPERS ACCORDING TO ALDOT STRUCTURAL DESIGN MANUAL SECTION 2 (NOT SHOWN). PROVIDE CLOSED DECK DRAINAGE SYSTEM FOR AREAS WHERE SCUPPERS ARE PROHIBITED AND ADJACENT SCUPPERS ARE NOT ADEQUATE TO CONVEY FLOW.

ALABAMA DEPARTMENT OF TRANSPORTATION

BRIDGE SHEET NO. 56 OF 59			MOBILE RIVER BRIDGE AND BAYWAY PROJECT EASTERN SHORE I-10 BAYWAY BRIDGE BAYWAY BRIDGE SECTION BALDWIN COUNTY, ALABAMA		
REVISIONS					
			BRIDGE SECTION (19 OF 20) )		
			ESTIMATED QUANTITIES	DESIGNED BY:	DRAWN BY:
			COMPUTED BY:	CHECKED BY:	DATE DRAWN:
			VERIFIED BY:	DATE CHECKED:	SCALE: AS SHOWN

