

I-10 MOBILE RIVER BRIDGE

MAIN SPAN BRIDGE, GEOTECHNICAL MEMO

SEPTEMBER 8, 2023



This Main Span Bridge Geotechnical Memo was prepared by Shannon & Wilson, Inc., which is a member of the Kiewit-Massman-Traylor Design Team.

The lead author and Responsible Engineer for this memo is Gerard J. Buechel, PE, who is the Responsible Geotechnical Engineer for Shannon & Wilson, Inc., which is a subconsultant to the Kiewit Engineering Group. The Responsible Geotechnical Engineer for the Kiewit Engineering Group is Michael Owens, PE, who is the overall lead for the Geotechnical Team.

Gerard J. Buechel, PE
Senior Vice President



TABLE OF CONTENTS

1 Purpose1

2 Project Description.....1

3 Information Provided by ALDOT2

4 Subsurface Conditions Along the Main Span Bridge Alignment.....3

5 Potential Variation of Subsurface Conditions.....6

6 Main Span Bridge Foundations6

7 Results of Analyses.....9

Attachments

- Table 1 – Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Tower Foundations (3 sheets)
- Table 2 – Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Transition Pier Foundations (4 sheets)
- Table 3 – Recommended Custom T-z and Q-z Curves for FB-MultiPier Analyses, Main Span Bridge Foundations
- Figure 1 – Site Plan
- Figure 2 – Generalized Subsurface Profile (2 sheets)
- Appendix A – Exploration Results Provided by ALDOT
- Appendix B – Laboratory Test Results Provided by ALDOT
- Appendix C – Results of Statistical Analyses
- Appendix D – Axial Resistance Plots

1 PURPOSE

This memo contains preliminary recommendations and a summary of available data for the proposed Main Span bridge of the I-10 Mobile River Bridge Project. This Geotechnical Memo is based on the available 30% design documents developed by the Kiewit-Massman-Traylor (KMT) team, and the results of borings, laboratory testing, and foundation load test results provided by the Alabama Department of Transportation (ALDOT) as part of the Request for Proposal documents. No additional explorations or testing were accomplished by the Kiewit Team to support this memo.

2 PROJECT DESCRIPTION

ALDOT selected the KMT Team to design and construct modifications to the existing Interstate-10 (I-10) in Mobile, Alabama. The project includes roadway modifications, new interchange bridges located along the west side of the Mobile River, and a new cable-stayed bridge spanning over the Mobile River that will connect to West and East high level approaches (WHLA and EHLA). The cable-stayed bridge will be about 220 feet above the Mobile River and extend between Stations 508+90.05 and 534+65.05. The bridge will be supported by two main span pylon foundations (designated Pylon P35 on the west and P36 on the east), with a tie-down pier and a transition pier located on the west (designated Piers P34 and P34A) and east (designated Piers P37 and Pier P37A) sides of the bridge. The main span of the bridge is about 1,400 feet long, and the west and east approach spans are each about 590 feet long. There is about 105 feet between the tie-down and transition piers located on the west and east sides of the main span.

On the west side of the Mobile River, new on- and off-ramps and bridges will be constructed from I-10 to Tennessee Street, South Carolina Street, Virginia Street, Texas Street, and the WHLA. The WHLA extends from I-10 near the Texas Street Bridge to the Main Span bridge over the Mobile River. The Main Span bridge connects the WHLA and the EHLA. The EHLA extends into Polecat Bay then transitions into the I-10 Bayway.

This memo provides preliminary foundation recommendations for the Main Span bridge. Each pylon foundation will be supported by 56, 72-inch diameter, driven steel pipe piles with a 1-1/4-inch wall thickness. The foundation cap will be 119 feet wide in the transverse direction and 104 feet long in the direction of the roadway. The cap will vary in thickness from 15.5 feet at its edge, increasing to 20 feet at the pylon interface. The bottom of the pile cap will be located at elevation -1.5 feet. The tip elevations of the piles that support P35 (west side, located at Station 514+80.05) and P36 (east side, located at Station 528+75.05) are estimated to be -250 feet and -260 feet, respectively. Concrete plugs with lengths of 90 and 110 feet will be constructed inside the steel pipes for the west and east pylons, respectively.

Each transition pier will be supported by two, pile-supported foundations. The pile caps supporting each foundation of Pier P34 (west side, located at Station 508+90.05) will be 40.5 feet wide in the transverse direction and 34.5 feet long in the direction of the roadway. The pile caps supporting each foundation of Pier P37 (east side, located at Station 534+65.05) will be 52.5 feet wide in the transverse direction

and 40.5 feet long in the direction of the roadway. The center-to-center distance between each pile supported cap is 80 feet. The caps will be 10 feet thick. The bottom of the pile caps will be located at elevation -12 feet. Each foundation of Piers P34 and P37 will be supported by 42 and 49, respectively, 24-inch square prestressed concrete piles (PSCP). The estimated tip elevations of the piles are -110 feet.

Each tiedown pier will be supported by two, pile-supported foundations. The pile caps supporting each foundation of Pier P34A (west side, located at Station 509+94.88) will be 48.5 feet wide in the transverse direction and 48.5 feet long in the direction of the roadway. The pile caps supporting each foundation of Pier P37A (east side, located at Station 533+60.22) will be 48.5 feet wide in the transverse direction and 49.5 feet long in the direction of the roadway. The center-to-center distance between each pile supported cap is 116 feet. The caps will be 10 feet thick. The bottom of the pile caps will be located at elevation -12 feet. Each foundation of Piers P34A and P37A will be supported by 25 and 30, respectively, 24-inch square PSCP. The estimated tip elevations of the piles are -110 feet.

3 INFORMATION PROVIDED BY ALDOT

Preliminary geotechnical engineering recommendations were developed by the KMT Team based on information provided by ALDOT as part of the Request for Proposal. This information includes the results of subsurface explorations, laboratory testing, and a foundation load test program.

Subsurface Explorations and Laboratory Testing

ALDOT provided the results of explorations completed in the Main Span bridge area. The explorations included borings completed in 2016-2017 by Thompson. The Thompson 2016-2017 deep borings drilled along the Main Span bridge alignment used in our analyses include TH-13, WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA13, as shown on Figure 1.

The results of these explorations and laboratory testing performed on selected samples retrieved from the borings were used to characterize the subsurface conditions along the alignment. In addition, nominal pile resistances were estimated using the results of these borings. The exploration logs and the results of lab testing performed on selected samples retrieved from the borings are included in Appendices A and B, respectively. This information was reproduced directly from the reports provided by ALDOT.

Foundation Load Testing Program

ALDOT performed a Pile/Drilled Shaft Load Test program in early 2018 in advance of project design and construction. The test program included installing and testing two HP14x89 steel H-piles, two 18-inch-square PSCPs, one 30-inch-square PSCP, five 54-inch-diameter spun-cast concrete cylinder piles, one 60-inch-diameter steel pipe pile, and one 72-inch-diameter drilled shaft. All the piles included high-strain dynamic pile testing (pile driving analyzer [PDA]) during initial drive and at multiple restrikes after initial drive. In addition, one of the H-piles and one of the 18-inch-square PSCPs were tested using a static load test frame; and the 30-inch-square PSCP, two 54-inch-diameter spun-cast concrete cylinder piles, and

the 60-inch-diameter steel pipe pile were tested using Statnamic load testing methods. The 72-inch-diameter drilled shaft was tested using a bi-directional Applied Foundation Testing hydraulic load cell.

The test program identified the following:

1. The nominal pile resistance, as determined by the PDA testing, increased with each restrike after the initial drive of a test pile. The greatest increase (compared to the end of initial drive [EOID] resistance, as determined by the PDA testing) is generally between the EOID and the one day restrike. Additional resistance increase was also observed between the restrike performed after 1 day and multiple days (7 to 17 days) after initial drive; but the resistance increase over this period was generally less than the additional resistance gained between EOID and the 1-day restrike.
2. The nominal resistance of the pile determined by static testing is always greater for the six piles tested using either a conventional load frame or Statnamic load testing, than that determined from the dynamic testing alone (PDA/CAPWAP analyses). The maximum resistance of the PSCP determined by the PDA testing (maximum resistance of the multiple restrikes, which always corresponded to the last restrike performed no matter how long the setup time between restrikes which ranged between about 7 and 17 days after EOID) varies between about 60 and 86%, with an average of 76% of the resistance estimated from the static/Statnamic load testing using the Davisson failure criteria. The resistance using the Davisson criteria was not determined for the steel H-pile and steel pipe pile, but the nominal resistance of these steel piles, determined by the PDA testing (maximum resistance of the multiple restrikes), varies between about 65 and 91% of the maximum pile failure load estimated from the static/Statnamic load testing.
3. For most of the PSCPs, the dynamic pile testing measurements indicate that the maximum tensile stress in the pile exceeded the allowable stress limits for portions of the initial drive and for restrike. In general, the high tensile stresses occurred early in the initial drive, during softer driving conditions. During restrikes, the maximum tensile stress values often exceeded the allowable values during the early part of the restrike, as the hammer was generally set at the highest fuel setting to transfer maximum energies to the pile in an attempt to fully mobilize resistance. Additional pile cushion material and/or modification to the driving procedures, such as reducing hammer energy setting during driving in soft soils, would be one method to reduce the potential for the tensile stresses to exceed the allowable stress limits during production pile driving and restrikes.

The ALDOT load test results were used to develop design parameters to estimate pile embedments at existing exploration locations provided by ALDOT for the proposed Main Span bridge.

4 SUBSURFACE CONDITIONS ALONG THE MAIN SPAN BRIDGE ALIGNMENT

The subsurface conditions along the Main Span bridge alignment were evaluated based on the results of the explorations and laboratory testing provided by ALDOT, as summarized in Section 3. No additional explorations or lab testing were performed by KMT for this Geotechnical Memo.

The subsurface conditions along the Main Span bridge alignment were generally separated into four layers, as described below. The upper two layers, however, were subdivided into an upper and lower sublayer based on the differences noted in the relative density of the material. A typical subsurface profile is presented on Figure 2. Note that five generalized layers are shown on Figure 2. The sand layer, as described below, is shown as two distinct layers (different shades of green) on the subsurface profile. Although the material types are generally similar for these two sand sublayers, the relative density appears to be greater for the lower sand sublayer, as described below.

A series of plots of the energy-corrected Standard Penetration Test (SPT) value versus elevation, normal and lognormal N-value distributions, and USCS (Unified Soil Classification System) classification are presented in Appendix C for the different soil layers.

Surficial Layer

The surficial soil layer is about 15 to 55 feet thick and extends from the existing ground surface, located between about elevation +3 feet and +15 feet, to about elevation -3 to -60 feet. Note that this layer was previously described as the “Overburden Layer,” but is now changed to “Surficial Layer” based on a reviewer’s comment on the WHLA and EHLA memos previously submitted. “Overburden Layer” is still used as a designation for this surficial layer in the tables and statistical summaries presented in the Appendices of this memo. The material generally consists of very loose to medium dense silty sand with layers of very soft to soft clay with organics.

The surficial layer was subdivided into upper and lower sublayers for the material encountered above and below elevation 0 feet, respectively. The upper layer encountered above about elevation 0 feet, generally consists of granular fill that was placed during the development of the area and the construction of the adjacent infrastructure. The existing ground surface elevation in these areas ranges between about elevation +3 and +15 feet. The material generally consists of very loose to medium dense, silty sand. The mean and median energy-corrected SPT value for this portion of the layer is 29 and 22 (30 data points), respectively. As shown in Appendix C (Figure C-15), 100% of the drill footage within the granular fill encountered (as presented in the bore logs) is classified (USCS) as SP, SP-SM, SM, and SC-SM.

The lower sublayer is located below about elevation 0 feet and extends to about elevation -10 to -60 feet. The material generally consists of very loose to loose, silty sand with layers of very soft to soft clay with organics. The mean and median energy-corrected SPT values for this portion of the layer are 7 and 6 (70 data points), respectively. As shown in Appendix C (Figure C-16), approximately 94% of the drill footage within this portion of the layer encountered (as presented in the bore logs) is classified (USCS) as SM, SP, SP-SM, SC, GP-GM, GP, and SC-SM, with the remaining 6% classified as CH, CL, and MH.

Sand Layer

The surficial soil layer is underlain by a sand layer that is approximately 60 to 125 feet thick and extends to about elevation -130 to -190 feet. The material generally consists of medium dense to very dense silty sand, with occasional layers of silt and low and high plasticity clay.

The sand layer was subdivided into upper sand and lower sand sublayers for the material encountered above and below about elevation -85 feet, respectively. The upper sand layer is about 25 to 70 feet thick and extends to about elevation -80 to -90 feet. The upper sand layer material generally consists of medium dense to very dense silty sand, with occasional layers of low plasticity clay. The mean and median energy-corrected SPT values for this material are 48 and 42 (65 data points), respectively. As shown in Appendix C (Figure C-17), approximately 98% of the drill footage within the upper sand layer encountered (as presented in the bore logs) is classified (USCS) as SP-SM, SP, SM, and SW-SM, with the remaining 2% classified as CL-ML.

The lower sand layer is about 35 to 100 feet thick and extends to about elevation -120 to -190 feet. The lower sand layer material generally consists of medium dense to very dense silty sand, with occasional layers of low and high plasticity clay. The mean and median energy-corrected SPT values for this material are 63 and 58 (63 data points), respectively. As shown in Appendix C (Figure C-18), approximately 75% of the drill footage within the lower sand layer encountered (as presented in the bore logs) is classified (USCS) as SP-SM, SM, SP, SC, and SC-SM, with the remaining 25% classified as CH, CL, and ML.

Clay/Silt Layer

The sand layer is underlain by a clay/silt layer that is approximately 30 to 105 feet thick and extends to about elevation -215 to -230 feet. The material generally consists of stiff to hard clay and silt, with occasional layers of silty sand. The mean and median energy-corrected SPT values for this material are 63 and 51 (52 data points), respectively. As shown in Appendix C (Figure C-19), approximately 77% of the drill footage within the clay/silt layer encountered (as presented in the bore logs) is classified (USCS) as CL, CH, CL-ML, and ML, with the remaining 23% classified as SM, SC, SP-SM, and SP.

Basal Silt/Sand Layer

The clay/silt layer is underlain to the bottom of the borings by loose to very dense, silty sand with occasional low plasticity silt and clay layers. This layer is about 15 to 90 feet thick, as it extends to the bottom of the borings. The mean and median energy-corrected SPT value for this material are 85 and 47 (38 data points), respectively. As shown in Appendix C (Figure C-20), approximately 82% of the drill footage within the basal silt/sand layer encountered (as presented in the bore logs) is classified (USCS) as SM and SP-SM, with the remaining 18% classified as ML and CL.

5 POTENTIAL VARIATION OF SUBSURFACE CONDITIONS

Our site interpretation, engineering analyses, and recommendations are based on the results of borings, laboratory testing, and foundation load tests that were performed by others. Our interpretations are specific to the locations and depths noted on the exploration logs and may not be applicable to all areas of the project alignment. No number of explorations and testing can precisely predict the characteristics, quality, or distribution of subsurface and site conditions.

Potential variation includes, but is not limited to:

- There are some areas where there is limited to no available subsurface data, such that there is a potential for high variability in the foundation embedments.
- The conditions between and below explorations may be different. The thickness of the geologic units will vary across the site, and in some cases, subsurface conditions can vary in relatively short distances.
- The passage of time or intervening causes (natural and manmade) may result in changes to site and subsurface conditions.
- Groundwater levels will likely fluctuate due to seasonal and tidal changes.
- We did not observe the samples in the previous borings performed along the Main Span bridge alignment by ALDOT. Therefore, we cannot confirm that the soil conditions shown on the ALDOT logs are representative of in situ conditions.
- The ALDOT load tests were performed on different size PSCPs than those proposed by KMT for this project, and they were generally performed at locations away from the Main Span bridge. The results of the ALDOT load tests may therefore not be representative of the soil conditions and pile sizes being considered for the main span foundations.

If conditions different from those considered in our analyses are encountered during the exploration program that will be completed during the final design phase and during construction, we should review our understanding of the subsurface conditions and reconsider our recommendations presented in this report, as appropriate.

6 MAIN SPAN BRIDGE FOUNDATIONS

General

We performed a series of axial resistance analyses on potential foundation types and sizes to support the transition and tiedown piers, and the main span pylons. In addition, we developed FB-MultiPier (FBMP) parameters for use by the structural designers to evaluate the lateral resistance of the foundations. In general, the purpose of this study was to provide preliminary design information to the structural engineers and to develop an estimate of the pile embedments and resistances based on the

available data. The structural designers with input from the KMT constructors used these results to develop suitable and cost-effective foundations.

Our analyses assume that the piles and shafts will be spaced a minimum of 3.0 foundation diameters, center-to-center, and that no drag loads act on the piles/shafts. We assume that the foundation construction and any required fill placement activities will be timed so that any adverse settlements that may occur as a result of the fill placement activities will occur prior to foundation installation. This assumption will be confirmed as the bridge design progresses.

Axial resistance analyses were performed for several PSCP sizes to support the transition and tie-down piers. Axial resistance analyses were also performed for 72-inch diameter driven steel pipe piles, and 72-inch and 96-inch-diameter drilled shafts to support the main span pylon foundations. Based on KMT's analyses using the results of our preliminary analyses, it was decided that 24-inch square piles will be used to support both the east and west transition and tiedown piers, and that 72-inch diameter driven steel pipe piles would be used to support the main span pylons. As a result, axial resistance plots developed for the other foundation sizes and types are not included in this memo, as these foundations are no longer being considered by KMT for support of the Main Span bridge.

Assumed Resistance Factor

Per Section 10.4.1.2 of the Technical Provisions (TP), the factored resistance of the piles shall depend upon the level of dynamic and static testing accomplished on production piles. To use the highest RF, 0.8, AASHTO and the TPs require that the driving criteria be established by a successful static load test of at least one pile per site condition and dynamic testing of at least two piles per site condition, but no less than 2% of the production piles. Table 10-3 of the TPs increases the minimum dynamic testing frequency to 5% of the production piles for concrete prestressed or post-tensioned piles greater than 36 inches in size. If a static load test is not performed, AASHTO indicates that a RF equal to 0.65 may be used provided that dynamic testing of at least two piles per site condition, but no less than 2% of the production piles is performed. Considering that the TPs specify this minimum level of dynamic testing, a RF equal to 0.65 is the lowest RF considered in our analyses.

As indicated in Section 3, the nominal resistance of the pile determined by static testing in the ALDOT load testing program was greater for the six piles tested using either a conventional load frame or Statnamic load testing, than that measured in the PDA/CAPWAP (dynamic) analyses. The resistance of the PSCP determined by the dynamic testing (greatest resistance of the multiple restrikes) varied between about 60 and 86%, with an average of 76% of the resistance estimated from the static/Statnamic load testing considering the Davisson failure criteria. As a result, for estimating the pile embedments using a RF equal to 0.65 because only dynamic testing would be performed during production pile installation, it was decided to use 90% of the RF, 0.585 ($0.65 \times 0.90 = 0.585$), considering the reduced resistance that may be determined using dynamic testing only. As a result, the pile resistances and the corresponding estimated pile embedments assume RFs equal to 0.585 and 0.80. The reduction in pile length considering a RF equal to 0.80 (assumes that a static load test is performed) can be considered by the KMT Team to determine if performing a static load test is beneficial to the

project by reducing the pile footage required for the project and/or by reducing the PSCP length required to achieve the factored axial resistance to the preferred 120 feet.

Recommendations for a load testing program are being developed and summarized in a separate report.

Transition and Tiedown Pier Foundation Support

We performed axial resistance analyses for 24-, 30-, and 36-inch-square PSCPs to support the transition and tiedown piers using the results of borings WHLA-03, HLA-12, MB-02, and MB-02A. Note that the east transition and tiedown piers are located about midway between borings HLA-12 and MB-02/MB-02A. The subsurface conditions encountered in these borings vary, such that the estimated axial pile resistances at the east transition and tiedown pier locations may vary from those estimated for the available borings.

As requested by the KIE structural designers, for each axial resistance analysis performed for the driven PSCPs, we assumed the following factored axial compression demands for the piles:

- 24-inch square – 939 kips,
- 30-inch square – 1,400 kips, and
- 36-inch square – 1,760 kips.

We understand that these loads correspond to the Strength Limit State. We used these top of pile loads in our axial resistance analyses. These factored axial compression demands correspond to the approximate maximum structural capacity of the PSCP allowed by ALDOT assuming a concrete compressive strength equal to 6,000 psi. These values include an additional phi factor equal to 0.65 relative to the maximum structural capacity allowed by the American Association of State Highway and Transportation Officials (AASHTO). We understand that per RFI 015, ALDOT has agreed to increase the phi factor from 0.65 to 1.0, such that the maximum structural capacity allowed by ALDOT for this project is equal to that allowed by AASHTO. We estimated the pile embedments assuming two different resistance factors (RF), 0.585 and 0.80.

In addition to these analyses, we understand that KMT would prefer to limit the pile length to about 120 feet. As a result, we also evaluated the estimated nominal axial compression resistance for a pile length equal to 120 feet for 24-, 30-, and 36-inch square piles. The factored axial compression resistance was then estimated considering geotechnical RFs equal to 0.585 and 0.80.

Based on KMT's analyses, it was decided that 24-inch square piles will be used to support both the east and west transition and tiedown piers.

Main Span Bridge Pylon Foundation Support

We performed axial resistance analyses for 72-inch diameter driven steel pipe piles, and 72-inch- and 96-inch-diameter drilled shafts to support the main span pylon foundations using the results of borings MB-01, MB-02, and MB-02A.

The axial resistance analyses performed for the 72-inch diameter driven steel pipe piles evaluated the nominal resistance of the piles for the depth (about 300-feet) of the borings (MB-01, MB-02, and MB-02A) located near the pylon foundations. The structural designers used the results of these analyses in conjunction with input from the KMT constructors to develop an appropriate pylon foundation design. Two geotechnical RFs, 0.585 and 0.80, were considered in the evaluation of the factored axial resistance.

In addition to the driven pile foundations, we also evaluated the axial resistance of 72-inch- and 96-inch-diameter drilled shafts to support the main span pylon foundations. The axial resistance evaluations were performed for a shaft embedment of 175 feet, which was considered to be the maximum shaft embedment that KMT constructors would install without excessive risk. We recommended that the KIE structural designers consider two different RFs, 0.50 and 0.70. A RF equal to 0.70 assumes that a static load test is performed to confirm the drilled shaft resistances.

Based on KMT's analyses, it was decided that 72-inch diameter driven steel pipe piles will be used to support the main span pylons.

7 RESULTS OF ANALYSES

FB-MultiPier Parameters

Engineering properties of the soil were developed for the purposes of performing deep foundation analyses based on a review of available logs of borings, published correlations between SPT N-values and soil material properties, results of laboratory testing accomplished on samples retrieved from the available explorations accomplished along the project alignment, the results of the ALDOT load test program, and our experience on similar projects with similar subsurface conditions.

Our recommended axial soil input models for FBMP analyses are in the form of custom (or user-defined) side and base resistance load transfer curves, also referred to as T-z and Q-z curves, respectively, which describe mobilized side ("T") and base ("Q") resistance for a corresponding foundation displacement ("z").

We recommend that the built-in FBMP lateral soil models be used by the structural designers for the FBMP analyses, which require the input of soil strength and stiffness properties. For cohesionless soil layers, the recommended internal angle of friction (ϕ') and modulus of subgrade reaction (k) input values are based on published literature correlations to SPT N-value in addition to our experience in similar soil and project conditions. For cohesive soil layers, the recommended strain at 50% maximum stress (ϵ_{50}) input values are also based on published literature correlations. In general, to develop the recommended undrained shear strength (S_u) input properties for cohesive soil layers, we first considered the results of available laboratory triaxial compression test data. In the absence of triaxial compression test data, we used the available natural water content results and correlations of average SPT N-value data to estimate S_u input values.

Our recommended FBMP soil input parameters are presented in Tables 1 and 2. Table 3 presents our recommended custom T-z and Q-z curves. Our recommended lateral soil models presented in Tables 1 and 2 represent lateral soil resistance for a single foundation element or pile. For groups of piles, the mobilized lateral soil resistance is dependent on the number, proximity, and diameter/width of adjacent piles. At center-to-center pile spacings less than 6.0 pile diameters/widths, the pile group efficiency is reduced, and reduction factors, or P-multipliers less than 1.0, should be applied to the lateral soil models. The reduction factors may vary within a pile group, depending on the pile spacing, pile width/diameter, position of a pile within the group, the direction of loading, and the total number of piles in a group. At this stage of the project, we recommend that the P-multipliers generated by the FBMP program be used for group analysis.

Axial Resistance Analyses

The axial resistance plots for the driven, 24-inch square PSCP and 72-inch diameter steel pipe piles are presented in Appendix D. Axial resistance plots for the 30-inch and 36-inch square piles, and the drilled shafts are not included in Appendix D, because these foundations are no longer being considered by KMT for support of the Main Span bridge. The axial resistance plots with appropriate RFs were used by the structural designers with input from the KMT constructors to develop appropriate foundations to support the Main Span bridge.

The KMT Team did not evaluate potential settlements and/or vibrations as a result of the pile driving activities. Depending upon the proximity of the adjacent infrastructure to the pile driving activities, it may not be practical to drive displacement PSCPs without exceeding the settlement and vibration limits, unless mitigation measures such as predrilling, jetting, and/or driving the piles within a sheet pile enclosure are implemented. It should be noted that the axial resistance plots provided in this memo assume that the piles will be driven with impact hammers. If jetting and/or predrilling are used to install the piles, the actual pile lengths driven will likely be greater than those provided in this report to achieve the required pile resistance.

The KMT Team should drill additional borings to evaluate the subsurface conditions to limit risks associated with pile embedments and resistances for the Main Span bridge. We recommend that a foundation load testing program be developed and implemented prior to final design to confirm the design parameters used in estimating pile embedments. In addition, the reduction in foundation length considering the higher RF that can be used if a load test is performed can be considered by the KMT Team to determine if performing additional static load tests is cost effective and beneficial to the project. The higher RF will reduce the foundation footage required for the project and will increase the probability that the required axial pile resistance can be achieved with the preferred 120-foot pile length.

Table 1 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Tower Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven Steel Pipe Pile	Drilled Shaft	Driven Steel Pipe Pile
		(feet)	(feet)			(feet)	(feet)						(pcf)	(-)	(ksi)	(deg)	(pci)	(psf)	(-)	(ksf)	(ksf)	(ksf)	(ksf)
West Tower	MB-01	2.9	-0.2	Overburden	SM	2.9	-0.2	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.31	31	65	-	-	0.34	0.15	-	-
				Overburden	GP-GM	-0.2	-14.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.25	3.56	33	20	-	-	0.37	0.17	-	-
				Overburden	SP	-14.1	-24.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.82	32	40	-	-	0.65	0.29	-	-
				Overburden	SP	-24.1	-29.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	125	0.35	2.88	37	85	-	-	1.1	0.5	-	-
				Overburden	SP	-29.1	-44.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.96	33	50	-	-	0.92	0.41	-	-
				Overburden	GP	-44.1	-47.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	4.43	36	40	-	-	0.91	0.41	-	-
				Overburden	GP	-47.1	-54.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.3	4.27	35	30	-	-	0.84	0.39	-	-
				Upper Sand with Clay/Silt Interbeds	SP-SM	-54.1	-64.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.76	35	70	-	-	1.36	0.63	32	64
				Upper Sand with Clay/Silt Interbeds	SP-SM	-64.1	-77.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	2.65	1.19	60	144
				Upper Sand with Clay/Silt Interbeds	SP-SM	-77.1	-84.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.57	34	65	-	-	1.47	0.66	26	52
				Lower Sand with Clay/Silt Interbeds	CH	-84.1	-99.1	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.4	2.19	-	-	1,750	0.008	0.98	0.89	16	16
				Lower Sand with Clay/Silt Interbeds	SP/SC-SM	-99.1	-124.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	3.03	1.38	60	144
				Lower Sand with Clay/Silt Interbeds	CH	-124.1	-129.1	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	3.29	-	-	2,750	0.007	1.53	1.39	25	25
				Lower Sand with Clay/Silt Interbeds	SP-SM	-129.1	-144.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.13	36	85	-	-	2.46	1.1	52	87
				Lower Sand with Clay/Silt Interbeds	SP-SM/SC	-144.1	-184.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	3.81	1.75	110	144
				Clay with Sand/Silt Interbeds	CL	-184.1	-211.1	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	5,100	0.004	2.34	2.55	45	45
				Basal Silt/Sand with Clay Interbeds	SM	-211.1	-222.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Basal Silt/Sand with Clay Interbeds	SM	-222.1	-252.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.35	1.8	35	75	-	-	2.99	1.34	43	72
				Basal Silt/Sand with Clay Interbeds	SP-SM	-252.1	-297.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	4	2	110	144

Table 1 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Tower Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven Steel Pipe Pile	Drilled Shaft	Driven Steel Pipe Pile
		(feet)	(feet)			(feet)	(feet)						(pcf)	(-)	(ksi)	(deg)	(pci)	(psf)	(-)	(ksf)	(ksf)	(ksf)	(ksf)
East Tower	MB-02	7.4	2.7	Overburden	SP	7.4	2.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.74	32	55	-	-	0.38	0.17	-	-
				Overburden	SP	2.7	-4.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.66	31	30	-	-	0.53	0.24	-	-
				Overburden	SP-SM	-4.6	-48.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.25	0.84	29	15	-	-	0.51	0.24	-	-
				Overburden	SP	-48.6	-60.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.62	31	30	-	-	0.87	0.4	-	-
				Upper Sand with Clay/Silt Interbeds	SP/SP-SM	-60.6	-84.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.26	37	90	-	-	1.85	0.85	46	93
				Lower Sand with Clay/Silt Interbeds	ML	-84.6	-89.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.57	27	35	-	-	1.01	0.45	14	28
				Lower Sand with Clay/Silt Interbeds	SP-SM	-89.6	-119.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.63	38	105	-	-	2.41	1.07	55	110
				Clay with Sand/Silt Interbeds	ML	-119.6	-132.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	0.87	31	75	-	-	1.76	0.8	33	67
				Clay with Sand/Silt Interbeds	CL/CL-ML	-132.6	-144.6	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	3.23	-	-	2,700	0.007	1.5	1.36	24	24
				Clay with Sand/Silt Interbeds	SM	-144.6	-159.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.62	1.62	27	27
				Clay with Sand/Silt Interbeds	CL	-159.6	-164.6	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.07	-	-	3,400	0.004	1.85	1.72	31	31
				Clay with Sand/Silt Interbeds	SM	-164.6	-174.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.95	1.82	38	38
				Clay with Sand/Silt Interbeds	CL	-174.6	-217.6	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	4,950	0.004	2.32	2.49	44	44
				Basal Silt/Sand with Clay Interbeds	ML	-217.6	-227.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	1.02	32	90	-	-	2.66	1.26	44	88
				Basal Silt/Sand with Clay Interbeds	SM	-227.6	-247.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.76	34	70	-	-	2.83	1.19	39	64
				Basal Silt/Sand with Clay Interbeds	CL	-247.6	-257.6	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	120	0.45	4.79	-	-	4,100	0.005	2.08	2.06	37	37
				Basal Silt/Sand with Clay Interbeds	SM	-257.6	-292.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144

Table 1 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Tower Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven Steel Pipe Pile	Drilled Shaft	Driven Steel Pipe Pile
		(feet)	(feet)										(pcf)	(-)	(ksi)	(deg)	(pci)	(psf)	(-)				
East Tower	MB-02A	-2.0	-2.0	Overburden	SC/SM	-2.0	-29.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	110	0.25	0.53	26	1	-	-	0.08	0.04	-	-
				Overburden	SP	-29.0	-50.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.25	1.36	30	20	-	-	0.5	0.22	-	-
				Upper Sand with Clay/Silt Interbeds	SP	-50.0	-74.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	2.5	35	70	-	-	1.17	0.52	32	64
				Upper Sand with Clay/Silt Interbeds	SP	-74.0	-84.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.82	32	40	-	-	1.02	0.45	16	33
				Lower Sand with Clay/Silt Interbeds	CH/CL	-84.0	-99.0	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	2.45	-	-	2,050	0.01	1.15	1.05	18	18
				Lower Sand with Clay/Silt Interbeds	SP-SM/SP	-99.0	-119.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	2.5	1.1	60	144
				Clay with Sand/Silt Interbeds	CL/CH	-119.0	-149.0	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	2.69	-	-	2,250	0.006	1.25	1.14	20	20
				Clay with Sand/Silt Interbeds	SM/SP-SM	-149.0	-166.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.11	1.38	97	144
				Clay with Sand/Silt Interbeds	CL	-166.0	-226.0	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	5,850	0.004	2.48	2.93	52	52
				Basal Silt/Sand with Clay Interbeds	SM	-226.0	-246.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.46	32	55	-	-	2.17	0.95	27	45
				Basal Silt/Sand with Clay Interbeds	CL	-246.0	-256.0	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	4.55	-	-	3,800	0.006	1.99	1.92	34	34
				Basal Silt/Sand with Clay Interbeds	SP-SM/SM	-256.0	-296.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Basal Silt/Sand with Clay Interbeds	ML	-296.0	-306.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.57	27	35	-	-	1.76	0.88	14	28
				Basal Silt/Sand with Clay Interbeds	CL	-306.0	-322.0	Cohesive	Stiff Clay w/o Free Water (Reese)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	5	-	-	4,350	0.004	2.16	2.18	39	39

NOTES:

deg = degrees; Elev. = elevation; GWT = groundwater table; ksf = kips per square foot; pcf = pounds per cubic foot; pci = pounds per cubic inch; psf = pounds per square foot; USCS = Unified Soil Classification Designation

Table 2 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Transition Pier Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven PSCP	Drilled Shaft	Driven PSCP
		(feet)	(feet)			(ksf)	(ksf)																
West Transition Pier	WHLA-03	7.1	1.1	Overburden	SM	7.1	4.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.74	34	110	-	-	0.43	0.37	-	-
				Overburden	SM/SP-SM	4.1	1.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.18	30	50	-	-	0.51	0.44	-	-
				Overburden	SP-SM	1.1	-4.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	110	0.25	0.6	27	5	-	-	0.23	0.2	-	-
				Overburden	CH	-4.9	-9.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	-	115	0.4	1.21	-	-	900	0.01	0.5	0.7	-	-
				Upper Sand with Clay/Silt Interbeds	SP	-9.9	-29.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.88	37	85	-	-	1.19	1.02	40	81
				Upper Sand with Clay/Silt Interbeds	SP	-29.9	-44.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	4.11	39	110	-	-	1.73	1.5	60	120
				Upper Sand with Clay/Silt Interbeds	SP-SM	-44.9	-84.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.79	35	75	-	-	1.61	1.38	33	66
				Lower Sand with Clay/Silt Interbeds	CH	-84.9	-89.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.4	1.67	-	-	1,300	0.006	0.74	0.77	12	12
				Lower Sand with Clay/Silt Interbeds	SC	-89.9	-101.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.46	32	55	-	-	1.59	1.34	22	45
				Lower Sand with Clay/Silt Interbeds	CH	-101.9	-104.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.4	2.36	-	-	1,900	0.006	1.05	0.95	17	17
				Lower Sand with Clay/Silt Interbeds	SP-SM/SM	-104.9	-129.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.17	2	103	144
				Clay with Sand/Silt Interbeds	CL/CH	-129.9	-147.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	120	0.45	3.77	-	-	3,150	0.005	1.74	1.58	28	28
				Clay with Sand/Silt Interbeds	SM	-147.9	-154.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Clay with Sand/Silt Interbeds	CL	-154.9	-169.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.19	-	-	3,500	0.004	1.89	1.77	31	31
				Clay with Sand/Silt Interbeds	SP-SM/SM	-169.9	-184.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Clay with Sand/Silt Interbeds	CL	-184.9	-216.9	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	5,050	0.004	2.33	2.53	45	45
				Basal Silt/Sand with Clay Interbeds	ML	-216.9	-226.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.53	27	30	-	-	1.57	1.29	12	24
				Basal Silt/Sand with Clay Interbeds	SM	-226.9	-247.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.25	31	40	-	-	2.12	1.82	19	32
				Basal Silt/Sand with Clay Interbeds	SP-SM/SM	-247.9	-292.9	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144

Table 2 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Transition Pier Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven PSCP	Drilled Shaft	Driven PSCP
		(feet)	(feet)			(ksf)	(ksf)																
East Transition Pier	HLA-12	16.3	15.1	Overburden	SP	16.3	15.1	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.77	32	55	-	-	0.2	0.17	-	-
				Overburden	SP	15.1	-0.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	2.12	33	60	-	-	0.51	0.43	-	-
				Overburden	CH	-0.7	-5.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	-	115	0.4	1.5	-	-	1,150	0.009	0.63	0.76	-	-
				Overburden	SP	-5.7	-36.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.75	32	40	-	-	0.75	0.64	-	-
				Upper Sand with Clay/Silt Interbeds	SP	-36.7	-46.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	2	33	50	-	-	1.09	0.92	21	42
				Upper Sand with Clay/Silt Interbeds	SP	-46.7	-70.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	3.62	38	100	-	-	1.86	1.59	52	104
				Upper Sand with Clay/Silt Interbeds	SP-SM	-70.7	-87.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	3.11	2	60	144
				Lower Sand with Clay/Silt Interbeds	CH	-87.7	-95.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	120	0.4	2.36	-	-	1,900	0.005	1.07	0.97	17	17
				Lower Sand with Clay/Silt Interbeds	ML	-95.7	-100.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.59	28	40	-	-	1.18	0.97	15	31
				Lower Sand with Clay/Silt Interbeds	SP-SM	-100.7	-130.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	3.63	2	110	144
				Clay with Sand/Silt Interbeds	CL	-130.7	-147.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	4,300	0.004	2.14	2.15	38	38
				Clay with Sand/Silt Interbeds	CL	-147.7	-157.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	4,000	0.004	2.05	2	36	36
				Clay with Sand/Silt Interbeds	SP	-157.7	-167.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	4.11	40	125	-	-	4	2	110	144
				Clay with Sand/Silt Interbeds	CL	-167.7	-197.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	5,250	0.004	2.38	2.63	47	47
				Clay with Sand/Silt Interbeds	SM	-197.7	-207.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Clay with Sand/Silt Interbeds	CL	-207.7	-217.7	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	120	0.45	4.13	-	-	3,450	0.005	1.86	1.74	31	31
				Basal Silt/Sand with Clay Interbeds	SM	-217.7	-233.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.76	34	70	-	-	2.86	2	39	64

Table 2 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Transition Pier Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven PSCP	Drilled Shaft	Driven PSCP
		(feet)	(feet)			(ksf)	(ksf)																
East Transition Pier	MB-02	7.4	2.7	Overburden	SP	7.4	2.7	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.74	32	55	-	-	0.38	0.33	-	-
				Overburden	SP	2.7	-4.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.66	31	30	-	-	0.53	0.45	-	-
				Overburden	SP-SM	-4.6	-48.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.25	0.84	29	15	-	-	0.51	0.43	-	-
				Overburden	SP	-48.6	-60.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	120	0.3	1.62	31	30	-	-	0.87	0.77	-	-
				Upper Sand with Clay/Silt Interbeds	SP/SP-SM	-60.6	-84.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.26	37	90	-	-	1.85	1.56	46	93
				Lower Sand with Clay/Silt Interbeds	ML	-84.6	-89.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.57	27	35	-	-	1.01	0.84	14	28
				Lower Sand with Clay/Silt Interbeds	SP-SM	-89.6	-119.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	2.63	38	105	-	-	2.41	2	55	110
				Clay with Sand/Silt Interbeds	ML	-119.6	-132.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	0.87	31	75	-	-	1.76	1.52	33	67
				Clay with Sand/Silt Interbeds	CL/CL-ML	-132.6	-144.6	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	3.23	-	-	2,700	0.007	1.5	1.36	24	24
				Clay with Sand/Silt Interbeds	SM	-144.6	-159.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.62	2	27	27
				Clay with Sand/Silt Interbeds	CL	-159.6	-164.6	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.07	-	-	3,400	0.004	1.85	1.72	31	31
				Clay with Sand/Silt Interbeds	SM	-164.6	-174.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.95	2	38	38
				Clay with Sand/Silt Interbeds	CL	-174.6	-217.6	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	4,950	0.004	2.32	2.49	44	44
				Basal Silt/Sand with Clay Interbeds	ML	-217.6	-227.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	125	0.35	1.02	32	90	-	-	2.66	2	44	88
				Basal Silt/Sand with Clay Interbeds	SM	-227.6	-247.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.76	34	70	-	-	2.83	2	39	64
				Basal Silt/Sand with Clay Interbeds	CL	-247.6	-257.6	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	120	0.45	4.79	-	-	4,100	0.005	2.08	2.06	37	37
				Basal Silt/Sand with Clay Interbeds	SM	-257.6	-292.6	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144

Table 2 - Recommended Soil Properties and Parameters for FB-MultiPier Analyses, Main Span Bridge Transition Pier Foundations

Subsurface Soil Conditions								Soil Design Parameters															
Foundation Location	Nearby Exploration	Ground Surface Elev. at Boring Location	GWT Elev.	Generalized Stratigraphy Beneath Ground Surface Elev. at Boring Location				Soil Type	Lateral Model	Axial Model	Torsional Model	Tip Model	Total Unit Weight, γ	Poisson's Ratio, ν	Shear Modulus, G	Internal Angle of Friction, φ	Initial Modulus of Subgrade Reaction, k	Undrained Shear Strength, S _u	Strain at 50% Maximum Stress, ε ₅₀	Nominal (Ultimate) Unit Skin Friction / Torsional Shear Stress, T _{ult}		Nominal (Ultimate) Unit Tip Resistance, Q _{ult}	
				Soil Layer	USCS	Top Elev.	Bottom Elev.													Drilled Shaft	Driven PSCP	Drilled Shaft	Driven PSCP
		(feet)	(feet)			(feet)	(feet)						(ksf)	(ksf)	(ksf)	(ksf)							
East Transition Pier	MB-02A	-2.0	-2.0	Overburden	SC/SM	-2.0	-29.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	110	0.25	0.53	26	1	-	-	0.08	0.07	-	-
				Overburden	SP	-29.0	-50.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	-	115	0.25	1.36	30	20	-	-	0.5	0.42	-	-
				Upper Sand with Clay/Silt Interbeds	SP	-50.0	-74.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	2.5	35	70	-	-	1.17	0.99	32	64
				Upper Sand with Clay/Silt Interbeds	SP	-74.0	-84.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.82	32	40	-	-	1.02	0.85	16	33
				Lower Sand with Clay/Silt Interbeds	CH/CL	-84.0	-99.0	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	2.45	-	-	2,050	0.01	1.15	1.05	18	18
				Lower Sand with Clay/Silt Interbeds	SP-SM/SP	-99.0	-119.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	40	125	-	-	2.5	2	60	144
				Clay with Sand/Silt Interbeds	CL/CH	-119.0	-149.0	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	2.69	-	-	2,250	0.006	1.25	1.14	20	20
				Clay with Sand/Silt Interbeds	SM/SP-SM	-149.0	-166.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	3.11	2	97	144
				Clay with Sand/Silt Interbeds	CL	-166.0	-226.0	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	4.79	-	-	5,850	0.004	2.48	2.93	52	52
				Basal Silt/Sand with Clay Interbeds	SM	-226.0	-246.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	120	0.3	1.46	32	55	-	-	2.17	1.9	27	45
				Basal Silt/Sand with Clay Interbeds	CL	-246.0	-256.0	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	115	0.45	4.55	-	-	3,800	0.006	1.99	1.92	34	34
				Basal Silt/Sand with Clay Interbeds	SP-SM/SM	-256.0	-296.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	130	0.35	2.83	39	125	-	-	4	2	110	144
				Basal Silt/Sand with Clay Interbeds	ML	-296.0	-306.0	Cohesionless	Sand (Reese)	Cohesionless Custom T-z Curve	Hyperbolic	Cohesionless Custom Q-z Curve	115	0.3	0.57	27	35	-	-	1.76	1.59	14	28
				Basal Silt/Sand with Clay Interbeds	CL	-306.0	-322.0	Cohesive	Clay (Stiff, without free water)	Cohesive Custom T-z Curve	Hyperbolic	Cohesive Custom Q-z Curve	125	0.45	5	-	-	4,350	0.004	2.16	2.18	39	39

NOTES:

deg = degrees; Elev. = elevation; GWT = groundwater table; ksf = kips per square foot; pcf = pounds per cubic foot; pci = pounds per cubic inch; PSCP = prestressed concrete pile; psf = pounds per square foot; USCS = Unified Soil Classification System Designation

Table 3 - Recommended Custom T-z and Q-z Curves for FB-MultiPier Analyses, Main Span Bridge Foundations

Drilled Shafts ¹								Driven Piles ²							
Cohesionless Soil				Cohesive Soil				Cohesionless Soil				Cohesive Soil			
Custom T-z Curve ³		Custom Q-z Curve ³		Custom T-z Curve ³		Custom Q-z Curve ³		Custom T-z Curve ³		Custom Q-z Curve ³		Custom T-z Curve ³		Custom Q-z Curve ³	
z / D	T / T _{ult}	z / D	Q / Q _{ult}	z / D	T / T _{ult}	z / D	Q / Q _{ult}	z	T / T _{ult}	z / D	Q / Q _{ult}	z / D	T / T _{ult}	z / D	Q / Q _{ult}
(-)	(-)	(-)	(-)	(-)	(-)	(-)	(-)	(inch)	(-)	(-)	(-)	(-)	(-)	(-)	(-)
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0.00125	0.4	0.01	0.31	0.0008	0.42	0.0042	0.3	0.1	1	0.002	0.25	0.0016	0.3	0.002	0.25
0.0022	0.6	0.02	0.56	0.0015	0.65	0.0092	0.57	12	1	0.013	0.5	0.0031	0.5	0.013	0.5
0.0035	0.8	0.025	0.67	0.00225	0.79	0.0145	0.72	-	-	0.042	0.75	0.0057	0.75	0.042	0.75
0.0042	0.86	0.032	0.784	0.0029	0.855	0.02	0.81	-	-	0.073	0.9	0.008	0.9	0.073	0.9
0.00585	0.93	0.04	0.882	0.0038	0.91	0.025	0.87	-	-	0.1	1	0.01	1	0.1	1
0.0084	0.974	0.05	1	0.0055	0.96	0.0315	0.92	-	-	-	-	0.02	1	-	-
0.012	0.976	0.1	1	0.0083	0.968	0.042	0.957	-	-	-	-	0.1	1	-	-
0.05	1	-	-	0.05	1	0.05	1	-	-	-	-	-	-	-	-
0.1	1	-	-	0.1	1	0.1	1	-	-	-	-	-	-	-	-

NOTES:

- 1 Drilled shaft custom T-z and Q-z curve recommendations are based on AASHTO LRFD BDS (2020) Figures 10.8.2.2.2-1 through 10.8.2.2.2-4.
- 2 Driven pile custom T-z and Q-z curve recommendations are based on API Recommended Practice 2A-LRFD (1993) Sections G.7.2 and G.7.3 axial load transfer curve recommendations.
- 3 D = foundation diameter / width
T = mobilized unit skin friction
T_{ult} = nominal (ultimate) unit skin friction (See Tables 1 and 2)
Q = mobilized unit tip resistance
Q_{ult} = nominal (ultimate) unit tip resistance (See Tables 1 and 2)
z = foundation displacement




Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama

SITE PLAN

SUBSURFACE UNITS

- An upper granular layer consisting of medium dense, silty sand with occasional soft clay layers (some of this material is embankment fill).
- As the alignment extends to the east towards Mobile Bay, this granular layer transitions to very soft, low and high plasticity Clay.
- A granular layer consisting of loose to dense sand and silty sand.
- Interbedded soft to medium stiff, clay and silt and medium dense to very dense, silty sand.
- Stiff to hard, low to high plasticity clay with interbedded sand and silt.
- Medium dense to very dense sandy silt and silt.

EXPLORATION LEGEND



RELATIVE DENSITY / CONSISTENCY

COARSE-GRAINED SOILS		FINE-GRAINED/COHESIVE SOILS	
N, SPT, BLOWS/FT.	RELATIVE DENSITY	N, SPT, BLOWS/FT.	RELATIVE CONSISTENCY
0 - 4	Very loose	<2	Very soft
4 - 10	Loose	2 - 4	Soft
10 - 30	Medium dense	4 - 8	Medium stiff
30 - 50	Dense	8 - 15	Stiff
Over 50	Very dense	15 - 30	Very stiff
		Over 30	Hard

UNIFIED SOIL CLASSIFICATION SYSTEM (From USACE Tech Memo 3-357)			SAMPLE TYPES
GP		SM	2" O.D. Split Spoon Sampler Driven with 140 lb. Hammer Shelby Tube
GW		SC	
GP-GM		CL	
GW-GM		ML	
GM		OL	
GC		CH	
SW		MH	
SP		OH	
SW-SM		PT	
SP-SM			
1. Dual Symbols (symbols separated by a hyphen) are used for soils with between 5% and 12% fines (such as SP-SM for slightly silty fine SAND) or when the liquid limit and plasticity index values plot in the CL-ML area of the plasticity chart. 2. Borderline symbols (symbols separated by a slash, i.e., CL/ML, silty CLAY/clayey SILT; GW/SW, sandy GRAVEL/gravelly SAND) indicate that the soil may fall into one of two possible basic groups, based on ASTM D 2488-93 Visual Manual Classification System. The graphic symbol of only the first group symbol is shown on the profile.			

NOTES

1. Subsurface contacts should be considered approximate. Variations between the profile and actual conditions are likely to exist.
2. Groundwater levels may fluctuate seasonally and may have changed since the last shown reading. Groundwater fluctuations should be expected.
3. N > 100 is shown for samples where refusal was encountered or samples where N-values exceed 100 blows/foot.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

GENERALIZED
SUBSURFACE PROFILE
LEGEND AND NOTES


September 2023

110704-023

Kiewit | Massman | Traylor
a joint venture

FIG. 2
Sheet 1 of 2

Filename: C:\Users\jrs\CAD Group\Dropbox\UDrive\SEA\110704\023\110704-023 ALDOT Subsurface Profile.dwg Layout: Bridge Date: 09-07-2023 Login: JRS



NOTE
See Figure 1, Sheet 1 of 2 for profile legend and notes.

Alabama Department of Transportation I-10 Mobile River Bridge Project Mobile County, Alabama	
GENERALIZED SUBSURFACE PROFILE	
September 2023	110704-023
Kiewit Massman Traylor a joint venture	FIG. 2 Sheet 2 of 2

APPENDIX A

Exploration Results Provided by ALDOT

Contents:

- Thompson Boring Logs
 - HLA-12
 - HLA-13
 - MB-01
 - MB-02
 - MB-02A
 - TH-13
 - WHLA-03

KEY TO SYMBOLS

PROJECT NAME I-10 Mobile River Bridge and Bayway

CLIENT ALDOT

ALDOT PROJECT NO: DPI-0030(005)

TE PROJECT NO: 15-1101-0228

PROJECT LOCATION Baldwin, Baldwin

LITHOLOGIC SYMBOLS



ASPHALT: Asphalt



AUGER



CH: USCS High Plasticity Clay



CL: USCS Low Plasticity Clay



CL-ML: USCS Low Plasticity Silty Clay



CONCRETE: Concrete



GM: USCS Silty Gravel



GP: USCS Poorly-graded Gravel



GP-GM: USCS Poorly-graded Gravel with Silt



GW: USCS Well-graded Gravel



MH: USCS Elastic Silt



ML: USCS Silt



SC: USCS Clayey Sand



SC-SM: USCS Clayey Sand



SM: USCS Silty Sand



SP: USCS Poorly-graded Sand

SAMPLER TYPE

SS - Split Spoon

T - Shelby Tube

DCP - Dynamic Cone Penetrometer

AC - Auger Cuttings

GB - Grab Bag

NQ - Rock Core

GROUNDWATER LEGEND

▽ Delayed Groundwater Level

▼ Groundwater Level at TOB (Time of Boring). Water levels at the time of boring may have not been obtained due to mud rotary drilling techniques.

N.E. - Not Encountered

N.O. - Not Obtained

ABBREVIATIONS

LL - LIQUID LIMIT (%)
PL - PLASTIC LIMIT (%)
PI - PLASTIC INDEX (%)
NMC - MOISTURE CONTENT (%)
DD - DRY DENSITY (PCF)
NP - NON PLASTIC

%#200 - PERCENT PASSING NO. 200 SIEVE
PP - POCKET PENETROMETER (TSF)
TV - TORVANE
UC - UNCONFINED COMPRESSION



RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	SPT N VALUE (blows / foot)	PL	MC	LL	FINES CONTENT (%)
0.0														
15.0		Approximately 17 inches of topsoil. Loose, dry, tan, medium grained, POORLY GRADED SAND (SP)		0.0	SS-1	3	4	5	9	●				
		Medium dense, dry, white and tan, fine to medium grained, with trace gravel, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=3.1		1.5	SS-2	8	6	8	14	●				
5.0		Loose, moist, tan		3.0	SS-3	3	6	4	10	●				
		Medium dense, wet		4.5	SS-4	8	10	12	22	●				
10.0		Very loose, fine to medium grained		6.0	SS-5	1	1	3	4	●				
				8.5										
10.0		Medium dense, wet, tan, medium to fine and coarse grained, POORLY GRADED SAND with GRAVEL (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=11.3			SS-6	4	7	7	14	●				
5.0		%#200=2.5												
15.0		Medium dense, tan and pale brown		13.5	SS-7	5	6	9	15	●				
0.0														
20.0		Firm, wet, gray, with trace wood, GRAVELLY FAT CLAY (CH)		18.5	SS-8	9	3	3	6	●				
-5.0														
25.0		Loose, wet, gray, fine to medium grained, POORLY GRADED SAND (SP)		23.5	SS-9	4	5	5	10	●				
-10.0														
30.0		Loose, medium to fine grained		28.5	SS-10	3	4	4	8	●				

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
30.0										
	-15.0									
35.0		Loose, wet, brown, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=22.3 % #200=3.8		33.5	SS-11	3	3	4	7 X	●
	-20.0									
40.0		Loose, pale brown, medium to fine grained		38.5	SS-12	4	4	4	8	●
	-25.0									
45.0		Loose, dark brown		43.5	SS-13	3	4	6	10	●
	-30.0									
50.0		Loose, brown		48.5	SS-14	3	4	5	9	●
	-35.0									
55.0		Medium dense, wet, pale brown, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=23.6 % #200=4.5		53.5	SS-15	4	5	6	11 X	●
	-40.0									
60.0		Medium dense, white and pale brown		58.5	SS-16	5	5	8	13	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description: I-10 Mobile River Bridge and Bayway				County: Mobile	
Boring No.: HLA-12		Boring Location: 541+43.3		Offset: LT 45.4	Alignment: High Level Approach
ALDOT PE No.: DPI-0030(005)		TE Project No.: 15-1101-0228		Eng./Geo.: S.Howard	
Elev.: 16.3 ft.	Northing: 251274.32		Easting: 1801615.13	Date Started: 9/13/2017	
Total Depth: 250.0 ft.	Soil Depth: 250.0 ft.		Core Depth: 0.0 ft.	Date Completed: 9/18/2017	
Bore Hole Diameter (in): 4-inch		AASHTO / ASTM Sampling Methods: AASHTO T206 & T207			
Drill Machine: CME 550X		Drill Method: MR	Hammer Type: Automatic		Energy Ratio: 88%
Core Size: N/A		Driller: Thompson Eng	Groundwater: TOB	1.2 ft.	Delayed: 15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0										
	-45.0									
		Medium dense, pale brown		63.5	SS-17	10	14	15	29	●
65.0										
	-50.0									
		Dense		68.5	SS-18	16	18	20	38	●
70.0										
	-55.0									
		Medium dense, brown and pale brown		73.5	SS-19	11	11	13	24	●
75.0										
	-60.0									
		Dense, wet, white and pale brown, medium to fine grained, POORLY GRADED SAND (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=15.8 % #200=4.9		78.5	SS-20	14	17	14	31	▲ ○ ●
80.0										
	-65.0									
		Medium dense		83.5	SS-21	9	13	12	25	●
85.0										
	-70.0									
90.0		Very dense, wet, white and pale brown, fine to medium grained, with trace gravel, POORLY		88.5	SS-22	19	28	37	65	▲ ○ ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
90.0										10 20 30 40 50 60 70 80 90
	-75.0	GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=18.4 % _{#200} =5.4								
		Very dense, pale brown, fine to medium grained		93.5	SS-23	15	40	50	90	
95.0										
	-80.0	Very dense		98.5	SS-24	21	32	37	69	
100.0										
	-85.0									
		Top of spoon: Medium dense, brown, with trace wood Bottom of spoon: Very stiff, wet, very dark gray, FAT CLAY (CH)		103.5	SS-25	17	8	9	17	
105.0										
	-90.0	Undisturbed sample obtained from 108.0 to 110.0 feet. Approximately 24 inches of recovery. Stiff, wet, gray, with trace sand, FAT CLAY (CH, A-7-6(79)), LL=97 PL=26 PI=71 NMC=36.6 % _{#200} =96.2		108.0	T-1					
110.0										
	-95.0	Stiff, wet, gray, SANDY SILT (ML, A-4(0)), LL=NP PL=NP PI=NP NMC=25.6 % _{#200} =50.1		113.5	SS-26	5	4	5	9	
115.0										
	-100.0									
120.0		Dense, wet, brown and gray, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM)		118.5	SS-27	15	17	22	39	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0										
	-105.0									
		Very dense, pale brown, medium to fine grained		123.5	SS-28	17	27	38	65	●
125.0										
	-110.0									
		Very dense		128.5	SS-29	21	36	40	76	●
130.0										
	-115.0									
		Very dense		133.5	SS-30	25	40	50	90	●
135.0										
	-120.0									
		Very dense, wet, pale brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=21.9 % _{#200} =6.3		138.5	SS-31	20	32	31	63	X▲ O●
140.0										
	-125.0									
		Very dense		143.5	SS-32	29	38	37	75	●
145.0										
	-130.0									
150.0		Very stiff, wet, bluish gray, with few sand, LEAN CLAY (CL, A-6(22)), LL=39 PL=15 PI=24 NMC=21.4		148.5	SS-33	9	11	17	28	X● O● X▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
150.0										
	-135.0	%#200=92.6								
155.0										
	-140.0									
160.0		Very stiff, wet, bluish gray, SANDY LEAN CLAY (CL, A-7-6(18)), LL=46 PL=15 PI=31 NMC=22.4 %#200=66.1		158.5	SS-34	9	13	16	29	X X ● X X ▲
	-145.0									
165.0										
	-150.0									
170.0		Hard		168.5	SS-35	13	22	32	54	●
	-155.0									
175.0										
	-160.0									
180.0		Very dense, wet, light gray, fine to medium grained, POORLY GRADED SAND (SP)		178.5	SS-36	44	50/5	X	50+	>>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
180.0										
	-165.0									
	-170.0									
185.0										
	-175.0	Undisturbed sample obtained from 188.0 to 190.0 feet. Approximately 24 inches of recovery. Hard, wet, gray, with few sand, LEAN CLAY (CL, A-6(11)), LL=29 PL=15 PI=14 NMC=20.4 %200=89.0		188.0	T-2					X O X ▲
190.0										
	-180.0									
195.0										
	-185.0	Hard, bluish gray, with few sand		198.5	SS-37	15	19	22	41	●
200.0										
	-190.0									
205.0										
	-190.0									
210.0		Hard, wet, bluish gray, SANDY LEAN CLAY (CL, A-6(5)), LL=32 PL=16 PI=16 NMC=19.8 %200=51.3		208.5	SS-38	15	14	18	32	X O ● ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
210.0										
	-195.0									
215.0										
	-200.0									
220.0		Very dense, wet, bluish gray, fine grained, SILTY SAND (SM)		218.5	SS-39	42	39	26	65	●
	-205.0									
225.0										
	-210.0									
230.0		Firm, wet, bluish gray, LEAN CLAY with SAND (CL, A-6(10)), LL=34 PL=19 PI=15 NMC=25.7 % _{#200} =74.0		228.5	SS-40	11	9	7	16	● X O X ▲
	-215.0									
235.0										
	-220.0									
240.0		Medium dense, wet, bluish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP		238.5	SS-41	12	11	11	22 X	● ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-12	Boring Location:	541+43.3	Offset:	LT 45.4	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	S.Howard
Elev.:	16.3 ft.	Northing:	251274.32	Easting:	1801615.13	Date Started:	9/13/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/18/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:			AASHTO T206 & T207		
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 1.2 ft.	Delayed:	15.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
240.0										
	-225.0	NMC=22.2 % $\#$ 200=31.0								
245.0										
	-230.0									
250.0		Medium dense, wet, gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=24.3 % $\#$ 200=23.3		248.5	SS-42	10	6	8	14 X	● ▲
		Boring Terminated at 250.0 feet.								

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	SPT N VALUE (blows / foot)	PL	MC	LL	FINES CONTENT (%)
0.0														
		Approximately 2.5 inches of asphalt and 10 inches of crushed aggregate.		1.0										
		Medium dense, dry, white and light tan, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=12.5 %200=2.8		2.5	SS-1	6	9	15	24					
		Medium dense, moist, white and tan		4.0	SS-2	8	11	10	21					
5.0	10.0	Medium dense, moist, white and tan, fine to medium grained, with trace gravel, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=15.9 %200=3.0		5.5	SS-3	5	9	10	19					
		Medium dense, tan and pale brown		7.0	SS-4	6	7	9	16					
		Medium dense		8.5	SS-5	5	6	8	14					
10.0	5.0	Medium dense, wet, pale brown			SS-6	5	7	7	14					
15.0	0.0	Very loose, wet, pale brown and gray, fine grained, SILTY SAND (SM, A-4(0)), LL=NP PL=NP PI=NP NMC=42.5 %200=43.9		13.5	SS-7	2	1	1	2					
20.0	-5.0	Undisturbed sample obtained from 18.0 to 20.0 feet. Approximately 24 inches of recovery. Medium dense, wet, dark brown, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=33.9 %200=25.3		18.0	T-1									
25.0	-10.0	Loose, wet, brown, fine grained, POORLY GRADED SAND (SP)		23.5	SS-8	3	4	5	9					
30.0	-15.0	Loose, fine to medium grained		28.5	SS-9	3	3	5	8					

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
30.0										10 20 30 40 50 60 70 80 90
35.0	-20.0	Loose, wet, dark brown, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=23.7 % _{#200} =5.2		33.5	SS-10	2	2	3	5 X ●	○
40.0	-25.0	Very loose, wet, dark brown, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=23.1 % _{#200} =5.5		38.5	SS-11	1	0	1	1 ● ▲	○
45.0	-30.0	Very loose, brown		43.5	SS-12	1	1	2	3 ●	
50.0	-35.0	Very loose, wet, dark brown, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=17.8 % _{#200} =34.3		48.5	SS-13	2	1	2	3 X ● ○ ▲	
55.0	-40.0	Stiff, wet, reddish brown and gray, SANDY SILTY CLAY (CL-ML, A-4(1)), LL=24 PL=17 PI=7 NMC=22.2 % _{#200} =53.2		53.5	SS-14	4	6	7	13 ● X ○ ▲	
60.0	-45.0	Dense, wet, bluish gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		58.5	SS-15	1	16	22	38 ●	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0										
65.0	-50.0	Dense, wet, pale brown and brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=26.0 % _{#200} =5.8		63.5	SS-16	11	15	18	33X▲	○●
70.0	-55.0	Dense, pale brown, with trace gravel		68.5	SS-17	12	14	17	31	●
75.0	-60.0	Medium dense, wet, white and pale gray, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=19.7 % _{#200} =9.1		73.5	SS-18	8	9	13	22X▲●	○●
80.0	-65.0	Dense, pale brown		78.5	SS-19	8	18	23	41	●
85.0	-70.0	Very dense		83.5	SS-20	18	24	28	52	●
90.0	-75.0	Very dense		88.5	SS-21	17	25	33	58	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0										
95.0	-80.0	Dense, wet, pale brown and light tan, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=20.8 % #200=3.9		93.5	SS-22	17	23	26	49X▲	○ ●
100.0	-85.0	Very soft, wet, dark gray, with trace wood and few sand, FAT CLAY (CH, A-7-5(39)), LL=68 PL=30 PI=38 NMC=47.2 % #200=89.4		98.5	SS-23	0	0	0	0 ●	X ○ X ▲
105.0	-90.0	Very stiff, wet, gray, fine to medium grained, SILTY SAND (SM)		103.5	SS-24	7	9	9	18 ●	
110.0	-95.0	Medium dense, wet, light gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=24.7 % #200=18.8		108.5	SS-25	6	6	15	21X●○	
115.0	-100.0	Dense, gray, with trace clay		113.5	SS-26	12	19	14	33 ●	
120.0	-105.0	Very dense, pale brown, medium to fine grained		118.5	SS-27	21	36	46	82 ●	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0										
125.0	-110.0	Very dense, wet, pale brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM)		123.5	SS-28	24	31	31	62	●
130.0	-115.0	Very dense, wet, pale brown, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=22.9 % #200=7.0		128.5	SS-29	27	40	44	84 X ▲ O	●
135.0	-120.0	Dense		133.5	SS-30	12	17	24	41	●
140.0	-125.0	Dense		138.5	SS-31	19	18	16	34	●
145.0	-130.0	Dense, wet, bluish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=22.8 % #200=27.2		143.5	SS-32	11	16	19	35 X O ▲ ●	●
150.0	-135.0	Dense, bluish gray and brown		148.5	SS-33	15	20	23	43	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD


HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.



LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	S.Howard		
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
180.0										
185.0	-170.0									
190.0	-175.0	Hard, wet, bluish gray, with few sand, LEAN CLAY (CL, A-6(18)), LL=34 PL=14 PI=20 NMC=20.4 % _{#200} =93.9		188.5	SS-36	0	14	17	31	X O ● X ▲
195.0	-180.0									
200.0	-185.0	Hard, wet, bluish gray and brown, SANDY LEAN CLAY (CL, A-6(7)), LL=28 PL=14 PI=14 NMC=17.5 % _{#200} =68.2		198.5	SS-37	13	15	18	33	X O X ● ▲
205.0	-190.0									
210.0	-195.0	Very dense, wet, bluish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP		208.5	SS-38	17	26	31	57	X ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	HLA-13	Boring Location:	544+74.9	Offset:	RT 27.7	Alignment:	High Level Approach
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	S.Howard
Elev.:	14.3 ft.	Northing:	251402.66	Easting:	1801928.72	Date Started:	9/19/2017
Total Depth:	250.0 ft.	Soil Depth:	250.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 8.5 ft.	Delayed:	7.8 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
210.0		NMC=21.4 % _{#200} =20.5								
215.0	-200.0									
220.0	-205.0	Very dense		218.5	SS-39	30	31	26	57	●
225.0	-210.0									
230.0	-215.0	Very stiff, wet, bluish gray, with trace sand, LEAN CLAY (CL, A-6(17)), LL=37 PL=20 PI=17 NMC=28.7 % _{#200} =97.1		228.5	SS-40	8	8	12	20	● ○ X ▲
235.0	-220.0									
240.0	-225.0	Medium dense, wet, bluish gray, fine grained, SILTY SAND (SM)		238.5	SS-41	10	9	7	16	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring

RECORD OF TEST BORING

Site Description: I-10 Mobile River Bridge and Bayway						County: Mobile	
Boring No.: HLA-13		Boring Location: 544+74.9		Offset: RT 27.7		Alignment: High Level Approach	
ALDOT PE No.: DPI-0030(005)			TE Project No.: 15-1101-0228			Eng./Geo.: S.Howard	
Elev.: 14.3 ft.		Northing: 251402.66		Easting: 1801928.72		Date Started: 9/19/2017	
Total Depth: 250.0 ft.		Soil Depth: 250.0 ft.		Core Depth: 0.0 ft.		Date Completed: 9/21/2017	
Bore Hole Diameter (in): 4-inch		AASHTO / ASTM Sampling Methods: AASHTO T206 & T207					
Drill Machine: CME 550X		Drill Method: MR		Hammer Type: Automatic		Energy Ratio: 88%	
Core Size: N/A		Driller: Thompson Eng		Groundwater: TOB 8.5 ft.		Delayed: 7.8 ft.	

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
240.0										10 20 30 40 50 60 70 80 90
245.0	-230.0									
250.0	-235.0	Dense, wet, bluish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=23.2 %#200=24.4		248.5	SS-42	11	15	17	32	▲ ●
		Boring Terminated at 250.0 feet.								

LEGEND

SAMPLER TYPE		DRILLING METHOD	
SS - Split Spoon	AC - Auger Cuttings	HSA - Hollow Stem Augers	MR - Mud Rotary Wash
T - Shelby Tube	GB - Grab Bag	SSA - Solid Stem Augers	RC - Rock Coring
DCP - Dynamic Cone Penetrometer	NQ - Rock Core	HA - Hand Auger	



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
0.0										10 20 30 40 50 60 70 80 90
		Loose, moist, dark brown, fine to coarse grained, SILTY SAND with GRAVEL (SM)		0.0	SS-1	4	4	4	8	●
	0.0	Medium dense, wet, dark brown, fine to medium grained, with wood, SILTY SAND with GRAVEL (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=57.0 % _{#200} =17.6		1.5	SS-2	4	5	7	12	●▲○
		Very loose, wet, dark brown, fine to coarse grained, POORLY GRADED GRAVEL with SILT and SAND (GP-GM)		3.0	SS-3	4	2	2	4	●
	5.0	Loose, most likely fall in		4.5	SS-4	2	2	5	7	●
	-5.0	Loose, most likely fall in		6.0	SS-5	3	3	3	6	●
		Very loose, most likely fall in		8.5	SS-6	2	1	1	2	●
	10.0									
	-10.0									
	15.0	Very loose, wet, dark brown, fine and coarse grained, POORLY GRADED GRAVEL with SILT and SAND (GP-GM, A-1-a(0)), LL=NP PL=NP PI=NP NMC=18.9 % _{#200} =10.9		13.5	SS-7	1	2	2	4	●▲○
	-15.0									
	20.0	Loose, wet, gray and brown, fine grained, POORLY GRADED SAND with GRAVEL (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=16.9 % _{#200} =4.7		18.5	SS-8	5	5	4	9	●▲○
	-20.0									
	25.0	Loose, dark brown and gray, fine to medium grained		23.5	SS-9	4	5	5	10	●
	-25.0									
	30.0	Medium dense, gray and light gray		28.5	SS-10	8	12	11	23	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
30.0										10 20 30 40 50 60 70 80 90
35.0	-30.0	Medium dense, wet, yellowish brown and brown, fine grained, POORLY GRADED SAND with GRAVEL (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=28.7 % _{#200} =3.4		33.5	SS-11	6	5	6	11	▲ ● ○
40.0	-35.0	Loose, with trace shells		38.5	SS-12	5	4	5	9	●
45.0	-40.0	Medium dense, wet, pale brown, fine to medium grained, with trace gravel, POORLY GRADED SAND (GP, A-1-a(0)), LL=NP PL=NP PI=NP NMC=22.2 % _{#200} =2.1		43.5	SS-13	4	6	8	14	▲ ● ○
50.0	-45.0	Loose, wet, pale brown, fine to medium grained, POORLY GRADED GRAVEL with SAND (GP, A-1-a(0)), LL=NP PL=NP PI=NP NMC=11.7 % _{#200} =3.1		48.5	SS-14	6	5	4	9	▲ ● ○
55.0	-50.0	Loose, light brown		53.5	SS-15	4	3	4	7	●
60.0	-55.0	Medium dense, wet, pale brown, fine to medium grained, POORLY GRADED SAND with SILT		58.5	SS-16	8	10	6	16	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
60.0										10 20 30 40 50 60 70 80 90
	-60.0	(SP-SM)								
65.0		Medium dense, wet, reddish brown and brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=19.3 % _{#200} =8.6		63.5	SS-17	6	8	12	20X	▲ ●
	-65.0									
70.0		Very dense, No Recovery		68.5	SS-18	35	50/5	X	50/5	>> ●
	-70.0									
75.0		Very dense, light brown		73.5	SS-19	12	28	24	52	●
	-75.0									
80.0		Very dense		78.5	SS-20	50	X	X	100+	>> ●
	-80.0									
85.0		Medium dense, wet, medium to fine grained, with trace gravel		83.5	SS-21	7	8	7	15	●
	-85.0									
90.0		Firm, moist, dark gray, FAT CLAY (CH) NOTE: Sample rods slipped through hoisting ring and		88.5	SS-22	0	0	5	5	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL ○ MC × LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0										
	-90.0	penetrated the first 12 inches of the sample length. Undisturbed sample obtained from 90.5 to 92.5 feet. Approximately 24 inches of recovery. Very stiff, moist, dark grayish brown, with trace sand, FAT CLAY with SAND (CH, A-7-6(23)), LL=52 PL=22 PI=30 NMC=40.1 %200=75.7 Firm		90.5	T-1					× — ○ — × ▲
	-95.0			93.5	SS-23	2	4	4	8	●
	-95.0			98.5	T-2					× — ○ — × ▲
	-100.0	Undisturbed sample obtained from 98.5 to 100.5 feet. Approximately 24 inches of recovery. Very stiff, moist, dark brown and light gray, FAT CLAY (CH, A-7-6(71)), LL=89 PL=28 PI=61 NMC=44.0 %200=99.4		103.5	SS-24	3	20	32	52	× × ○ ▲ ●
	-105.0	Very dense, wet, gray and light gray, fine grained, SILTY, CLAYEY SAND (SC-SM, A-2-4(0)), LL=21 PL=17 PI=4 NMC=23.9 %200=26.7		108.5	SS-25	14	20	28	48	●
	-110.0	Dense, wet, light gray, fine grained, POORLY GRADED SAND (SP)		113.5	SS-26	19	32	33	65	× ▲ ○ ●
	-115.0	Very dense, wet, light gray, fine to coarse and medium grained, POORLY GRADED SAND (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=19.5 %200=3.3		118.5	SS-27	9	15	23	38	●
	-120.0	Dense, fine grained, with trace gravel								

LEGEND

SAMPLER TYPE

SS - Split Spoon AC - Auger Cuttings
T - Shelby Tube GB - Grab Bag
DCP - Dynamic Cone Penetrometer NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers MR - Mud Rotary Wash
SSA - Solid Stem Augers RC - Rock Coring
HA - Hand Auger



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0										
	-120.0									
125.0		Very dense		123.5	SS-28	15	29	28	57	●
	-125.0									
130.0		Stiff, moist, gray, with trace sand, FAT CLAY (CH, A-7-6(34)), LL=53 PL=21 PI=32 NMC=23.7 % _{#200} =95.0		128.5	SS-29	4	5	4	9	● X O X ▲
	-130.0									
135.0		Medium dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		133.5	SS-30	3	7	19	26	●
	-135.0									
140.0		Medium dense		138.5	SS-31	15	14	15	29	●
	-140.0									
145.0		Medium dense		143.5	SS-32	7	8	10	18	●
	-145.0									
150.0		Very dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-2-4(0)), LL=NP		148.5	SS-33	28	34	27	61	X ▲ O ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
150.0		PL=NP PI=NP NMC=22.5 % _{#200} =10.5								
	-150.0									
155.0		Undisturbed sample obtained from 153.5 to 155.5 feet. Approximately 24 inches of recovery. With trace clay		153.5	T-3					
	-155.0									
160.0		Very dense		158.5	SS-34	26	24	32	56	●
	-160.0									
165.0		Very dense, wet, greenish gray, fine grained, with trace gravel, POORLY GRADED SAND with SILT (SP-SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=23.8 % _{#200} =11.5		163.5	SS-35	23	47	50+	100*	▲ ○ >>●
	-165.0									
170.0		Dense, wet, greenish gray, fine grained, CLAYEY SAND (SC, A-6(7)), LL=36 PL=13 PI=23 NMC=23.2 % _{#200} =48.4		168.5	SS-36	11	19	18	37	X ○ ● ▲
	-170.0									
175.0		Dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		173.5	SS-37	11	18	25	43	●
	-175.0									
180.0		Dense		178.5	SS-38	16	19	20	39	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD


HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.



LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
210.0		%#200=88.7								
-210.0										
215.0										
-215.0										
220.0		Very dense, wet, bluish gray, fine grained, SILTY SAND (SM)		218.5	SS-43	23	33	48	81	●
-220.0										
225.0										
-225.0										
230.0		Dense, gray		228.5	SS-44	6	13	19	32	●
-230.0										
235.0										
-235.0										
240.0		Loose, wet, gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=25.3		238.5	SS-45	4	4	4	8 X	● ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	B.Ellis/C.Tisher
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
240.0		%#200=28.0								
-240.0										
245.0										
-245.0										
250.0		Medium dense		248.5	SS-46	5	10	11	21	●
-250.0										
255.0										
-255.0										
260.0		Very dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		258.5	SS-47	30	50/0	X	50/0	>>●
-260.0										
265.0										
-265.0										
270.0		Very dense, with trace gravel		268.5	SS-48	43	50	X	50/6	>>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-01	Boring Location:	514+25.9	Offset:	LT 18.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	2.9 ft.	Northing:	249675.65	Easting:	1799417.497	Date Started:	4/20/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	4/27/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 2.0 ft.	Delayed:	3.1 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
270.0										
	-270.0									
275.0										
	-275.0									
280.0		Very dense		278.5	SS-49	24	50/4	X	50/4	>>●
	-280.0									
285.0										
	-285.0									
290.0		Very dense, wet, light gray, fine grained, with trace gravel, POORLY GRADED SAND with SILT (SP-SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=21.1 % _{#200} =10.9		288.5	SS-50	43	41	49	90X	▲ ○ ●
	-290.0									
295.0										
	-295.0									
300.0		Very dense, gray, with trace clay		298.5	SS-51	25	50	X	50/6	>>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



Site Description:		I-10 Mobile River Bridge and Bayway						County:		Mobile					
Boring No.:		MB-01		Boring Location:		514+25.9		Offset:		LT 18.8					
Alignment:		I-10 Main Span													
ALDOT PE No.:		DPI-0030(005)			TE Project No.:			15-1101-0228			Eng./Geo.:		B.Ellis/C.Tisher		
Elev.:		2.9 ft.		Northing:		249675.65		Easting:		1799417.497		Date Started:		4/20/2016	
Total Depth:		300.0 ft.		Soil Depth:		300.0 ft.		Core Depth:		0.0 ft.		Date Completed:		4/27/2016	
Bore Hole Diameter (in):		4-inch		AASHTO / ASTM Sampling Methods:				AASHTO T206 & T207							
Drill Machine:		CME 550X		Drill Method:		MR		Hammer Type:		Automatic		Energy Ratio:		88%	
Core Size:		N/A		Driller:		Thompson Eng		Groundwater:		TOB 2.0 ft.		Delayed:		3.1 ft.	

LEGEND			
SAMPLER TYPE		DRILLING METHOD	
SS - Split Spoon	AC - Auger Cuttings	HSA - Hollow Stem Augers	MR - Mud Rotary Wash
T - Shelby Tube	GB - Grab Bag	SSA - Solid Stem Augers	RC - Rock Coring
DCP - Dynamic Cone Penetrometer	NQ - Rock Core	HA - Hand Auger	



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB	N.O.	Delayed: 4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲
0.0										10 20 30 40 50 60 70 80 90
	5.0	Loose, dry, dark brown gray and light brown, fine to medium grained, with Mobile Abrasives particles, POORLY GRADED SAND (SP), FILL		0.0	SS-1	3	4	5	9	●
	5.0	Loose, brown and black, fine to coarse grained, with Mobile Abrasives particles, FILL		3.0	SS-2	5	3	5	8	●
	0.0	Loose, moist, brown and black, fine to medium grained, with Mobile Abrasive particles and trace gravel, POORLY GRADED SAND (SP, A-3(0)), FILL, LL=NP PL=NP PI=NP NMC=18.7 % #200=3.8		6.0	SS-3	3	4	5	9	● ● ○
10.0		Loose, FILL		9.0	SS-4	4	3	3	6	●
	-5.0									
15.0		Very loose, moist to wet, light brown, fine to medium grained		13.5	SS-5	2	2	2	4	●
	-10.0									
20.0		Very loose, wet, greenish gray and brown, fine grained		18.5	SS-6	2	1	1	2	●
	-15.0									
25.0		Very loose		23.5	SS-7	1	1	1	2	●
	-20.0									
30.0		Very loose, wet, greenish gray and brown, fine to medium grained, POORLY GRADED SAND with SILT		28.5	SS-8	2	1	1	2	● ● ● ○

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB	N.O.	Delayed: 4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	SPT N VALUE (blows / foot)	PL	MC	LL	FINES CONTENT (%)
30.0														
		(SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=22.7 % _{#200} =7.6		30.0	SS-9	1	1	1	2	●				
	-25.0	Very loose, fine grained, with trace Mobile Abrasive particles		31.5	SS-10	1	1	1	2	●				
		Very loose		33.0	SS-11	2	1	1	2	●				
		Very loose, brown and black, with trace Mobile Abrasive particles		34.5	SS-12	1	1	1	2	●				
35.0		Very loose, greenish gray and brown		36.0	SS-13	1	1	1	2	●				
	-30.0	Very loose, No Recovery		37.5	SS-14	2	1	2	3	●▲				
		Very loose, wet, grayish brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=28.4 % _{#200} =10.1		39.0	SS-15	2	2	3	5	●				
40.0		Loose, light brown to brown		40.5	SS-16	1	2	3	5	●				
	-35.0	Loose, fine to medium grained		42.0	SS-17	0	1	2	3	●				
		Very loose, light brown, medium grained		43.5	SS-18	3	3	3	6	●				
45.0		Loose, brown, fine grained, with trace gravel		45.0	SS-19	1	1	2	3	●				
		Loose, light brown, fine to medium grained, with trace gravel		46.5	SS-20	2	2	3	5	●				
	-40.0	Loose, with trace gravel		48.0	SS-21	3	2	3	5	●				
		Loose		49.5	SS-22	1	2	3	5	●				
50.0		Loose, wet, light brown, fine to medium grained, with few gravel, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=23.2 % _{#200} =6.0		51.0	SS-23	3	3	2	5	●				
	-45.0	Loose, fine grained		52.5	SS-24	2	2	2	4	●				
		Very loose		54.0	SS-25	2	1	4	5	●				
55.0		Loose		55.5	SS-26	3	3	5	8	●▲				
	-50.0	Loose, wet, light brown, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=29.4 % _{#200} =3.8		57.0	SS-27	3	4	3	7	●				
		Loose		58.5	SS-28	2	2	4	6	●				
60.0		Loose, fine to medium grained												

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0										
	-55.0									
65.0		Loose		63.5	SS-29	3	3	4	7	●
	-60.0									
70.0		Medium dense, wet, light brown, fine to medium grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=25.3 % _{#200} =4.9		68.5	SS-30	8	10	10	20	X▲ ● O
	-65.0									
75.0		Medium dense, wet, red and light brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM)		73.5	SS-31	2	6	10	16	●
	-70.0									
80.0		Dense, wet, red and light brown, fine to medium grained, with trace gravel, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=22.3 % _{#200} =6.8		78.5	SS-32	11	15	20	35	X▲ O ●
	-75.0									
85.0		Medium dense, wet, light brown, fine to medium grained, POORLY GRADED SAND (SP)		83.5	SS-33	12	10	12	22	●
	-80.0									
90.0		Dense		88.5	SS-34	15	18	20	38	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0										
	-85.0									
95.0		Firm, wet, greenish gray, with few sand, SILT (ML, A-4(0)), LL=NP PL=NP PI=NP NMC=37.7 % _{#200} =91.9		93.5	SS-35	2	3	5	8 X ●	O ▲
	-90.0									
100.0		Dense, wet, green, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=25.9 % _{#200} =12.3		98.5	SS-36	13	16	15	31 X ▲	O ●
	-95.0									
105.0		Medium dense, wet, green, fine grained, POORLY GRADED SAND with SILT (SP-SM)		103.5	SS-37	5	8	17	25	●
	-100.0									
110.0		Dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=29.5 % _{#200} =6.9		108.5	SS-38	15	18	21	39 X ▲	O ●
	-105.0									
115.0		Medium dense, greenish gray		113.5	SS-39	14	15	15	30	●
	-110.0									
120.0		Medium dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-2-4(0)), LL=NP		118.5	SS-40	15	10	13	23 X ▲	O ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0		PL=NP PI=NP NMC=26.6 % $\#$ 200=10.7								
-115.0		Possible gravel layer at approximately 122.0 ft.								
125.0		Dense, wet, brown, fine to medium grained, with trace gravel, POORLY GRADED SAND (SP)		123.5	SS-41	26	19	20	39	●
-120.0										
130.0		Very stiff, wet, greenish gray, SILT (ML, A-4)		128.5	SS-42	7	7	12	19	●
-125.0										
135.0		Very stiff		133.5	SS-43	14	15	14	29	●
-130.0		Undisturbed sample could not be obtained from 135.0 to 137.0 feet. No Recovery		135.0	T-1					
140.0		Stiff, wet, greenish gray, SANDY SILT (ML, A-4(0)), LL=NP PL=NP PI=NP NMC=27.1 % $\#$ 200=66.5		138.5	SS-44	7	5	4	9 X	● O ▲
-135.0		Undisturbed sample obtained from 140.0 to 142.0 feet. Approximately 24 inches of recovery. Stiff, wet, greenish gray, LEAN CLAY with SAND (CL, A-6(6)), LL=29 PL=18 PI=11 NMC=23.8 % $\#$ 200=71.6		140.0	T-2					XOX ▲
145.0		Stiff, gray		143.5	SS-45	5	6	7	13	●
-140.0		Undisturbed sample obtained from 145.0 to 147.0 feet. Approximately 24 inches of recovery. Very stiff, wet, greenish gray, SILTY CLAY with SAND (CL-ML, A-4(2)), LL=23 PL=18 PI=5 NMC=21.0 % $\#$ 200=81.6		145.0	T-3					XOX ▲
150.0		Firm, wet, greenish gray, LEAN CLAY with SAND (CL, A-6(7)), LL=26 PL=14 PI=12 NMC=22.6 % $\#$ 200=78.9		148.5	SS-46	0	2	4	6	● XOX ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
150.0										
	-145.0									
155.0		Very dense, wet, greenish gray, fine grained, with trace clay, SILTY SAND (SM)		153.5	SS-47	23	16	36	52	●
	-150.0									
160.0		Very dense, wet, light brown and gray, fine to medium grained, SILTY SAND (SM, A-1-b(0)), LL=NP PL=NP PI=NP NMC=22.7 %200=17.6		158.5	SS-48	16	25	34	59X	▲○●
	-155.0									
165.0		Very dense, fine to medium grained		163.5	SS-49	15	20	33	53	●
	-160.0									
170.0		Hard, wet, greenish gray, SANDY LEAN CLAY (CL, A-6(4)), LL=28 PL=15 PI=13 NMC=29.9 %200=56.0		168.5	SS-50	8	16	21	37	X○●▲
	-165.0									
175.0		Very dense, wet, gray, fine grained, SILTY SAND (SM)		173.5	SS-51	32	43	50/5	100+	>>●
	-170.0									
180.0		Dense, wet, greenish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=28.5		178.5	SS-52	18	23	23	46X	▲○●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD


HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.



LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
210.0										
	-205.0	Undisturbed sample obtained from 210.0 to 212.0 feet. Approximately 22 inches of recovery. Hard, wet, greenish gray, SANDY LEAN CLAY (CL, A-6(11)), LL=33 PL=13 PI=20 NMC=14.4 %200=69.2		210.0	T-5					X — X ▲
215.0										
	-210.0									
	-220.0	Very stiff, wet, greenish gray, with few sand, LEAN CLAY (CL, A-6(19)), LL=36 PL=15 PI=21 NMC=17.2 %200=94.2		218.5	SS-58	8	12	17	29	X — ● — X ▲
220.0										
	-215.0									
	-225.0									
225.0										
	-220.0									
	-230.0	Undisturbed sample obtained from 228.5.0 to 230.0 feet. Approximately 18 inches of recovery. Hard, wet, greenish gray, SILT with SAND (ML, A-4(3)), LL=29 PL=23 PI=6 NMC=26.2 %200=72.8 Very stiff		228.5	T-6					X — X ▲
230.0				230.5	SS-59	7	7	18	25	●
	-225.0									
	-235.0									
	-230.0									
235.0										
	-230.0									
	-240.0	Medium dense, wet, greenish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP		238.5	SS-60	11	11	13	24	X ● ▲
240.0										

LEGEND

SAMPLER TYPE

SS - Split Spoon AC - Auger Cuttings
 T - Shelby Tube GB - Grab Bag
 DCP - Dynamic Cone Penetrometer NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers MR - Mud Rotary Wash
 SSA - Solid Stem Augers RC - Rock Coring
 HA - Hand Auger



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
240.0										
	-235.0	NMC=23.1 % $\#$ 200=27.7								
245.0										
	-240.0									
250.0		Medium dense		248.5	SS-61	6	5	7	12	●
	-245.0									
255.0										
	-250.0									
260.0		Stiff, wet, greenish gray, LEAN CLAY with SAND (CL, A-6(8)), LL=29 PL=16 PI=13 NMC=21.7 % $\#$ 200=80.1		258.5	SS-62	0	5	9	14	● ○ X ▲
	-255.0									
265.0										
	-260.0									
270.0		Medium dense, wet, greenish gray, fine grained, SILTY SAND (SM)		268.5	SS-63	4	6	15	21	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02	Boring Location:	527+75.9	Offset:	LT 22.0	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	7.4 ft.	Northing:	250461.65	Easting:	1800515.058	Date Started:	9/8/2015
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/15/2015
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB N.O.	Delayed:	4.7 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
270.0										
	-265.0	Undisturbed sample obtained from 270.0 to 272.0 feet. Approximately 8 inches of recovery. Medium dense, wet, greenish gray, fine grained, SILTY SAND (SM, A-4(0)), LL=NP PL=NP PI=NP NMC=19.6 % _{#200} =45.6		270.0	T-7				X	○ ● ▲ 10 20 30 40 50 60 70 80 90
275.0										
	-270.0									
280.0		Very dense, wet, light greenish gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=25.3 % _{#200} =16.5		278.5	SS-64	27	50/4	X	50/4X	▲ ○ ● >>●
	-275.0									
285.0										
	-280.0									
290.0		Very dense, with trace wood		288.5	SS-65	24	29	36	65	●
	-285.0									
295.0										
	-290.0									
300.0		Very dense, wet, pale brown, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP		298.5	SS-66	48	38	50/4	100X	▲ ● >>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring

[illegible]



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
0.0		Very loose, brown, fine grained, with trace gravel, CLAYEY SAND (SC)		0.0	SS-1	0	0	0	0	
1.5		Very loose, No Recovery		1.5	SS-2	0	0	0	0	
3.0		Very loose, No Recovery		3.0	SS-3	0	0	0	0	
4.5		Very loose, No Recovery		4.5	SS-4	0	0	0	0	
6.0		Very soft, dark gray, with trace gravel, SANDY LEAN CLAY (CL, A-6(5)), LL=33 PL=18 PI=15 NMC=73.4 % _{#200} =54.6		6.0	SS-5	0	0	0	0	X X ▲ O
8.5		Very loose, dark gray, fine grained, SILTY SAND (SM)		8.5	SS-6	0	0	0	0	
13.5		Very loose, gray, fine grained, CLAYEY SAND (SC)		13.5	SS-7	0	0	1	1	
18.5		Very loose, light gray, fine to medium grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=26.4 % _{#200} =16.8		18.5	SS-8	0	0	0	0	▲ O
23.5		Very loose, brown, with trace clay		23.5	SS-9	1	1	1	2	
28.5		Very loose, brown, fine grained, POORLY GRADED SAND (SP)		28.5	SS-10	1	1	2	3	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
30.0										
	-35.0	Very loose, white		33.5	SS-11	1	2	2	4	●
35.0										
	-40.0	Very loose, tan, fine to medium grained, with trace gravel		38.5	SS-12	2	2	2	4	●
40.0										
	-45.0	Loose, fine grained		43.5	SS-13	3	4	5	9	●
45.0										
	-50.0	Medium dense, tan, medium to fine grained, with trace gravel, POORLY GRADED SAND (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=21.7 % #200=1.5		48.5	SS-14	4	6	9	15	● ○
50.0										
	-55.0	Medium dense		53.5	SS-15	6	8	9	17	●
55.0										
	-60.0	Medium dense, wet		58.5	SS-16	6	6	10	16	●
60.0										

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0										
	-65.0	Medium dense		63.5	SS-17	7	9	11	20	●
65.0										
	-70.0	Medium dense		68.5	SS-18	9	11	11	22	●
70.0										
	-75.0	Loose		73.5	SS-19	4	5	5	10	●
75.0										
	-80.0	Loose, wet, tan, fine to medium grained, with trace gravel, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP NMC=21.2 % #200=2.3		78.5	SS-20	5	5	4	9	▲ ● ○
80.0										
	-85.0	Firm, moist, gray, with trace organics and trace gravel, FAT CLAY with SAND (CH, A-7-6(50)), LL=87 PL=29 PI=58 NMC=37.5 % #200=78.7		83.5	SS-21	9	2	3	5	● X ○ — ▲ X
85.0										
	-90.0	Undisturbed sample could not be obtained from 88.5 to 90.5 feet. No Recovery.		88.5	T-1					
90.0										

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL — MC — LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0										
	-95.0									
95.0		Undisturbed sample obtained from 93.5 to 95.5 feet. Approximately 24 inches of recovery. Moist, brown, SANDY LEAN CLAY (CL, A-7-6(12)), LL=45 PL=18 PI=27 NMC=25.7 % _{#200} =56.4		93.5	T-2					× ○ — × ▲
	-100.0									
100.0		Dense, wet, brown, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=23.6 % _{#200} =7.0		98.5	SS-22	7	15	19	34	× ▲ ○ ●
	-105.0									
105.0		Dense		103.5	SS-23	17	24	25	49	●
	-110.0									
110.0		Dense, wet, brown, fine grained, POORLY GRADED SAND (SP)		108.5	SS-24	6	14	19	33	●
	-115.0									
115.0		Very dense, wet, brown, medium to fine grained, POORLY GRADED SAND with GRAVEL (SP, A-1-b(0)), LL=NP PL=NP PI=NP NMC=10.7 % _{#200} =3.8		113.5	SS-25	24	33	37	70	× ▲ ○ ●
	-120.0									
120.0		Stiff, wet, gray, with trace sand, LEAN CLAY (CH)		118.5	SS-26	0	4	5	9	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0										
	-125.0	Undisturbed sample obtained from 123.0 to 125.0 feet. Approximately 24 inches of recovery. Wet, greenish gray, with trace sand, LEAN CLAY (CL, A-6(18)), LL=35 PL=17 PI=18 NMC=26.0 %200=97.7		123.0	T-3					X O X ▲
125.0										
	-130.0	Stiff		128.5	SS-27	0	7	8	15	●
130.0										
	-135.0	Undisturbed sample could not be obtained from 133.0 to 135.0 feet. No Recovery.		133.0	T-4					
135.0										
	-140.0	Stiff, wet, gray, with few sand, FAT CLAY (CH, A-7-6(59)), LL=77 PL=20 PI=57 NMC=23.0 %200=92.6		138.5	SS-28	2	4	7	11	● X O X ▲
140.0										
	-145.0	Undisturbed sample obtained from 143.0 to 145.0 feet. Approximately 11 inches of recovery. Wet, gray, with trace sand, FAT CLAY (CH, A-7-6(35)), LL=51 PL=16 PI=35 NMC=47.7 %200=95.1		143.0	T-5					X O X ▲
145.0										
	-150.0	Dense, No Recovery NOTE: Shoe came off of Split Spoon and sample was								
150.0										

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L/Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
150.0		lost								
155.0	-155.0	Dense, brown, fine grained, with few gravel, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=30.4 %200=16.2		153.5	SS-29	50	23	22	45X	▲ ○ ●
160.0	-160.0	Undisturbed sample obtained from 158.0 to 160.0 feet. Approximately 24 inches of recovery. Gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=26.7 %200=7.4		158.0	T-6				X ▲	○
170.0	-170.0	Hard, gray, SANDY LEAN CLAY (CL, A-6(7)), LL=33 PL=15 PI=18 NMC=18.6 %200=55.6		168.5	SS-30	17	29	34	63	X ○ X ▲ ●
180.0	-180.0	Undisturbed sample could not be obtained from 178.0 to 180.0 feet. Split Spoon sample taken at 178.0 feet. Hard, light greenish gray		178.0	SS-31					

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
180.0										
	-185.0									
185.0										
	-190.0									
190.0		Hard, green		188.5	SS-32	12	14	20	34	●
	-195.0									
195.0										
	-200.0									
200.0		Undisturbed sample obtained from 198.0 to 200.0 feet. Approximately 24 inches of recovery. Green, LEAN CLAY with SAND (CL, A-6(16)), LL=39 PL=14 PI=25 NMC=31.2 % #200=74.2		198.0	T-8					X O X ▲
	-205.0									
205.0										
	-210.0									
210.0		Very stiff, green, with few sand, LEAN CLAY (CL, A-6(14)), LL=33 PL=18 PI=15 NMC=22.1 % #200=94.8		208.5	SS-33	12	8	9	17	● O X ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD


HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.



LEGEND

SAMPLER TYPE

SS - Split Spoon
 T - Shelby Tube
 DCP - Dynamic Cone Penetrometer
 AC - Auger Cuttings
 GB - Grab Bag
 NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
 SSA - Solid Stem Augers
 HA - Hand Auger
 MR - Mud Rotary Wash
 RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
240.0										
		%#200=41.8								
-245.0										
245.0										
-250.0										
250.0		Stiff, greenish gray, SANDY LEAN CLAY (CL, A-6(5)), LL=25 PL=14 PI=11 NMC=22.1 %#200=69.6		248.5	SS-37	4	6	6	12	● X ▲
-255.0										
255.0										
-260.0										
260.0		Undisturbed sample obtained from 258.0 to 260.0 feet. Approximately 20 inches of recovery. Gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		258.0	T-10					
-265.0										
265.0										
-270.0										
270.0		Very dense, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP		268.5	SS-38	35	45	50/5	100*	▲ O >>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
270.0		PI=NP NMC=22.5 % $\#$ 200=9.7								
-275.0										
275.0										
-280.0										
280.0		Very dense, gray, fine to medium grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=22.0 % $\#$ 200=13.1		278.5	SS-39	19/4	39	X	100*	▲ ○ >>●
-285.0										
285.0										
-290.0										
290.0		Very dense		288.5	SS-40	48	50/5	X	50/5	>>●
-295.0										
295.0										
-300.0										
300.0		Firm, greenish gray, SANDY SILT (ML, A-4(0)), LL=NP PL=NP PI=NP NMC=24.6 % $\#$ 200=63.8		298.5	SS-41	5	3	5	8 X	● ○ ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	MB-02A	Boring Location:	528+88.0	Offset:	RT 32.9	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	Chris L\Charles T		
Elev.:	-2.0 ft.	Northing:	250481.989	Easting:	1800638.256	Date Started:	6/20/2017
Total Depth:	320.0 ft.	Soil Depth:	320.0 ft.	Core Depth:	0.0 ft.	Date Completed:	7/24/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	90%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 0.0 ft.	Delayed:	0.0 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
300.0										
	-305.0									
305.0										
	-310.0									
310.0		Very stiff, greenish gray, LEAN CLAY with SAND (CL, A-7-6(24)), LL=49 PL=12 PI=37 NMC=17.0 % _{#200} =70.6		308.5	SS-42	7	9	11	20	X ● X ▲
	-315.0									
315.0										
	-320.0									
320.0		Hard, green, LEAN CLAY with SAND (CL, A-7-6(22)), LL=45 PL=14 PI=31 NMC=35.6 % _{#200} =76.2		318.5	SS-43	11	17	24	41	X O ● X ▲
		Boring Terminated at 320.0 feet.								

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD


HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	TH-13	Boring Location:	153+01.7	Offset:	RT 78.9	Alignment:	West Area
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	C. Tisher		
Elev.:	25.3 ft.	Northing:	250156.58	Easting:	1798133.78	Date Started:	9/19/2017
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	D50	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	94%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 36.3 ft.	Delayed:	23.3 ft.



LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	TH-13	Boring Location:	153+01.7	Offset:	RT 78.9	Alignment:	West Area
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	C. Tisher		
Elev.:	25.3 ft.	Northing:	250156.58	Easting:	1798133.78	Date Started:	9/19/2017
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	D50	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	94%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 36.3 ft.	Delayed:	23.3 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
30.0	-5.0	SAND (MH, A-7-5(33)), LL=83 PL=46 PI=37 NMC=98.2 %200=75.9								
35.0	-10.0	Loose, moist, light gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=25.9 %200=28.9		33.5	SS-10	5	4	4	8 X ●	○ ▲
40.0	-15.0	Medium dense, moist, reddish brown, fine grained, with trace clay, POORLY GRADED SAND with SILT (SP-SM)		38.5	SS-11	4	9	12	21 ●	
45.0	-20.0	Dense		43.5	SS-12	15	17	19	36 ●	
50.0	-25.0	Dense, moist, white and brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=24.2 %200=6.6		48.5	SS-13	14	19	22	41 X ▲ ○ ●	
55.0	-30.0	Dense, white		53.5	SS-14	12	14	19	33 ●	
60.0		Medium dense		58.5	SS-15	9	12	17	29 ●	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	TH-13	Boring Location:	153+01.7	Offset:	RT 78.9	Alignment:	West Area
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	C. Tisher		
Elev.:	25.3 ft.	Northing:	250156.58	Easting:	1798133.78	Date Started:	9/19/2017
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	D50	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	94%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 36.3 ft.	Delayed:	23.3 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0	-35.0									
65.0	-40.0	Dense, moist, white and brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=21.9 % _{#200} =6.8		63.5	SS-16	12	21	20	41X	▲ ○ ●
70.0	-45.0	Dense		68.5	SS-17	16	16	22	38	●
75.0	-50.0	Medium dense, medium to coarse grained, with trace gravel		73.5	SS-18	12	13	14	27	●
80.0	-55.0	Medium dense, moist, tan, fine to medium grained, with trace clay and trace gravel, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=21.2 % _{#200} =13.5		78.5	SS-19	11	11	16	27X	▲ ○ ●
85.0	-60.0	Dense, white, with trace gravel		83.5	SS-20	16	19	21	40	●
90.0		Dense		88.5	SS-21	16	21	19	40	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	TH-13	Boring Location:	153+01.7	Offset:	RT 78.9	Alignment:	West Area
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	C. Tisher		
Elev.:	25.3 ft.	Northing:	250156.58	Easting:	1798133.78	Date Started:	9/19/2017
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	D50	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	94%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 36.3 ft.	Delayed:	23.3 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0	-65.0									
95.0	-70.0	Dense, moist, pale brown, medium to fine and coarse grained, with few gravel, WELL-GRADED SAND with SILT (SW-SM, A-1-b(0)), LL=NP PL=NP PI=NP NMC=13.8 % _{#200} =5.7		93.5	SS-22	14	18	17	35	▲ ○ ●
100.0	-75.0	Dense, light reddish brown and brown, fine to medium grained		98.5	SS-23	17	16	27	43	●
105.0	-80.0	Stiff, moist, gray and light gray, with trace organics and trace sand, FAT CLAY (CH)		103.5	SS-24	3	4	5	9	●
110.0	-85.0	Undisturbed sample obtained from 108.5 to 110.5 feet. Approximately 24 inches of recovery. Stiff, moist, gray, with few sand, FAT CLAY (CH, A-7-6(47)), LL=67 PL=22 PI=45 NMC=40.8 % _{#200} =93.4		108.5	T-3					X ○ X ▲
115.0	-90.0	Firm, gray, with trace organics and trace sand		113.5	SS-25	2	3	4	7	●
120.0		Undisturbed sample obtained from 118.5 to 120.5 feet. Approximately 24 inches of recovery.		118.5	T-4					X ○ X ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	TH-13	Boring Location:	153+01.7	Offset:	RT 78.9	Alignment:	West Area
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	C. Tisher		
Elev.:	25.3 ft.	Northing:	250156.58	Easting:	1798133.78	Date Started:	9/19/2017
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.	Core Depth:	0.0 ft.	Date Completed:	9/21/2017
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	D50	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	94%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 36.3 ft.	Delayed:	23.3 ft.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0	-95.0	Stiff, moist, gray, with little sand, FAT CLAY (CH, A-7-6(32)), LL=54 PL=18 PI=36 NMC=30.4 % _{#200} =86.3								
125.0	-100.0	Loose, wet, bluish gray, fine grained, CLAYEY SAND (SC, A-4(1)), LL=22 PL=13 PI=9 NMC=23.8 % _{#200} =42.1		123.5	SS-26	4	4	6	10	● ← ○ ▲
130.0	-105.0	Very dense, moist, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		128.5	SS-27	14	30	50	80	●
135.0	-110.0	Very dense, white, fine to medium grained		133.5	SS-28	22	35	41	76	●
140.0	-115.0	Very dense		138.5	SS-29	16	22	29	51	●
145.0	-120.0	Very dense, moist, tan, medium to fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=18.8 % _{#200} =7.6		143.5	SS-30	21	31	42	73	● X ▲ ○
150.0		Very stiff, moist, gray, with trace sand, FAT CLAY (CH)		148.5	SS-31	5	10	14	24	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring

RECORD OF TEST BORING

Site Description:		I-10 Mobile River Bridge and Bayway					County:	Mobile		
Boring No.:		TH-13	Boring Location:		153+01.7	Offset:	RT 78.9	Alignment:	West Area	
ALDOT PE No.:		DPI-0030(005)		TE Project No.:		15-1101-0228		Eng./Geo.:	C. Tisher	
Elev.:	25.3 ft.	Northing:	250156.58		Easting:	1798133.78		Date Started:	9/19/2017	
Total Depth:	150.0 ft.	Soil Depth:	150.0 ft.		Core Depth:	0.0 ft.		Date Completed:	9/21/2017	
Bore Hole Diameter (in):		4-inch	AASHTO / ASTM Sampling Methods:			AASHTO T206 & T207				
Drill Machine:		D50	Drill Method:		MR	Hammer Type:		Automatic	Energy Ratio:	94%
Core Size:	N/A		Driller:	Thompson Eng	Groundwater:	TOB	36.3 ft.	Delayed:	23.3 ft.	

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6" 2nd 6" 3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
		Boring Terminated at 150.0 feet.						

LEGEND

SAMPLER TYPE		DRILLING METHOD	
SS - Split Spoon	AC - Auger Cuttings	HSA - Hollow Stem Augers	MR - Mud Rotary Wash
T - Shelby Tube	GB - Grab Bag	SSA - Solid Stem Augers	RC - Rock Coring
DCP - Dynamic Cone Penetrometer	NQ - Rock Core	HA - Hand Auger	



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228		Eng./Geo.:	B.Ellis/C.Tisher	
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC ○ LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
0.0				0.0	SS-1	6	13	6	19	●
5.0		Medium dense, dry, black, fine grained, with glass, metal and debris, SILTY SAND (SM)		1.5	SS-2	6	7	10	17 X	● ○
5.0		Medium dense, dry, black and reddish yellow, fine grained, with some debris, SILTY SAND with GRAVEL (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=34.6 % #200=17.8		3.0	SS-3	3	3	4	7	●
5.0		Loose, wet, gray and brown, fine grained, with trace gravel		4.5	SS-4	4	4	5	9 X	● ○
0.0		Loose, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=24.5 % #200=8.3		6.0	SS-5	1	1	1	2	●
		Very loose		8.5						
10.0		Very loose			SS-6	0	0	0	0	●
-5.0				13.5	T-1					
15.0		Undisturbed sample obtained 13.5 to 15.5 feet. Approximately 19 inches of recovery.								
-10.0		Moist, gray and dark gray, with trace organics, FAT CLAY (CH)								
20.0		Medium dense, wet, tan, fine grained, POORLY GRADED SAND (SP)		18.5	SS-7	7	10	14	24	●
-15.0				23.5	SS-8	8	11	16	27	●
25.0		Medium dense		28.5	SS-9	8	10	14	24 X	●
-20.0										
30.0		Medium dense, wet, white, fine grained, POORLY GRADED SAND (SP, A-3(0)), LL=NP PL=NP PI=NP								

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	B.Ellis/C.Tisher
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
30.0										
	-25.0	NMC=25.6 % #200=3.4								
35.0		Medium dense, light tan		33.5	SS-10	4	6	10	16	●
	-30.0									
40.0		Medium dense, light tan and white		38.5	SS-11	10	12	17	29	●
	-35.0									
45.0		Dense		43.5	SS-12	13	21	28	49	●
	-40.0									
50.0		Medium dense, white and brown, fine to medium grained		48.5	SS-13	10	11	12	23	●
	-45.0									
55.0		Medium dense, wet, tan, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM)		53.5	SS-14	5	5	6	11	●
	-50.0									
60.0		Medium dense, wet, tan, fine grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP		58.5	SS-15	7	10	15	25	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	B.Ellis/C.Tisher
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
60.0		PL=NP PI=NP NMC=23.7 % $\#$ 200=9.9								
	-55.0	Medium dense		63.5	SS-16	9	7	9	16	●
65.0										
	-60.0									
	-65.0	Loose, wet, reddish brown, medium to fine grained, with trace gravel, POORLY GRADED SAND with SILT (SP-SM, A-1-b(0)), LL=NP PL=NP PI=NP NMC=18.3 % $\#$ 200=10.9		68.5	SS-17	3	3	6	9 X	● ○
70.0										
	-70.0	Medium dense, fine grained		73.5	SS-18	6	9	8	17	●
75.0										
	-75.0	Medium dense, light brown		78.5	SS-19	11	13	16	29	●
80.0										
	-80.0	Loose, light brown and brown, fine to medium grained		83.5	SS-20	5	4	5	9	●
85.0										
	-85.0									
	-90.0	Dense, wet, reddish brown, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-3(0)),		88.5	SS-21	10	19	16	35 X	▲ ○ ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
90.0		LL=NP PL=NP PI=NP NMC=22.5 % _{#200} =7.1								
	-85.0									
95.0		Undisturbed sample obtained from 93.5 to 95.5 feet. Approximately 24 inches of recovery. Stiff, moist, dark grayish brown, with trace sand, FAT CLAY (CH, A-7-6(65)), LL=81 PL=25 PI=56 NMC=46.9 % _{#200} =98.5		93.5	T-2					
	-90.0									
100.0		Undisturbed sample obtained from 98.5 to 100.5 feet. Approximately 7 inches of recovery. Wet, brown, fine to medium grained, CLAYEY SAND (SC)		98.5	T-3					
	-95.0									
105.0		Medium dense, moist, dark gray, with organics, CLAYEY SAND (SC, A-7-5(11)), LL=82 PL=32 PI=50 NMC=77.0 % _{#200} =38.6		103.5	SS-22	1	6	7	13	
	-100.0									
110.0		Undisturbed sample obtained from 108.5 to 110.5 feet. Approximately 24 inches of recovery. Top of tube: Brown Bottom of tube: Moist, gray, FAT CLAY with SAND (CH)		108.5	T-4					
	-105.0									
115.0		Dense, wet, gray and grayish brown, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=29.7 % _{#200} =23.1		113.5	SS-23	19	20	21	41	
	-110.0									
120.0		Dense, wet, dark gray, fine grained, with trace organics, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP		118.5	SS-24	11	15	27	42	

LEGEND

SAMPLER TYPE

SS - Split Spoon
 T - Shelby Tube
 DCP - Dynamic Cone Penetrometer
 AC - Auger Cuttings
 GB - Grab Bag
 NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
 SSA - Solid Stem Augers
 HA - Hand Auger
 MR - Mud Rotary Wash
 RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
120.0		PI=NP NMC=23.6 % $\#$ 200=14.4								
125.0	-115.0	Dense, wet, gray, fine to medium grained, with few gravel, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=13.8 % $\#$ 200=8.9		123.5	SS-25	23	23	25	48X	▲○●
130.0	-120.0	Dense, fine to coarse grained, with trace gravel		128.5	SS-26	16	18	23	41	●
135.0	-125.0	Very dense, with trace gravel		133.5	SS-27	42	45	44	89	●
140.0	-130.0	Stiff, moist, bluish gray, with trace sand, FAT CLAY (CH, A-7-6(40)), LL=60 PL=18 PI=42 NMC=20.9 % $\#$ 200=89.0		138.5	SS-28	2	8	7	15	●○—X▲
145.0	-135.0	Undisturbed sample obtained from 140.5 to 141.9 feet. Approximately 17 inches of recovery. Gray, with trace sand and trace silt lenses		140.5	T-5					
145.0	-135.0	Undisturbed sample obtained from 143.5 to 145.3 feet. Approximately 21 inches of recovery. Very stiff, moist, bluish gray and gray, with few sand lenses, LEAN CLAY (CL, A-6(14)), LL=32 PL=16 PI=16 NMC=27.0 % $\#$ 200=91.5		143.5	T-6					X—○X▲
150.0	-140.0	Stiff		148.5	SS-29	5	6	9	15	●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
150.0										
	-145.0									
155.0		Undisturbed sample obtained from 153.5 to 155.5 feet. Approximately 24 inches of recovery. Top of tube: Gray		153.5	T-7					
	-150.0	Bottom of tube: Wet, gray, fine to medium grained, SILTY SAND (SM)								
160.0		Very dense, wet, gray, fine to medium grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=19.5 % _{#200} =12.4		158.5	SS-30	30	54	50/4	100*	▲ ○ >>●
	-155.0									
165.0		Hard, wet, gray, LEAN CLAY (CL)		163.5	SS-31	29	23	16	39	●
	-160.0	Undisturbed sample obtained from 166.0 to 168.0 feet. Approximately 24 inches of recovery. Very stiff, wet, bluish gray, LEAN CLAY with SAND (CL, A-7-6(25)), LL=48 PL=16 PI=32 NMC=29.5 % _{#200} =79.5		166.0	T-8					× ○ × ▲
170.0		Hard, wet, bluish gray, with trace sand, LEAN CLAY (CL, A-7-6(26)), LL=45 PL=19 PI=26 NMC=31.0 % _{#200} =92.5		168.0	SS-32	6	7	29	36	× ○ ● × ▲
	-165.0									
175.0		Hard		173.5	SS-33	22	26	24	50	●
	-170.0									
180.0		Very dense, wet, green, fine grained, SILTY SAND (SM, A-4(0)), LL=NP PL=NP PI=NP NMC=27.4		178.5	SS-34	19	40	44	84*	○ ▲ ●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:	AASHTO T206 & T207				
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
180.0		%#200=47.0								
-175.0										
185.0		Very dense, wet, dark gray, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM)		183.5	SS-35	44	50/5	X	50/5	>>●
-180.0										
190.0		Very dense, wet, gray, fine to medium grained, with trace gravel, POORLY GRADED SAND with SILT (SP-SM, A-3(0)), LL=NP PL=NP PI=NP NMC=17.5 %#200=8.4		188.5	SS-36	50	50/4	X	50/4X	▲ ○ >>●
-185.0										
195.0		Undisturbed sample obtained from 193.0 to 195.0 feet. Approximately 24 inches of recovery. Hard, wet to moist, bluish gray, SANDY LEAN CLAY (CL, A-4(3)), LL=28 PL=20 PI=8 NMC=19.9 %#200=63.4		193.0	T-9					⊗ X ▲
-190.0										
200.0		Very stiff		198.5	SS-37	8	12	14	26	●
-195.0		Undisturbed sample could not be obtained from 200.0 to 202.0 feet. No recovery.		200.0	T-10					
205.0										
-200.0										
210.0		Undisturbed sample obtained from 208.5 to 210.5 feet. Approximately 10 inches of recovery.		208.5	T-11					⊗ X ▲

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	B.Ellis/C.Tisher
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
210.0										
	-205.0	Very stiff, wet to moist, bluish gray, SANDY LEAN CLAY (CL, A-6(8)), LL=32 PL=11 PI=21 NMC=13.1 % _{#200} =54.9								
215.0										
	-210.0									
220.0		Undisturbed sample obtained from 218.5 to 220.5 feet. Approximately 9 inches of recovery. Moist to wet, SANDY LEAN CLAY (CL)		218.5	T-12					
	-215.0									
225.0										
	-220.0									
230.0		Firm, wet, gray, SANDY SILT (ML, A-4(0)), LL=NP PL=NP PI=NP NMC=27.5 % _{#200} =60.5		228.5	SS-38	6	3	4	7 X ●	○ ▲
	-225.0									
235.0										
	-230.0									
240.0		Loose, wet, gray, fine grained, SILTY SAND (SM)		238.5	SS-39	2	5	5	10 ●	

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228			Eng./Geo.:	B.Ellis/C.Tisher
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
240.0										
	-235.0									
245.0										
	-240.0									
250.0		Loose, wet, gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=27.5 %#200=29.2		248.5	SS-40	7	3	5	8 X ●	▲
	-245.0									
255.0										
	-250.0									
260.0		Very dense		258.5	SS-41	20	30	30	60	●
	-255.0									
265.0										
	-260.0									
270.0		Very dense, wet, gray, fine grained, SILTY SAND (SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=19.7		268.5	SS-42	38	36	50/6	100 X ●	▲ >>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring



thompson
ENGINEERING

RECORD OF TEST BORING

Site Description:	I-10 Mobile River Bridge and Bayway					County:	Mobile
Boring No.:	WHLA-03	Boring Location:	509+17.5	Offset:	LT 5.8	Alignment:	I-10 Main Span
ALDOT PE No.:	DPI-0030(005)	TE Project No.:	15-1101-0228	Eng./Geo.:	B.Ellis/C.Tisher		
Elev.:	7.1 ft.	Northing:	249311.95	Easting:	1798929.585	Date Started:	4/29/2016
Total Depth:	300.0 ft.	Soil Depth:	300.0 ft.	Core Depth:	0.0 ft.	Date Completed:	5/4/2016
Bore Hole Diameter (in):	4-inch	AASHTO / ASTM Sampling Methods:		AASHTO T206 & T207			
Drill Machine:	CME 550X	Drill Method:	MR	Hammer Type:	Automatic	Energy Ratio:	88%
Core Size:	N/A	Driller:	Thompson Eng	Groundwater:	TOB 6.0 ft.	Delayed:	N.O.

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6"	2nd 6"	3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL X MC O LL X ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
270.0										
	-265.0	%#200=17.3								
275.0										
	-270.0									
280.0		Very dense, wet, gray, fine grained, POORLY GRADED SAND with SILT (SP-SM)		278.5	SS-43	29	46	50/5	100+	>>●
	-275.0									
285.0										
	-280.0									
290.0		Very dense, wet, gray, fine to medium grained, POORLY GRADED SAND with SILT (SP-SM, A-2-4(0)), LL=NP PL=NP PI=NP NMC=20.8 %#200=11.1		288.5	SS-44	30	50	X	50/6X	▲ ○ >>●
	-285.0									
295.0										
	-290.0									
300.0		Very dense, light gray and white		298.5	SS-45	50	X	X	100+	>>●

LEGEND

SAMPLER TYPE

SS - Split Spoon
T - Shelby Tube
DCP - Dynamic Cone Penetrometer
AC - Auger Cuttings
GB - Grab Bag
NQ - Rock Core

DRILLING METHOD

HSA - Hollow Stem Augers
SSA - Solid Stem Augers
HA - Hand Auger
MR - Mud Rotary Wash
RC - Rock Coring

RECORD OF TEST BORING

Site Description: I-10 Mobile River Bridge and Bayway						County: Mobile	
Boring No.: WHLA-03		Boring Location: 509+17.5		Offset: LT 5.8		Alignment: I-10 Main Span	
ALDOT PE No.: DPI-0030(005)		TE Project No.: 15-1101-0228		Eng./Geo.: B.Ellis/C.Tisher			
Elev.: 7.1 ft.		Northing: 249311.95		Easting: 1798929.585		Date Started: 4/29/2016	
Total Depth: 300.0 ft.		Soil Depth: 300.0 ft.		Core Depth: 0.0 ft.		Date Completed: 5/4/2016	
Bore Hole Diameter (in): 4-inch		AASHTO / ASTM Sampling Methods:			AASHTO T206 & T207		
Drill Machine: CME 550X		Drill Method: MR		Hammer Type: Automatic		Energy Ratio: 88%	
Core Size: N/A		Driller: Thompson Eng		Groundwater: TOB 6.0 ft.		Delayed: N.O.	

Depth (ft)	Elevation (ft)	MATERIAL DESCRIPTION	Graphic Log	Sample Depth (ft.)	Sample No./Type	1st 6" 2nd 6" 3rd 6"	N Value (Field)	● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90
		Boring Terminated at 300.0 feet.						● SPT N VALUE (blows / foot) PL MC LL ▲ FINES CONTENT (%) ▲ 10 20 30 40 50 60 70 80 90

LEGEND

SAMPLER TYPE		DRILLING METHOD	
SS - Split Spoon	AC - Auger Cuttings	HSA - Hollow Stem Augers	MR - Mud Rotary Wash
T - Shelby Tube	GB - Grab Bag	SSA - Solid Stem Augers	RC - Rock Coring
DCP - Dynamic Cone Penetrometer	NQ - Rock Core	HA - Hand Auger	

APPENDIX B

Laboratory Results Provided by ALDOT

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay		D50 (mm)	USCS	AASHTO
495+05.3 RT 39.0	HLA-10A	SS-27	159.3	28.8	72	21	51	5.7	33.5	60.8			CH	A-7-6(28)
495+05.3 RT 39.0	HLA-10A	SS-30	189.3	20.6	NP	NP	NP	5.5	70.4	24.2		0.1899	SM	A-2-4(0)
495+05.3 RT 39.0	HLA-10A	T-2	198.8	24.4	50	16	34	0.0	25.2	74.8			CH	A-7-6(24)
495+05.3 RT 39.0	HLA-10A	T-3	218.8	16.8	30	17	13	0.0	22.1	59.8	18.0	0.0442	CL	A-6(8)
495+05.3 RT 39.0	HLA-10A	-	228.5	23.8	30	18	12	0.0	40.9	59.1			CL	A-6(4)
495+05.3 RT 39.0	HLA-10A	SS-36	249.3	25.4	NP	NP	NP	0.0	36.1	63.9			ML	A-4(0)
541+43.3 LT 45.4	HLA-12	SS-2	1.5	3.1	NP	NP	NP	3.5	92.6	3.9		0.4151	SP	A-3(0)
541+43.3 LT 45.4	HLA-12	SS-6	8.5	11.3	NP	NP	NP	22.7	74.8	2.5		1.1886	SP	A-1-b(0)
541+43.3 LT 45.4	HLA-12	SS-11	33.5	22.3	NP	NP	NP	0.1	96.1	3.8		0.2510	SP	A-3(0)
541+43.3 LT 45.4	HLA-12	SS-15	53.5	23.6	NP	NP	NP	0.2	95.3	4.5		0.3211	SP	A-3(0)
541+43.3 LT 45.4	HLA-12	SS-20	78.5	15.8	NP	NP	NP	0.7	94.5	4.9		0.4861	SP	A-1-b(0)
541+43.3 LT 45.4	HLA-12	SS-22	88.5	18.4	NP	NP	NP	1.9	92.6	5.4		0.3569	SP-SM	A-3(0)
541+43.3 LT 45.4	HLA-12	T-1	108.0	36.6	97	26	71	0.0	3.8	96.2			CH	A-7-6(79)
541+43.3 LT 45.4	HLA-12	SS-26	113.5	25.6	NP	NP	NP	0.3	49.6	50.1			ML	A-4(0)
541+43.3 LT 45.4	HLA-12	SS-31	138.5	21.9	NP	NP	NP	0.5	93.2	6.3		0.3223	SP-SM	A-3(0)
541+43.3 LT 45.4	HLA-12	SS-33	148.5	21.4	39	15	24	0.0	7.4	92.6			CL	A-6(22)
541+43.3 LT 45.4	HLA-12	SS-34	158.5	22.4	46	15	31	0.0	33.9	66.1			CL	A-7-6(18)
541+43.3 LT 45.4	HLA-12	T-2	188.0	20.4	29	15	14	0.0	11.0	89.0			CL	A-6(11)
541+43.3 LT 45.4	HLA-12	SS-38	208.5	19.8	32	16	16	0.0	48.7	51.3			CL	A-6(5)
541+43.3 LT 45.4	HLA-12	SS-40	228.5	25.7	34	19	15	0.0	26.0	74.0			CL	A-6(10)
541+43.3 LT 45.4	HLA-12	SS-41	238.5	22.2	NP	NP	NP	0.0	69.0	31.0		0.1142	SM	A-2-4(0)
541+43.3 LT 45.4	HLA-12	SS-42	248.5	24.3	NP	NP	NP	0.0	76.7	23.3		0.1308	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	SS-1	1.0	12.5	NP	NP	NP	0.7	96.5	2.8		0.3846	SP	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-3	4.0	15.9	NP	NP	NP	3.1	93.9	3.0		0.3937	SP	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-7	13.5	42.5	NP	NP	NP			43.9			SM	A-4(0)
544+74.9 RT 27.7	HLA-13	T-1	18.0	33.9	NP	NP	NP	0.0	74.7	17.9	7.4	0.0996	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	SS-10	33.5	23.7	NP	NP	NP	0.2	94.6	5.2		0.2435	SP-SM	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-11	38.5	23.1	NP	NP	NP	0.0	94.5	5.5		0.2440	SP-SM	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-13	48.5	17.8	NP	NP	NP	0.0	65.7	34.3		0.1402	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	SS-14	53.5	22.2	24	17	7	0.0	46.8	53.2			CL-ML	A-4(1)

Soil Classification Summary



ALDOT
ALDOT Project No.: 15-1101-0228
Project Name: I-10 Mobile River Bridge and Bayway
Mobile, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay		D50 (mm)	USCS	AASHTO
544+74.9 RT 27.7	HLA-13	SS-16	63.5	26.0	NP	NP	NP	0.3	93.9	5.8		0.2899	SP-SM	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-18	73.5	19.7	NP	NP	NP	0.8	90.1	9.1		0.3136	SP-SM	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-22	93.5	20.8	NP	NP	NP	0.4	95.7	3.9		0.3683	SP	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-23	98.5	47.2	68	30	38			89.4			CH	A-7-5(39)
544+74.9 RT 27.7	HLA-13	SS-25	108.5	24.7	NP	NP	NP	0.0	81.2	18.8		0.1426	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	SS-29	128.5	22.9	NP	NP	NP	0.0	93.0	7.0		0.2674	SP-SM	A-3(0)
544+74.9 RT 27.7	HLA-13	SS-32	143.5	22.8	NP	NP	NP	0.0	72.8	27.2		0.1564	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	T-2	158.0	20.3	41	16	25	0.0	16.9	40.8	42.3	0.0143	CL	A-7-6(20)
544+74.9 RT 27.7	HLA-13	SS-34	168.5	16.6	25	12	13	0.0	51.4	48.6		0.0785	SC	A-6(3)
544+74.9 RT 27.7	HLA-13	SS-35	178.5	23.2	29	11	18	0.0	44.0	56.0			CL	A-6(6)
544+74.9 RT 27.7	HLA-13	SS-36	188.5	20.4	34	14	20			93.9			CL	A-6(18)
544+74.9 RT 27.7	HLA-13	SS-37	198.5	17.5	28	14	14	0.0	31.8	68.2			CL	A-6(7)
544+74.9 RT 27.7	HLA-13	SS-38	208.5	21.4	NP	NP	NP	0.0	79.5	20.5		0.1462	SM	A-2-4(0)
544+74.9 RT 27.7	HLA-13	SS-40	228.5	28.7	37	20	17			97.1			CL	A-6(17)
544+74.9 RT 27.7	HLA-13	SS-42	248.5	23.2	NP	NP	NP	0.0	75.6	24.4		0.1313	SM	A-2-4(0)
547+39.7 LT 40.3	HLA-14	SS-1	1.0	6.8	NP	NP	NP	8.3	83.7	8.0		0.3631	SP-SM	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-2	2.5	14.2	NP	NP	NP	0.6	92.9	6.5		0.3820	SP-SM	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-4	5.5	19.3	NP	NP	NP	4.0	93.1	2.9		0.5122	SP	A-1-b(0)
547+39.7 LT 40.3	HLA-14	SS-6	8.5	16.8	NP	NP	NP	8.8	89.2	2.1		0.3678	SP	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-8	18.5	36.5	26	21	5	0.0	52.8	47.2		0.0797	SC-SM	A-4(0)
547+39.7 LT 40.3	HLA-14	SS-10	28.5	20.5	NP	NP	NP	0.0	95.4	4.6		0.2326	SP	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-13	43.5	22.2	NP	NP	NP	0.2	91.2	8.6		0.2586	SP-SM	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-15	53.5	19.9	NP	NP	NP	0.0	72.2	27.8		0.1664	SM	A-2-4(0)
547+39.7 LT 40.3	HLA-14	SS-16	58.5	41.8	25	19	6	0.0	37.6	39.1	23.3	0.0492	CL-ML	A-4(1)
547+39.7 LT 40.3	HLA-14	SS-17	63.5	28.5	26	20	6	0.0	23.4	76.6			CL-ML	A-4(3)
547+39.7 LT 40.3	HLA-14	T-1	68.0	22.3	24	15	9	0.0	43.9	56.1			CL	A-4(2)
547+39.7 LT 40.3	HLA-14	SS-19	78.5	21.0	NP	NP	NP	0.8	94.8	4.3		0.3192	SP	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-21	88.5	20.9	NP	NP	NP	5.6	90.0	4.4		0.3889	SP	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-23	98.5	21.0	NP	NP	NP	1.1	94.0	4.9		0.3677	SP	A-3(0)
547+39.7 LT 40.3	HLA-14	SS-29	128.5	23.3	NP	NP	NP	0.0	95.2	4.8		0.3357	SP	A-3(0)

Soil Classification Summary



ALDOT
ALDOT Project No.: 15-1101-0228
Project Name: I-10 Mobile River Bridge and Bayway
Mobile, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay (if hydrometer data available)		D50 (mm)	USCS	AASHTO Classification
514+25.9 LT 18.8	MB-1	SS-2	1.5	57.0	NP	NP	NP	19.9	62.6	11.3	6.2	0.2928	SM	A-2-4(0)
514+25.9 LT 18.8	MB-1	SS-7	13.5	18.9	NP	NP	NP	50.1	39.0	8.4	2.5	4.7614	GP-GM	A-1-a(0)
514+25.9 LT 18.8	MB-1	SS-8	18.5	16.9	NP	NP	NP	38.4	56.9	3.2	1.5	0.5977	SP	A-1-b(0)
514+25.9 LT 18.8	MB-1	SS-11	33.5	28.7	NP	NP	NP	16.6	80.0	3.4		0.3261	SP	A-3(0)
514+25.9 LT 18.8	MB-1	SS-13	43.5	22.2	NP	NP	NP	3.9	94.0	2.1		0.4741	SP	A-1-b(0)
514+25.9 LT 18.8	MB-1	SS-14	48.5	11.7	NP	NP	NP	55.6	41.3	3.1		6.0176	GP	A-1-a(0)
514+25.9 LT 18.8	MB-1	SS-17	63.5	19.3	NP	NP	NP	9.7	81.7	8.6		0.4055	SP-SM	A-3(0)
514+25.9 LT 18.8	MB-1	T-1	90.5	40.1	52	22	30	0.0	24.3	39.4	36.3	0.0185	CH	A-7-6(23)
514+25.9 LT 18.8	MB-1	T-2	98.5	44.0	89	28	61	0.0	0.7	20.0	79.3	---	CH	A-7-6(71)
514+25.9 LT 18.8	MB-1	SS-24	103.5	23.9	21	17	4	0.0	73.3	26.7		0.1545	SC-SM	A-2-4(0)
514+25.9 LT 18.8	MB-1	SS-26	113.5	19.5	NP	NP	NP	8.9	87.8	3.3		0.7445	SP	A-1-b(0)
514+25.9 LT 18.8	MB-1	SS-29	128.5	23.7	53	21	32	0.2	4.8	95.0		---	CH	A-7-6(34)
514+25.9 LT 18.8	MB-1	SS-33	148.5	22.5	NP	NP	NP	0.0	89.5	10.5		0.1997	SP-SM	A-2-4(0)
514+25.9 LT 18.8	MB-1	SS-35	163.5	23.8	NP	NP	NP	3.6	84.9	11.5		0.1583	SP-SM	A-2-4(0)
514+25.9 LT 18.8	MB-1	SS-36	168.5	23.2	36	13	23	0.0	51.6	48.4		0.0895	SC	A-6(7)
514+25.9 LT 18.8	MB-1	SS-39	183.5	26.5	NP	NP	NP	0.0	90.3	9.7		0.1758	SP-SM	A-3(0)
514+25.9 LT 18.8	MB-1	T-4	188.5	17.8	28	14	14	0.0	37.1	62.9		---	CL	A-6(6)
514+25.9 LT 18.8	MB-1	SS-40	193.5	21.0	46	16	30	0.0	8.3	91.7		---	CL	A-7-6(29)
514+25.9 LT 18.8	MB-1	SS-42	208.5	17.0	39	15	24	0.0	11.3	88.7		---	CL	A-6(21)
514+25.9 LT 18.8	MB-1	SS-45	238.5	25.3	NP	NP	NP	0.0	72.0	28.0		0.1152	SM	A-2-4(0)
514+25.9 LT 18.8	MB-1	SS-50	288.5	21.1	NP	NP	NP	2.4	86.7	10.9		0.2976	SP-SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-3	6.0	18.7	NP	NP	NP	2.1	94.1	3.8		0.4165	SP	A-3(0)
527+75.9 LT 22.0	MB-2	SS-8	28.5	22.7	NP	NP	NP	0.1	92.3	7.6		0.289	SP-SM	A-3(0)
527+75.9 LT 22.0	MB-2	SS-14	37.5	28.4	NP	NP	NP	0.0	89.9	10.1		0.274	SP-SM	A-3(0)
527+75.9 LT 22.0	MB-2	SS-22	49.5	23.2	NP	NP	NP	5.3	88.7	6.0		0.3947	SP-SM	A-3(0)
527+75.9 LT 22.0	MB-2	SS-26	55.5	29.4	NP	NP	NP	0.3	95.9	3.8		0.3456	SP	A-3(0)
527+75.9 LT 22.0	MB-2	SS-30	68.5	25.3	NP	NP	NP	0.0	95.1	4.9		0.3281	SP	A-3(0)



thompson
ENGINEERING

Soil Classification Summary

Alabama Department of Transportation

ALDOT PE Project No.: DPI-0030(005)

Project Name: Mobile River Bridge - Main Span Unit

Thompson Project No.: 17-1101-0145

Mobile, Mobile County, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200		D50 (mm)	USCS	AASHTO Classification
										% Silt	% Clay			
(if hydrometer data available)														
527+75.9 LT 22.0	MB-2	SS-32	78.5	22.3	NP	NP	NP	1.4	91.8	6.8		0.3907	SP-SM	A-3(0)
527+75.9 LT 22.0	MB-2	SS-35	93.5	37.7	NP	NP	NP	0.0	8.1	29.1	62.8	0.0011	ML	A-4(0)
527+75.9 LT 22.0	MB-2	SS-36	98.5	25.9	NP	NP	NP	0.0	87.7	12.3		0.2101	SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-38	108.5	29.5	NP	NP	NP	0.0	93.1	6.9		0.2576	SP-SM	A-3(0)
527+75.9 LT 22.0	MB-2	SS-40	118.5	26.6	NP	NP	NP	0.0	89.3	10.7		0.1889	SP-SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-44	138.5	27.1	NP	NP	NP	0.0	33.5	50.8	15.7	0.0533	ML	A-4(0)
527+75.9 LT 22.0	MB-2	T-2	140.0	23.8	29	18	11	0.0	28.4	52.2	19.4	0.0416	CL	A-6(6)
527+75.9 LT 22.0	MB-2	T-3	145.0	21.0	23	18	5	0.0	18.3	57.8	23.9	0.0371	CL-ML	A-4(2)
527+75.9 LT 22.0	MB-2	SS-46	148.5	22.6	26	14	12	0.0	21.1	52.6	26.3	0.0251	CL	A-6(7)
527+75.9 LT 22.0	MB-2	SS-48	158.5	22.7	NP	NP	NP	0.0	82.4	17.6		0.4834	SM	A-1-b(0)
527+75.9 LT 22.0	MB-2	SS-50	168.5	29.9	28	15	13	0.0	44.1	38.3	17.6	0.0613	CL	A-6(4)
527+75.9 LT 22.0	MB-2	SS-52	178.5	28.5	NP	NP	NP	0.6	74.9	24.5		0.1107	SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-54	188.5	17.6	32	16	16	0.0	21.9	58.4	19.7	0.0296	CL	A-6(11)
527+75.9 LT 22.0	MB-2	T-4	190.0	42.2	35	14	21	0.0	32.6	39.8	27.6	0.0413	CL	A-6(11)
527+75.9 LT 22.0	MB-2	SS-56	198.5	23.0	26	15	11	0.0	24.2	56.6	19.2	0.0396	CL	A-6(6)
527+75.9 LT 22.0	MB-2	T-5	210.0	14.4	33	13	20	0.0	30.8	30.1	39.1	0.0167	CL	A-6(11)
527+75.9 LT 22.0	MB-2	SS-58	218.5	17.2	36	15	21	0.0	5.9	53.0	41.1	0.0099	CL	A-6(19)
527+75.9 LT 22.0	MB-2	ST-6	228.5	26.2	29	23	6	0.0	27.2	61.5	11.3	0.0529	ML	A-4(3)
527+75.9 LT 22.0	MB-2	SS-60	238.5	23.1	NP	NP	NP	0.0	72.3	27.7		0.1176	SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-62	258.5	21.7	29	16	13	0.0	19.8	60.0	20.2	0.0341	CL	A-6(8)
527+75.9 LT 22.0	MB-2	T-7	270.0	19.6	NP	NP	NP	0.0	54.4	34.3	11.3	0.0865	SM	A-4(0)
527+75.9 LT 22.0	MB-2	SS-64	278.5	25.3	NP	NP	NP	0.0	83.5	16.5		0.2302	SM	A-2-4(0)
527+75.9 LT 22.0	MB-2	SS-66	298.5	23.4	NP	NP	NP	0.0	77.8	22.2		0.2083	SM	A-2-4(0)
528+88.0 RT 32.9	MB-2A	SS-5	6.0	73.4	33	18	15	3.0	42.4	54.6		---	CL	A-6(5)
528+88.0 RT 32.9	MB-2A	SS-8	18.5	26.4	NP	NP	NP	0.0	83.2	16.8		0.2754	SM	A-2-4(0)
528+88.0 RT 32.9	MB-2A	SS-14	48.5	21.7	NP	NP	NP	1.4	97.1	1.5		0.5527	SP	A-1-b(0)
528+88.0 RT 32.9	MB-2A	SS-20	78.5	21.2	NP	NP	NP	1.0	96.7	2.3		0.3799	SP	A-3(0)



Soil Classification Summary

Alabama Department of Transportation

ALDOT PE Project No.: DPI-0030(005)
Project Name: Mobile River Bridge - Main Span Unit
Thompson Project No.: 17-1101-0145
Mobile, Mobile County, Alabama

[illegible]

Soil Classification Summary

Alabama Department of Transportation

ALDOT PE Project No.: DPI-0030(005)

Project Name: Mobile River Bridge - Main Span Unit

Thompson Project No.: 17-1101-0145

Mobile, Mobile County, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay	D50 (mm)	USCS	AASHTO
141+91.2 LT 7.3	TH-11	SS-11	38.5	21.5	NP	NP	NP	0.6	95.9	3.5	0.3511	SP	A-3(0)
141+91.2 LT 7.3	TH-11	SS-16	63.5	20.2	NP	NP	NP	8.3	84.4	7.3	0.6244	SP-SM	A-1-b(0)
141+91.2 LT 7.3	TH-11	SS-20	83.5	34.9	60	16	44	0.0	22.9	77.1		CH	A-7-6(34)
141+91.2 LT 7.3	TH-11	SS-21	88.0	23.6	NP	NP	NP	0.0	90.9	9.1	0.2338	SP-SM	A-3(0)
141+91.2 LT 7.3	TH-11	T-3	93.0	41.9	59	24	35	0.0	7.5	92.5		CH	A-7-6(36)
141+91.2 LT 7.3	TH-11	SS-22	98.5	65.9	110	35	75	0.0	4.1	95.9		CH	A-7-5(86)
141+91.2 LT 7.3	TH-11	SS-23	103.5	22.7	NP	NP	NP	0.0	64.2	35.8	0.1015	SM	A-4(0)
141+91.2 LT 7.3	TH-11	SS-25	113.5	25.0	NP	NP	NP	0.0	89.9	10.1	0.1855	SP-SM	A-3(0)
141+91.2 LT 7.3	TH-11	SS-26	118.5	29.6	NP	NP	NP	0.0	75.5	24.5	0.1275	SM	A-2-4(0)
141+91.2 LT 7.3	TH-11	SS-27	123.5	26.2	NP	NP	NP	0.0	81.2	18.8	0.1548	SM	A-2-4(0)
141+91.2 LT 7.3	TH-11	SS-29	133.5	21.6	NP	NP	NP	0.1	94.7	5.1	0.2721	SP-SM	A-3(0)
141+91.2 LT 7.3	TH-11	SS-31	143.5	20.9	NP	NP	NP	0.8	92.7	6.4	0.3073	SP-SM	A-3(0)
1206+11.1 LT 2.5	TH-12	SS-2	1.5	12.8	NP	NP	NP	0.1	79.0	20.9	0.1888	SM	A-2-4(0)
1206+11.1 LT 2.5	TH-12	SS-5	6.0	16.1	18	13	5	2.3	72.6	25.1	0.1600	SC-SM	A-2-4(0)
1206+11.1 LT 2.5	TH-12	SS-8	18.5	28.8	NP	NP	NP	0.0	73.1	26.9	0.1700	SM	A-2-4(0)
1206+11.1 LT 2.5	TH-12	T-1	28.0	73.6	111	37	74	0.0	1.0	99.0		CH	A-7-5(89)
1206+11.1 LT 2.5	TH-12	SS-11	38.5	27.9	NP	NP	NP	0.0	80.8	19.2	0.1593	SM	A-2-4(0)
1206+11.1 LT 2.5	TH-12	SS-14	53.5	24.0	NP	NP	NP	0.0	94.1	5.9	0.2838	SP-SM	A-3(0)
1206+11.1 LT 2.5	TH-12	SS-18	73.5	23.8	NP	NP	NP	3.0	88.2	8.8	0.4616	SW-SM	A-1-b(0)
1206+11.1 LT 2.5	TH-12	SS-20	83.5	23.3	NP	NP	NP	0.1	95.6	4.3	0.3541	SP	A-3(0)
1206+11.1 LT 2.5	TH-12	SS-22	93.5	25.0	NP	NP	NP	0.0	95.0	5.0	0.3913	SP-SM	A-3(0)
153+01.7 RT 78.9	TH-13	SS-2	1.5	9.2	NP	NP	NP	1.5	73.8	24.7	0.2113	SM	A-2-4(0)
153+01.7 RT 78.9	TH-13	SS-3	3.0	15.1	NP	NP	NP	0.3	79.2	20.6	0.2592	SM	A-2-4(0)
153+01.7 RT 78.9	TH-13	SS-5	6.0	13.9	18	13	5	0.0	75.5	24.5	0.2194	SC-SM	A-2-4(0)
153+01.7 RT 78.9	TH-13	SS-9	25.0	28.6	24	18	6	0.0	71.8	28.2	0.1635	SC-SM	A-2-4(0)
153+01.7 RT 78.9	TH-13	T-2	28.0	98.2	83	46	37	0.0	24.1	75.9		MH	A-7-5(33)
153+01.7 RT 78.9	TH-13	SS-10	33.5	25.9	NP	NP	NP	0.0	71.1	28.9	0.1134	SM	A-2-4(0)
153+01.7 RT 78.9	TH-13	SS-13	48.5	24.2	NP	NP	NP	0.0	93.4	6.6	0.3123	SP-SM	A-3(0)
153+01.7 RT 78.9	TH-13	SS-16	63.5	21.9	NP	NP	NP	0.1	93.2	6.8	0.3322	SP-SM	A-3(0)
153+01.7 RT 78.9	TH-13	SS-19	78.5	21.2	NP	NP	NP	2.2	84.3	13.5	0.2636	SM	A-2-4(0)

Soil Classification Summary



ALDOT
ALDOT Project No.: 15-1101-0228
Project Name: I-10 Mobile River Bridge and Bayway
Mobile, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay	D50 (mm)	USCS	AASHTO
153+01.7 RT 78.9	TH-13	SS-22	93.5	13.8	NP	NP	NP	11.8	82.5	5.7	0.8108	SW-SM	A-1-b(0)
153+01.7 RT 78.9	TH-13	T-3	108.5	40.8	67	22	45	0.0	6.6	93.4		CH	A-7-6(47)
153+01.7 RT 78.9	TH-13	T-4	118.5	30.4	54	18	36	0.0	13.7	86.3		CH	A-7-6(32)
153+01.7 RT 78.9	TH-13	SS-26	123.5	23.8	22	13	9	0.0	57.9	42.1	0.0915	SC	A-4(1)
153+01.7 RT 78.9	TH-13	SS-30	143.5	18.8	NP	NP	NP	0.7	91.7	7.6	0.4167	SP-SM	A-3(0)
9014+62.1 LT 4.9	TH-24	SS-2	1.5	11.5	NP	NP	NP	1.8	78.4	19.9	0.2429	SM	A-2-4(0)
9014+62.1 LT 4.9	TH-24	SS-4	4.5	22.1	27	16	11	16.1	64.1	19.8	0.2386	SC	A-2-6(0)
9014+62.1 LT 4.9	TH-24	SS-7	13.5	23.4	NP	NP	NP	0.0	76.1	23.9	0.1940	SM	A-2-4(0)
906+09.3 LT 1.4	TH-25	SS-2	2.6	16.5	NP	NP	NP	11.0	72.9	16.1	0.3121	SM	A-2-4(0)
906+09.3 LT 1.4	TH-25	SS-4	5.6	19.1	31	13	18	0.0	67.8	32.2	0.1620	SC	A-2-6(1)
906+09.3 LT 1.4	TH-25	SS-7	14.6	23.1	NP	NP	NP	0.0	81.4	18.6	0.2095	SM	A-2-4(0)
906+09.3 LT 1.4	TH-25	SS-9	24.6	26.9	NP	NP	NP	0.2	88.8	11.0	0.2803	SP-SM	A-2-4(0)
23+83.8 LT 52.0	TH-26	SS-1	0.0	22.2	NP	NP	NP	9.2	69.2	21.6	0.2147	SM	A-2-4(0)
23+83.8 LT 52.0	TH-26	SS-2	1.5	13.7	NP	NP	NP	2.7	74.0	23.3	0.1438	SM	A-2-4(0)
23+83.8 LT 52.0	TH-26	SS-4	4.5	18.9	NP	NP	NP	0.0	78.9	21.1	0.1512	SM	A-2-4(0)
23+83.8 LT 52.0	TH-26	SS-6	10.5	43.6	NP	NP	NP	0.0	46.4	53.6		ML	A-4(0)
23+83.8 LT 52.0	TH-26	SS-9	25.5	27.2	29	18	11	0.0	50.5	49.5	0.0756	SC	A-6(3)
23+83.8 LT 52.0	TH-26	SS-11	33.5	24.3	NP	NP	NP	0.0	92.8	7.2	0.2775	SP-SM	A-3(0)
919+00.1 RT 7.6	TH-27	SS-1	1.7	8.7	NP	NP	NP	5.2	87.3	7.5	0.3177	SP-SM	A-3(0)
919+00.1 RT 7.6	TH-27	SS-4	6.2	3.9	NP	NP	NP	1.3	91.3	7.5	0.2652	SP-SM	A-3(0)
919+00.1 RT 7.6	TH-27	SS-7	15.2	18.1	NP	NP	NP	0.0	81.6	18.4	0.1620	SM	A-2-4(0)
919+00.1 RT 7.6	TH-27	SS-8	20.2	31.3	NP	NP	NP	0.0	52.1	47.9	0.0779	SM	A-4(0)
919+00.1 RT 7.6	TH-27	SS-9	25.2	126.3	67	31	36	0.0	33.7	66.3		CH	A-7-5(24)
919+00.1 RT 7.6	TH-27	T-1	27.2	167.5	80	49	31	0.0	68.1	31.9	0.3056	SM	A-2-7(4)
919+00.1 RT 7.6	TH-27	SS-11	35.2	51.7	68	24	44	0.0	9.6	90.4		CH	A-7-6(44)
4233+05.5 LT 83.3	W-01	SS-1	1.0	14.8	NP	NP	NP	6.5	72.6	20.8	0.2209	SM	A-2-4(0)
4233+05.5 LT 83.3	W-01	SS-2	2.5	21.8	NP	NP	NP	6.4	71.8	21.8	0.1970	SM	A-2-4(0)
4233+05.5 LT 83.3	W-01	SS-4	5.5	16.7	NP	NP	NP	0.0	80.2	19.8	0.1549	SM	A-2-4(0)
4233+05.5 LT 83.3	W-01	SS-5	7.0	20.0	NP	NP	NP	0.0	83.0	17.0	0.1554	SM	A-2-4(0)
4233+05.5 LT 83.3	W-01	SS-7	14.5	25.9	NP	NP	NP	0.0	71.0	29.0	0.1600	SM	A-2-4(0)

Soil Classification Summary



ALDOT
ALDOT Project No.: 15-1101-0228
Project Name: I-10 Mobile River Bridge and Bayway
Mobile, Alabama

Station & Offset	Boring No.	Sample ID	Depth (ft)	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	% Gravel	% Sand	% Pass 200 % Silt % Clay		D50 (mm)	USCS	AASHTO
564+40.6 LT 21.7	HLA-21	SS-31	148.5	19.3	49	17	32	0.0	13.8	86.2			CL	A-7-6(28)
564+40.6 LT 21.7	HLA-21	SS-34	178.5	20.2	47	16	31	0.0	7.2	92.8			CL	A-7-6(30)
564+40.6 LT 21.7	HLA-21	SS-35	188.5	21.9	35	17	18	0.0	2.5	97.5			CL	A-6(17)
564+40.6 LT 21.7	HLA-21	SS-36	198.5	18.8	39	13	26	0.0	18.1	81.9			CL	A-6(20)
564+40.6 LT 21.7	HLA-21	SS-39	228.5	19.2	NP	NP	NP	0.0	71.5	28.5		0.1413	SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-2	1.5	16.1	NP	NP	NP	0.0	87.8	12.2		0.1820	SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-4	4.5	24.2	NP	NP	NP	0.0	88.4	11.6		0.1845	SP-SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-7	13.5	31.8	NP	NP	NP	0.0	66.8	33.2		0.1258	SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-8	18.5	66.5	69	45	24			46.2			SM	A-7-5(8)
497+92.5 LT 26.8	WHLA-01	SS-9	28.5	23.3	NP	NP	NP	0.0	94.5	5.5		0.3132	SP-SM	A-3(0)
497+92.5 LT 26.8	WHLA-01	SS-11	38.5	18.9	NP	NP	NP	0.3	92.6	7.1		0.3081	SP-SM	A-3(0)
497+92.5 LT 26.8	WHLA-01	SS-15	58.5	24.4	NP	NP	NP	0.2	83.3	16.5		0.2729	SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-20	83.5	26.7	NP	NP	NP	0.6	91.2	8.2		0.1674	SP-SM	A-3(0)
497+92.5 LT 26.8	WHLA-01	ST-4	113.5	44.3	87	29	58	0.0	1.1	18.3	80.6		CH	A-7-6(68)
497+92.5 LT 26.8	WHLA-01	SS-28	133.5	11.1	NP	NP	NP	0.7	93.4	5.9		0.3467	SP-SM	A-3(0)
497+92.5 LT 26.8	WHLA-01	SS-36	178.5	19.5	NP	NP	NP	0.0	91.3	8.7		0.2151	SP-SM	A-3(0)
497+92.5 LT 26.8	WHLA-01	SS-39	193.5	29.1	38	21	17	0.0	54.1	45.9		0.0848	SC	A-6(4)
497+92.5 LT 26.8	WHLA-01	ST-6	198.5	56.2	30	14	16	0.0	16.7	54.4	28.9	0.0404	CL	A-6(11)
497+92.5 LT 26.8	WHLA-01	ST-7	218.5	18.8	36	16	20	0.0	17.1	53.7	29.2	0.0355	CL	A-6(15)
497+92.5 LT 26.8	WHLA-01	ST-8	238.5	24.9	NP	NP	NP	0.0	74.0	13.4	12.6	0.1789	SM	A-2-4(0)
497+92.5 LT 26.8	WHLA-01	SS-43	258.5	21.6	NP	NP	NP	0.0	57.8	42.2		0.0918	SM	A-4(0)
509+17.5 LT 5.8	WHLA-03	SS-2	1.5	34.6	NP	NP	NP	15.4	66.8	17.8		0.2102	SM	A-2-4(0)
509+17.5 LT 5.8	WHLA-03	SS-4	4.5	24.5	NP	NP	NP	0.0	91.7	8.3		0.1820	SP-SM	A-3(0)
509+17.5 LT 5.8	WHLA-03	SS-9	28.5	25.6	NP	NP	NP	0.0	96.6	3.4		0.2889	SP	A-3(0)
509+17.5 LT 5.8	WHLA-03	SS-15	58.5	23.7	NP	NP	NP	0.0	90.1	9.9		0.2508	SP-SM	A-3(0)
509+17.5 LT 5.8	WHLA-03	SS-17	68.5	18.3	NP	NP	NP	1.2	87.9	10.9		0.5673	SP-SM	A-1-b(0)
509+17.5 LT 5.8	WHLA-03	SS-21	88.5	22.5	NP	NP	NP	0.5	92.4	7.1		0.3353	SP-SM	A-3(0)
509+17.5 LT 5.8	WHLA-03	ST-2	93.5	46.9	81	25	56	0.0	1.5	36.0	62.5	0.0014	CH	A-7-6(65)
509+17.5 LT 5.8	WHLA-03	SS-22	103.5	77.0	82	32	50			38.6			SC	A-7-5(11)
509+17.5 LT 5.8	WHLA-03	SS-23	113.5	29.7	NP	NP	NP	0.0	76.9	23.1		0.1957	SM	A-2-4(0)

Soil Classification Summary



ALDOT
ALDOT Project No.: 15-1101-0228
Project Name: I-10 Mobile River Bridge and Bayway
Mobile, Alabama

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-12	HLA-12	HLA-12	HLA-12	HLA-12	HLA-12
Station	541+43.3	541+43.3	541+43.3	541+43.3	541+43.3	541+43.3
Offset	LT 45.4	LT 45.4	LT 45.4	LT 45.4	LT 45.4	LT 45.4
Sample ID	SS-2	SS-6	SS-11	SS-15	SS-20	SS-22
Depth (ft)	1.5	8.5	33.5	53.5	78.5	88.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	89.4	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	89.4	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	98.7	86.6	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	96.5	77.3	99.9	99.8	99.3	98.1
#10 SIEVE (2.00mm)	94.1	60.0	98.9	99.2	97.5	96.1
#20 SIEVE (0.85mm)	84.4	43.5	97.1	97.5	79.7	87.1
#40" SIEVE (425um)	51.5	24.5	84.6	81.1	42.9	61.5
#60 SIEVE (250um)	18.7	8.9	49.7	22.3	22.7	26.6
#100 SIEVE (150um)	6.4	3.6	10.7	8.0	9.9	10.1
#140 SIEVE (106um)	4.7	2.9	5.4	5.8	6.6	7.1
#200 SIEVE (75um)	3.9	2.5	3.8	4.5	4.9	5.4
Clay						
Silt						
Total Sand	92.6	74.8	96.1	95.3	94.5	92.6
Total Gravel	3.5	22.7	0.1	0.2	0.7	1.9
ATTERBERG LIMITS						
Liquid Limit	NP	NP	NP	NP	NP	NP
Plastic Limit	NP	NP	NP	NP	NP	NP
Plasticity Index	NP	NP	NP	NP	NP	NP
USCS	SP	SP	SP	SP	SP	SP-SM
AASHTO	A-3(0)	A-1-b(0)	A-3(0)	A-3(0)	A-1-b(0)	A-3(0)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-12	HLA-12	HLA-12	HLA-12	HLA-12	HLA-12
Station	541+43.3	541+43.3	541+43.3	541+43.3	541+43.3	541+43.3
Offset	LT 45.4	LT 45.4	LT 45.4	LT 45.4	LT 45.4	LT 45.4
Sample ID	T-1	SS-26	SS-31	SS-33	SS-34	T-2
Depth (ft)	108.0	113.5	138.5	148.5	158.5	188.0
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	99.7	99.5	100.0	100.0	100.0
#10 SIEVE (2.00mm)	100.0	98.8	98.8	99.9	98.6	100.0
#20 SIEVE (0.85mm)	99.9	98.4	95.2	99.8	97.0	99.9
#40" SIEVE (425um)	99.5	97.7	69.9	99.0	91.9	99.8
#60 SIEVE (250um)	99.0	96.3	31.8	97.8	86.5	99.7
#100 SIEVE (150um)	98.0	89.0	11.1	96.9	81.1	98.6
#140 SIEVE (106um)	97.0	71.8	8.1	95.6	74.9	95.6
#200 SIEVE (75um)	96.2	50.1	6.3	92.6	66.1	89.0

Clay

Silt

Total Sand	3.8	49.6	93.2	7.4	33.9	11.0
------------	-----	------	------	-----	------	------

Total Gravel	0.0	0.3	0.5	0.0	0.0	0.0
--------------	-----	-----	-----	-----	-----	-----

ATTERBERG LIMITS

Liquid Limit	97	NP	NP	39	46	29
--------------	----	----	----	----	----	----

Plastic Limit	26	NP	NP	15	15	15
---------------	----	----	----	----	----	----

Plasticity Index	71	NP	NP	24	31	14
------------------	----	----	----	----	----	----

USCS	CH	ML	SP-SM	CL	CL	CL
------	----	----	-------	----	----	----

AASHTO	A-7-6(79)	A-4(0)	A-3(0)	A-6(22)	A-7-6(18)	A-6(11)
--------	-----------	--------	--------	---------	-----------	---------

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-12	HLA-12	HLA-12	HLA-12	HLA-13	HLA-13
Station	541+43.3	541+43.3	541+43.3	541+43.3	544+74.9	544+74.9
Offset	LT 45.4	LT 45.4	LT 45.4	LT 45.4	RT 27.7	RT 27.7
Sample ID	SS-38	SS-40	SS-41	SS-42	SS-1	SS-3
Depth (ft)	208.5	228.5	238.5	248.5	1.0	4.0
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	100.0	100.0	100.0	99.3	96.9
#10 SIEVE (2.00mm)	100.0	100.0	100.0	100.0	97.6	94.5
#20 SIEVE (0.85mm)	99.4	99.2	99.9	99.9	90.6	87.1
#40" SIEVE (425um)	98.2	98.1	99.0	98.8	57.5	55.4
#60 SIEVE (250um)	94.9	94.7	91.0	87.9	17.5	18.0
#100 SIEVE (150um)	79.5	87.5	65.1	57.2	5.1	5.3
#140 SIEVE (106um)	64.2	82.3	45.9	38.9	3.7	3.7
#200 SIEVE (75um)	51.3	74.0	31.0	23.3	2.8	3.0

Clay

Silt

Total Sand	48.7	26.0	69.0	76.7	96.5	93.9
------------	------	------	------	------	------	------

Total Gravel	0.0	0.0	0.0	0.0	0.7	3.1
--------------	-----	-----	-----	-----	-----	-----

ATTERBERG LIMITS

Liquid Limit	32	34	NP	NP	NP	NP
Plastic Limit	16	19	NP	NP	NP	NP
Plasticity Index	16	15	NP	NP	NP	NP

USCS	CL	CL	SM	SM	SP	SP
AASHTO	A-6(5)	A-6(10)	A-2-4(0)	A-2-4(0)	A-3(0)	A-3(0)

BMT-5

Client: ALDOT
Project: I-10 Mobile River Bridge and Bayway
ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
Region: Southwest Region
Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13
Station	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9
Offset	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7
Sample ID	SS-7	T-1	SS-10	SS-11	SS-13	SS-14
Depth (ft)	13.5	18.0	33.5	38.5	48.5	53.5
TOTAL PASSING (%)						
3" SIEVE (75mm)		100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)		100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)		100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)		100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)		100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)		100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)		100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)		100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)		100.0	99.8	100.0	100.0	100.0
#10 SIEVE (2.00mm)		100.0	99.8	99.9	100.0	100.0
#20 SIEVE (0.85mm)		99.9	98.9	99.1	99.5	99.9
#40" SIEVE (425um)		98.4	88.4	89.1	92.4	98.9
#60 SIEVE (250um)		92.5	52.1	51.8	71.2	95.1
#100 SIEVE (150um)		77.1	12.4	13.2	51.6	88.1
#140 SIEVE (106um)		55.4	6.6	6.9	43.6	75.5
#200 SIEVE (75um)	43.9	25.3	5.2	5.5	34.3	53.2
Clay		7.4				
Silt		17.9				
Total Sand		74.7	94.6	94.5	65.7	46.8
Total Gravel		0.0	0.2	0.0	0.0	0.0
ATTERBERG LIMITS						
Liquid Limit	NP	NP	NP	NP	NP	24
Plastic Limit	NP	NP	NP	NP	NP	17
Plasticity Index	NP	NP	NP	NP	NP	7
USCS	SM	SM	SP-SM	SP-SM	SM	CL-ML
AASHTO	A-4(0)	A-2-4(0)	A-3(0)	A-3(0)	A-2-4(0)	A-4(1)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13
Station	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9
Offset	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7
Sample ID	SS-16	SS-18	SS-22	SS-23	SS-25	SS-29
Depth (ft)	63.5	73.5	93.5	98.5	108.5	128.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0		100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0		100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0		100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0		100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0		100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0		100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0		100.0	100.0
3/8" SIEVE (9.5mm)	100.0	99.2	100.0		100.0	100.0
#4 SIEVE (4.75mm)	99.7	99.2	99.6		100.0	100.0
#10 SIEVE (2.00mm)	99.5	99.2	99.1		100.0	100.0
#20 SIEVE (0.85mm)	98.7	98.4	95.3		100.0	99.8
#40" SIEVE (425um)	87.0	75.3	60.0		99.8	93.1
#60 SIEVE (250um)	35.6	31.1	23.0		92.5	43.7
#100 SIEVE (150um)	10.1	16.5	7.7		53.5	14.2
#140 SIEVE (106um)	7.4	12.3	5.3		29.7	9.5
#200 SIEVE (75um)	5.8	9.1	3.9	89.4	18.8	7.0
Clay						
Silt						
Total Sand	93.9	90.1	95.7		81.2	93.0
Total Gravel	0.3	0.8	0.4		0.0	0.0
ATTERBERG LIMITS						
Liquid Limit	NP	NP	NP	68	NP	NP
Plastic Limit	NP	NP	NP	30	NP	NP
Plasticity Index	NP	NP	NP	38	NP	NP
USCS	SP-SM	SP-SM	SP	CH	SM	SP-SM
AASHTO	A-3(0)	A-3(0)	A-3(0)	A-7-5(39)	A-2-4(0)	A-3(0)

BMT-5

Client: ALDOT
Project: I-10 Mobile River Bridge and Bayway
ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
Region: Southwest Region
Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13	HLA-13
Station	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9	544+74.9
Offset	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7	RT 27.7
Sample ID	SS-32	T-2	SS-34	SS-35	SS-36	SS-37
Depth (ft)	143.5	158.0	168.5	178.5	188.5	198.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0		100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0		100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0		100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0		100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0		100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0		100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0		100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0		100.0
#4 SIEVE (4.75mm)	100.0	100.0	100.0	100.0		100.0
#10 SIEVE (2.00mm)	100.0	100.0	100.0	99.7		100.0
#20 SIEVE (0.85mm)	99.8	100.0	99.9	99.2		99.2
#40" SIEVE (425um)	99.1	99.7	99.6	97.9		96.0
#60 SIEVE (250um)	82.1	99.1	97.5	92.8		92.8
#100 SIEVE (150um)	47.1	96.2	77.3	78.3		83.6
#140 SIEVE (106um)	34.8	91.4	59.1	64.0		76.0
#200 SIEVE (75um)	27.2	83.1	48.6	56.0	93.9	68.2

Clay		42.3				
Silt		40.8				
Total Sand	72.8	16.9	51.4	44.0		31.8
Total Gravel	0.0	0.0	0.0	0.0		0.0

ATTERBERG LIMITS

Liquid Limit	NP	41	25	29	34	28
Plastic Limit	NP	16	12	11	14	14
Plasticity Index	NP	25	13	18	20	14

USCS	SM	CL	SC	CL	CL	CL
AASHTO	A-2-4(0)	A-7-6(20)	A-6(3)	A-6(6)	A-6(18)	A-6(7)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	HLA-13	HLA-13	HLA-13	HLA-14	HLA-14	HLA-14
Station	544+74.9	544+74.9	544+74.9	547+39.7	547+39.7	547+39.7
Offset	RT 27.7	RT 27.7	RT 27.7	LT 40.3	LT 40.3	LT 40.3
Sample ID	SS-38	SS-40	SS-42	SS-1	SS-2	SS-4
Depth (ft)	208.5	228.5	248.5	1.0	2.5	5.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0		100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0		100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0		100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0		100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0		100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0		100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0		100.0	97.7	100.0	100.0
3/8" SIEVE (9.5mm)	100.0		100.0	94.2	100.0	100.0
#4 SIEVE (4.75mm)	100.0		100.0	91.7	99.4	96.0
#10 SIEVE (2.00mm)	100.0		100.0	89.5	96.3	91.0
#20 SIEVE (0.85mm)	99.9		99.9	82.7	87.3	77.0
#40" SIEVE (425um)	99.5		99.8	59.2	57.9	40.0
#60 SIEVE (250um)	97.4		87.6	28.1	18.8	12.4
#100 SIEVE (150um)	51.8		56.5	12.4	11.7	4.5
#140 SIEVE (106um)	27.3		39.6	9.6	8.6	3.5
#200 SIEVE (75um)	20.5	97.1	24.4	8.0	6.5	2.9
Clay						
Silt						
Total Sand	79.5		75.6	83.7	92.9	93.1
Total Gravel	0.0		0.0	8.3	0.6	4.0
ATTERBERG LIMITS						
Liquid Limit	NP	37	NP	NP	NP	NP
Plastic Limit	NP	20	NP	NP	NP	NP
Plasticity Index	NP	17	NP	NP	NP	NP
USCS	SM	CL	SM	SP-SM	SP-SM	SP
AASHTO	A-2-4(0)	A-6(17)	A-2-4(0)	A-3(0)	A-3(0)	A-1-b(0)



BMT-5

Page 1

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-1	MB-1	MB-1	MB-1	MB-1	MB-1
Station		514+25.9	514+25.9	514+25.9	514+25.9	514+25.9	514+25.9
Offset		LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8
Sample ID		SS-2	SS-7	SS-8	SS-11	SS-13	SS-14
Depth (ft)		1.5	13.5	18.5	33.5	43.5	48.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	100.0	---	---	---
3/4"	" (19mm)	100.0	100.0	89.2	100.0	---	100.0
1/2"	" (12.5mm)	92.3	89.8	78.8	90.6	100.0	79.9
3/8"	" (9.5mm)	87.9	78.6	69.3	86.2	98.1	60.8
#4	" (4.75mm)	80.1	49.9	61.6	83.4	96.1	44.4
#10	" (2.00mm)	71.6	33.2	55.8	81.9	95.2	36.0
#20	" (0.85mm)	66.3	28.4	51.3	80.2	90.0	30.5
#40	" (425um)	59.5	25.0	48.8	73.9	42.5	19.2
#60	" (250um)	46.0	20.4	25.2	26.0	7.3	8.5
#100	" (150um)	28.4	14.9	9.1	5.8	3.0	4.2
#140	" (106um)	21.7	12.6	6.3	4.2	2.5	3.5
#200	" (75um)	17.6	10.9	4.7	3.4	2.1	3.1
Clay		6.2	2.5	1.5	3.4	2.1	3.1
Silt		11.3	8.4	3.2			
Total Sand		62.6	39.0	56.9	80.0	94.0	41.3
Total Gravel		19.9	50.1	38.4	16.6	3.9	55.6
ATTERBERG LIMITS							
Liquid Limit		NP	NP	NP	NP	NP	NP
Plastic Limit		NP	NP	NP	NP	NP	NP
Plasticity Index		NP	NP	NP	NP	NP	NP
USCS		SM	GP-GM	SP	SP	SP	GP
AASHTO		A-2-4(0)	A-1-a(0)	A-1-b(0)	A-3(0)	A-1-b(0)	A-1-a(0)



BMT-5

Page 2

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-1	MB-1	MB-1	MB-1	MB-1	MB-1
Station		514+25.9	514+25.9	514+25.9	514+25.9	514+25.9	514+25.9
Offset		LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8
Sample ID		SS-17	T-1	T-2	SS-24	SS-26	SS-29
Depth (ft)		63.5	90.5	98.5	103.5	113.5	128.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	100.0	---	---	---	100.0	---
3/8"	" (9.5mm)	98.9	---	---	---	95.0	100.0
#4	" (4.75mm)	90.3	---	---	100.0	91.1	99.8
#10	" (2.00mm)	85.3	---	100.0	99.7	63.5	99.3
#20	" (0.85mm)	77.1	100.0	100.0	98.5	53.9	98.9
#40	" (425um)	53.1	99.9	99.9	91.5	33.7	98.6
#60	" (250um)	18.0	98.5	99.7	77.2	10.8	98.3
#100	" (150um)	9.9	83.3	99.5	48.3	4.4	97.9
#140	" (106um)	9.1	79.6	99.4	33.8	3.6	97.3
#200	" (75um)	8.6	75.7	99.4	26.7	3.3	95.0
Clay		8.6	36.3	79.3	26.7	3.3	95.0
Silt			39.4	20.0			
Total Sand		81.7	24.3	0.7	73.3	87.8	4.8
Total Gravel		9.7	0.0	0.0	0.0	8.9	0.2
ATTERBERG LIMITS							
Liquid Limit		NP	52	89	21	NP	53
Plastic Limit		NP	22	28	17	NP	21
Plasticity Index		NP	30	61	4	NP	32
USCS		SP-SM	CH	CH	SC-SM	SP	CH
AASHTO		A-3(0)	A-7-6(23)	A-7-6(71)	A-2-4(0)	A-1-b(0)	A-7-6(34)



BMT-5

Page 3

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-1	MB-1	MB-1	MB-1	MB-1	MB-1
Station		514+25.9	514+25.9	514+25.9	514+25.9	514+25.9	514+25.9
Offset		LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8	LT 18.8
Sample ID		SS-33	SS-35	SS-36	SS-39	T-4	SS-40
Depth (ft)		148.5	163.5	168.5	183.5	188.5	193.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	100.0	---	---	---	---
1/2"	" (12.5mm)	---	96.4	---	---	---	---
3/8"	" (9.5mm)	---	96.4	---	---	---	---
#4	" (4.75mm)	---	96.4	100.0	100.0	---	---
#10	" (2.00mm)	100.0	96.2	99.5	100.0	100.0	100.0
#20	" (0.85mm)	99.9	96.0	98.3	99.8	99.8	99.9
#40	" (425um)	96.4	95.4	92.9	98.2	99.4	99.5
#60	" (250um)	68.4	80.4	77.4	85.5	96.5	98.5
#100	" (150um)	26.6	46.4	57.9	34.0	89.1	96.7
#140	" (106um)	15.7	22.0	51.5	16.6	78.1	94.3
#200	" (75um)	10.5	11.5	48.4	9.7	62.9	91.7
Clay		10.5	11.5	48.4	9.7	62.9	91.7
Silt							
Total Sand		89.5	84.9	51.6	90.3	37.1	8.3
Total Gravel		0.0	3.6	0.0	0.0	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		NP	NP	36	NP	28	46
Plastic Limit		NP	NP	13	NP	14	16
Plasticity Index		NP	NP	23	NP	14	30
USCS		SP-SM	SP-SM	SC	SP-SM	CL	CL
AASHTO		A-2-4(0)	A-2-4(0)	A-6(7)	A-3(0)	A-6(6)	A-7-6(29)



BMT-5

Page 4

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-1	MB-1	MB-1	MB-2	MB-2	MB-2
Station		514+25.9	514+25.9	514+25.9	527+75.9	527+75.9	527+75.9
Offset		LT 18.8	LT 18.8	LT 18.8	LT 22.0	LT 22.0	LT 22.0
Sample ID		SS-42	SS-45	SS-50	SS-3	SS-8	SS-14
Depth (ft)		208.5	238.5	288.5	6.0	28.5	37.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	---	---	---	---	---	---
3/8"	" (9.5mm)	---	---	100.0	100.0	100.0	---
#4	" (4.75mm)	100.0	---	97.6	97.9	99.9	100.0
#10	" (2.00mm)	100.0	100.0	97.6	89.5	99.2	99.8
#20	" (0.85mm)	99.9	99.9	97.1	76.8	95.5	97.9
#40	" (425um)	99.5	99.0	89.6	51.4	77.9	85.1
#60	" (250um)	98.6	90.5	30.6	15.7	39.5	42.7
#100	" (150um)	97.5	65.2	17.6	5.2	11.4	16.9
#140	" (106um)	95.1	45.2	13.6	4.2	8.6	12.3
#200	" (75um)	88.7	28.0	10.9	3.8	7.6	10.1
Clay		88.7	28.0	10.9	3.8	7.6	10.1
Silt							
Total Sand		11.3	72.0	86.7	94.1	92.3	89.9
Total Gravel		0.0	0.0	2.4	2.1	0.1	0.0
ATTERBERG LIMITS							
Liquid Limit		39	NP	NP	NP	NP	NP
Plastic Limit		15	NP	NP	NP	NP	NP
Plasticity Index		24	NP	NP	NP	NP	NP
USCS		CL	SM	SP-SM	SP	SP-SM	SP-SM
AASHTO		A-6(21)	A-2-4(0)	A-2-4(0)	A-3(0)	A-3(0)	A-3(0)



BMT-5

Page 5

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2	MB-2	MB-2	MB-2	MB-2	MB-2
Station		527+75.9	527+75.9	527+75.9	527+75.9	527+75.9	527+75.9
Offset		LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0
Sample ID		SS-22	SS-26	SS-30	SS-32	SS-35	SS-36
Depth (ft)		49.5	55.5	68.5	78.5	93.5	98.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	100.0	---	---	---	---	---
3/8"	" (9.5mm)	98.9	100.0	---	100.0	---	---
#4	" (4.75mm)	94.7	99.7	100.0	98.6	---	100.0
#10	" (2.00mm)	90.6	99.5	100.0	95.9	100.0	99.9
#20	" (0.85mm)	85.8	98.4	98.7	89.9	98.0	99.7
#40	" (425um)	55.5	83.4	82.7	56.4	97.1	98.5
#60	" (250um)	16.1	---	15.6	15.9	95.7	63.8
#100	" (150um)	7.3	5.7	6.4	9.2	93.6	23.2
#140	" (106um)	6.5	4.3	5.5	7.8	92.4	16.5
#200	" (75um)	6.0	3.8	4.9	6.8	91.9	12.3
Clay		6.0	3.8	4.9	6.8	62.8	12.3
Silt						29.1	
Total Sand		88.7	95.9	95.1	91.8	8.1	87.7
Total Gravel		5.3	0.3	0.0	1.4	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		NP	NP	NP	NP	NP	NP
Plastic Limit		NP	NP	NP	NP	NP	NP
Plasticity Index		NP	NP	NP	NP	NP	NP
USCS		SP-SM	SP	SP	SP-SM	ML	SM
AASHTO		A-3(0)	A-3(0)	A-3(0)	A-3(0)	A-4(0)	A-2-4(0)



BMT-5

Page 6

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2	MB-2	MB-2	MB-2	MB-2	MB-2
Station		527+75.9	527+75.9	527+75.9	527+75.9	527+75.9	527+75.9
Offset		LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0
Sample ID		SS-38	SS-40	SS-44	T-2	T-3	SS-46
Depth (ft)		108.5	118.5	138.5	140.0	145.0	148.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	---	---	---	---	---	---
3/8"	" (9.5mm)	---	---	---	---	---	---
#4	" (4.75mm)	---	---	---	---	---	---
#10	" (2.00mm)	100.0	100.0	---	100.0	100.0	100.0
#20	" (0.85mm)	99.9	99.8	100.0	99.7	99.8	100.0
#40	" (425um)	98.0	98.4	99.7	98.5	99.8	99.8
#60	" (250um)	47.1	75.3	99.2	95.3	99.7	99.5
#100	" (150um)	16.5	29.2	98.3	91.2	97.0	95.7
#140	" (106um)	9.4	16.7	89.5	84.8	89.9	87.3
#200	" (75um)	6.9	10.7	66.5	71.6	81.6	78.9
Clay		6.9	10.7	15.7	19.4	23.9	26.3
Silt				50.8	52.2	57.8	52.6
Total Sand		93.1	89.3	33.5	28.4	18.3	21.1
Total Gravel		0.0	0.0	0.0	0.0	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		NP	NP	NP	29	23	26
Plastic Limit		NP	NP	NP	18	18	14
Plasticity Index		NP	NP	NP	11	5	12
USCS		SP-SM	SP-SM	ML	CL	CL-ML	CL
AASHTO		A-3(0)	A-2-4(0)	A-4(0)	A-6(6)	A-4(2)	A-6(7)



BMT-5

Page 7

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2	MB-2	MB-2	MB-2	MB-2	MB-2
Station		527+75.9	527+75.9	527+75.9	527+75.9	527+75.9	527+75.9
Offset		LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0
Sample ID		SS-48	SS-50	SS-52	SS-54	T-4	SS-56
Depth (ft)		158.5	168.5	178.5	188.5	190.0	198.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	---	---	---	---	---	---
3/8"	" (9.5mm)	---	---	100.0	---	---	---
#4	" (4.75mm)	100.0	---	99.4	---	---	---
#10	" (2.00mm)	99.8	100.0	99.3	100.0	100.0	100.0
#20	" (0.85mm)	99.5	99.8	99.1	99.7	98.7	100.0
#40	" (425um)	38.7	99.6	98.9	97.2	93.3	99.7
#60	" (250um)	18.5	99.2	98.2	94.0	86.8	97.0
#100	" (150um)	18.0	92.0	84.7	91.0	80.9	92.2
#140	" (106um)	17.8	72.9	45.0	85.6	74.4	84.8
#200	" (75um)	17.6	56.0	24.5	78.1	67.4	75.8
Clay		17.6	17.6	24.5	19.7	27.6	19.2
Silt			38.3		58.4	39.8	56.6
Total Sand		82.4	44.1	74.9	21.9	32.6	24.2
Total Gravel		0.0	0.0	0.6	0.0	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		NP	28	NP	32	35	26
Plastic Limit		NP	15	NP	16	14	15
Plasticity Index		NP	13	NP	16	21	11
USCS		SM	CL	SM	CL	CL	CL
AASHTO		A-1-b(0)	A-6(4)	A-2-4(0)	A-6(11)	A-6(11)	A-6(6)



BMT-5

Page 8

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2	MB-2	MB-2	MB-2	MB-2	MB-2
Station		527+75.9	527+75.9	527+75.9	527+75.9	527+75.9	527+75.9
Offset		LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0	LT 22.0
Sample ID		T-5	SS-58	T-6	SS-60	SS-62	T-7
Depth (ft)		210.0	218.5	228.5	238.5	258.5	270.0
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	---	---	---	---	---	---
3/8"	" (9.5mm)	---	---	---	---	---	---
#4	" (4.75mm)	---	---	---	---	---	---
#10	" (2.00mm)	100.0	100.0	100.0	100.0	100.0	---
#20	" (0.85mm)	95.9	99.6	99.3	99.9	99.1	100.0
#40	" (425um)	94.1	99.2	99.1	99.2	98.0	98.9
#60	" (250um)	91.4	98.6	96.6	90.9	92.6	80.9
#100	" (150um)	82.9	96.8	88.7	65.1	89.2	64.3
#140	" (106um)	75.3	95.8	82.3	43.5	85.8	56.3
#200	" (75um)	69.2	94.2	72.8	27.7	80.1	45.6
Clay		39.1	41.1	11.3	27.7	20.2	11.3
Silt		30.1	53.0	61.5		60.0	34.3
Total Sand		30.8	5.9	27.2	72.3	19.8	54.4
Total Gravel		0.0	0.0	0.0	0.0	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		33	36	29	NP	29	NP
Plastic Limit		13	15	23	NP	16	NP
Plasticity Index		20	21	6	NP	13	NP
USCS		CL	CL	ML	SM	CL	SM
AASHTO		A-6(11)	A-6(19)	A-4(3)	A-2-4(0)	A-6(8)	A-4(0)



BMT-5

Page 9

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2	MB-2	MB-2A	MB-2A	MB-2A	MB-2A
Station		527+75.9	527+75.9	528+88.0	528+88.0	528+88.0	528+88.0
Offset		LT 22.0	LT 22.0	RT 32.9	RT 32.9	RT 32.9	RT 32.9
Sample ID		SS-64	SS-66	SS-5	SS-8	SS-14	SS-20
Depth (ft)		278.5	298.5	6.0	18.5	48.5	78.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	---	---	---
1/2"	" (12.5mm)	---	---	100.0	---	---	---
3/8"	" (9.5mm)	---	---	99.4	---	100.0	100.0
#4	" (4.75mm)	---	100.0	97.0	100.0	98.6	99.0
#10	" (2.00mm)	100.0	99.8	93.8	98.7	97.9	96.2
#20	" (0.85mm)	99.9	98.9	91.9	95.1	93.3	87.7
#40	" (425um)	98.9	92.9	87.1	79.2	23.6	59.9
#60	" (250um)	55.5	60.2	73.7	43.5	4.7	12.9
#100	" (150um)	21.2	31.6	61.6	19.0	2.2	3.6
#140	" (106um)	18.1	26.1	57.9	17.3	1.8	2.7
#200	" (75um)	16.5	22.2	54.6	16.8	1.5	2.3
Clay		16.5	22.2	54.6	16.8	1.5	2.3
Silt							
Total Sand		83.5	77.8	42.4	83.2	97.1	96.7
Total Gravel		0.0	0.0	3.0	0.0	1.4	1.0
ATTERBERG LIMITS							
Liquid Limit		NP	NP	33	NP	NP	NP
Plastic Limit		NP	NP	18	NP	NP	NP
Plasticity Index		NP	NP	15	NP	NP	NP
USCS		SM	SM	CL	SM	SP	SP
AASHTO		A-2-4(0)	A-2-4(0)	A-6(5)	A-2-4(0)	A-1-b(0)	A-3(0)



BMT-5

Page 10

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2A	MB-2A	MB-2A	MB-2A	MB-2A	MB-2A
Station		528+88.0	528+88.0	528+88.0	528+88.0	528+88.0	528+88.0
Offset		RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9
Sample ID		SS-21	T-2	SS-22	SS-25	T-3	SS-28
Depth (ft)		83.5	93.5	98.5	113.5	123.0	138.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	---	---	100.0	---	---
1/2"	" (12.5mm)	---	---	---	91.9	---	---
3/8"	" (9.5mm)	100.0	---	---	87.3	---	100.0
#4	" (4.75mm)	98.8	100.0	100.0	64.1	100.0	99.7
#10	" (2.00mm)	97.6	97.5	99.8	53.3	99.8	99.7
#20	" (0.85mm)	94.3	91.1	98.9	41.1	99.7	99.3
#40	" (425um)	86.2	73.5	95.0	23.3	99.7	98.8
#60	" (250um)	80.8	61.9	39.2	10.3	99.6	98.0
#100	" (150um)	79.4	58.3	10.6	5.9	99.5	94.9
#140	" (106um)	79.1	57.3	8.0	4.7	99.3	93.7
#200	" (75um)	78.7	56.4	7.0	3.8	97.7	92.6
Clay		78.7	56.4	7.0	3.8	97.7	92.6
Silt							
Total Sand		20.1	43.6	93.0	60.3	2.3	7.1
Total Gravel		1.2	0.0	0.0	35.9	0.0	0.3
ATTERBERG LIMITS							
Liquid Limit		87	45	NP	NP	35	77
Plastic Limit		29	18	NP	NP	17	20
Plasticity Index		58	27	NP	NP	18	57
USCS		CH	CL	SP-SM	SP	CL	CH
AASHTO		A-7-6(50)	A-7-6(12)	A-3(0)	A-1-b(0)	A-6(18)	A-7-6(59)



BMT-5

Page 11

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2A	MB-2A	MB-2A	MB-2A	MB-2A	MB-2A
Station		528+88.0	528+88.0	528+88.0	528+88.0	528+88.0	528+88.0
Offset		RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9
Sample ID		T-5	SS-29	T-6	SS-30	T-8	SS-33
Depth (ft)		143.0	153.5	158.0	168.5	198.0	208.5
TOTAL PASSING (%)							
3"	SIEVE (75mm)	---	---	---	---	---	---
2 1/2"	" (63mm)	---	---	---	---	---	---
2"	" (50mm)	---	---	---	---	---	---
1 1/2"	" (37.5mm)	---	---	---	---	---	---
1"	" (25mm)	---	---	---	---	---	---
3/4"	" (19mm)	---	100.0	---	---	---	---
1/2"	" (12.5mm)	---	95.3	---	---	---	---
3/8"	" (9.5mm)	---	95.3	100.0	---	---	---
#4	" (4.75mm)	---	93.4	99.4	100.0	100.0	100.0
#10	" (2.00mm)	100.0	92.9	99.3	100.0	99.7	99.9
#20	" (0.85mm)	99.8	91.7	99.2	99.7	99.4	99.6
#40	" (425um)	99.3	89.4	98.9	99.4	98.1	99.4
#60	" (250um)	98.9	83.5	97.1	98.4	96.6	99.1
#100	" (150um)	98.5	34.4	45.8	90.0	89.9	98.3
#140	" (106um)	97.7	22.6	14.0	72.5	81.1	97.2
#200	" (75um)	95.1	16.2	7.4	55.6	74.2	94.8
Clay		95.1	16.2	7.4	55.6	74.2	94.8
Silt							
Total Sand		4.9	77.2	92.0	44.4	25.8	5.2
Total Gravel		0.0	6.6	0.6	0.0	0.0	0.0
ATTERBERG LIMITS							
Liquid Limit		51	NP	NP	33	39	33
Plastic Limit		16	NP	NP	15	14	18
Plasticity Index		35	NP	NP	18	25	15
USCS		CH	SM	SP-SM	CL	CL	CL
AASHTO		A-7-6(35)	A-2-4(0)	A-3(0)	A-6(7)	A-6(16)	A-6(14)



BMT-5

Page 12

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.			MB-2A	MB-2A	MB-2A	MB-2A	MB-2A	MB-2A
Station			528+88.0	528+88.0	528+88.0	528+88.0	528+88.0	528+88.0
Offset			RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9	RT 32.9
Sample ID			SS-34	SS-36	SS-37	SS-38	SS-39	SS-41
Depth (ft)			218.0	238.5	248.5	268.5	278.5	298.5
TOTAL PASSING (%)								
3"	SIEVE	(75mm)	---	---	---	---	---	---
2 1/2"	"	(63mm)	---	---	---	---	---	---
2"	"	(50mm)	---	---	---	---	---	---
1 1/2"	"	(37.5mm)	---	---	---	---	---	---
1"	"	(25mm)	---	---	---	---	---	---
3/4"	"	(19mm)	---	---	---	---	---	---
1/2"	"	(12.5mm)	---	---	---	---	---	---
3/8"	"	(9.5mm)	---	---	100.0	---	---	---
#4	"	(4.75mm)	100.0	100.0	99.8	100.0	100.0	100.0
#10	"	(2.00mm)	99.9	99.9	99.4	99.9	99.8	100.0
#20	"	(0.85mm)	99.9	99.9	99.2	99.8	97.2	99.9
#40	"	(425um)	99.8	99.4	98.7	99.6	76.2	99.7
#60	"	(250um)	99.5	93.6	94.6	93.8	36.9	97.9
#100	"	(150um)	98.4	77.4	86.4	20.7	18.0	91.8
#140	"	(106um)	96.4	60.6	79.1	13.1	15.0	82.9
#200	"	(75um)	89.4	41.8	69.6	9.7	13.1	63.8
Clay			89.4	41.8	69.6	9.7	13.1	63.8
Silt								
Total Sand			10.6	58.2	30.2	90.3	86.9	36.2
Total Gravel			0.0	0.0	0.2	0.0	0.0	0.0
ATTERBERG LIMITS								
Liquid Limit			39	NP	25	NP	NP	NP
Plastic Limit			18	NP	14	NP	NP	NP
Plasticity Index			21	NP	11	NP	NP	NP
USCS			CL	SM	CL	SP-SM	SM	ML
AASHTO			A-6(19)	A-4(0)	A-6(5)	A-3(0)	A-2-4(0)	A-4(0)



BMT-5

Page 13

Client: Alabama Department of Transportation
 Project: Mobile River Bridge - Main Span Unit
 ALDOT PE Project No.: DPI-0030(005)

Project No.: 17-1101-0145
 Region: Southwest Region
 Date: 9/29/2017

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COURSE ANALYSIS**

Boring No.		MB-2A	MB-2A
Station		528+88.0	528+88.0
Offset		RT 32.9	RT 32.9
Sample ID		SS-42	SS-43
Depth (ft)		308.5	318.5
TOTAL PASSING (%)			
3"	SIEVE (75mm)	---	---
2 1/2"	" (63mm)	---	---
2"	" (50mm)	---	---
1 1/2"	" (37.5mm)	---	---
1"	" (25mm)	---	---
3/4"	" (19mm)	---	---
1/2"	" (12.5mm)	---	---
3/8"	" (9.5mm)	---	---
#4	" (4.75mm)	---	100.0
#10	" (2.00mm)	100.0	100.0
#20	" (0.85mm)	99.8	99.9
#40	" (425um)	99.3	99.6
#60	" (250um)	97.4	98.8
#100	" (150um)	91.2	94.8
#140	" (106um)	81.7	87.2
#200	" (75um)	70.6	76.2
Clay		70.6	76.2
Silt			
Total Sand		29.4	23.8
Total Gravel		0.0	0.0
ATTERBERG LIMITS			
Liquid Limit		49	45
Plastic Limit		12	14
Plasticity Index		37	31
USCS		CL	CL
AASHTO		A-7-6(24)	A-7-6(22)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/15/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	TH-12	TH-12	TH-12	TH-13	TH-13	TH-13
Station	1206+11.1	1206+11.1	1206+11.1	153+01.7	153+01.7	153+01.7
Offset	LT 2.5	LT 2.5	LT 2.5	RT 78.9	RT 78.9	RT 78.9
Sample ID	SS-18	SS-20	SS-22	SS-2	SS-3	SS-5
Depth (ft)	73.5	83.5	93.5	1.5	3.0	6.0
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	97.0	99.9	100.0	98.5	99.7	100.0
#10 SIEVE (2.00mm)	82.8	99.3	100.0	95.0	98.5	98.7
#20 SIEVE (0.85mm)	68.8	96.5	98.3	91.4	94.1	93.9
#40" SIEVE (425um)	47.5	66.0	55.7	78.6	75.9	79.0
#60 SIEVE (250um)	26.9	19.6	19.2	57.2	48.1	55.5
#100 SIEVE (150um)	13.9	7.5	8.9	35.2	28.5	33.9
#140 SIEVE (106um)	10.6	5.4	6.5	28.6	23.4	27.9
#200 SIEVE (75um)	8.8	4.3	5.0	24.7	20.6	24.5

Clay

Silt

Total Sand	88.2	95.6	95.0	73.8	79.2	75.5
Total Gravel	3.0	0.1	0.0	1.5	0.3	0.0

ATTERBERG LIMITS

Liquid Limit	NP	NP	NP	NP	NP	18
Plastic Limit	NP	NP	NP	NP	NP	13
Plasticity Index	NP	NP	NP	NP	NP	5

USCS	SW-SM	SP	SP-SM	SM	SM	SC-SM
AASHTO	A-1-b(0)	A-3(0)	A-3(0)	A-2-4(0)	A-2-4(0)	A-2-4(0)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/15/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	TH-13	TH-13	TH-13	TH-13	TH-13	TH-13
Station	153+01.7	153+01.7	153+01.7	153+01.7	153+01.7	153+01.7
Offset	RT 78.9	RT 78.9	RT 78.9	RT 78.9	RT 78.9	RT 78.9
Sample ID	SS-9	T-2	SS-10	SS-13	SS-16	SS-19
Depth (ft)	25.0	28.0	33.5	48.5	63.5	78.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0	100.0	99.3
#4 SIEVE (4.75mm)	100.0	100.0	100.0	100.0	99.9	97.8
#10 SIEVE (2.00mm)	99.3	92.7	100.0	100.0	99.5	96.9
#20 SIEVE (0.85mm)	98.5	85.2	100.0	99.8	97.1	92.8
#40" SIEVE (425um)	96.5	80.8	99.8	81.7	70.6	71.7
#60 SIEVE (250um)	83.8	78.6	97.0	27.1	26.3	47.6
#100 SIEVE (150um)	43.1	77.1	68.3	11.3	11.1	20.4
#140 SIEVE (106um)	32.5	76.4	45.6	8.3	8.3	15.6
#200 SIEVE (75um)	28.2	75.9	28.9	6.6	6.8	13.5

Clay

Silt

Total Sand	71.8	24.1	71.1	93.4	93.2	84.3
------------	------	------	------	------	------	------

Total Gravel	0.0	0.0	0.0	0.0	0.1	2.2
--------------	-----	-----	-----	-----	-----	-----

ATTERBERG LIMITS

Liquid Limit	24	83	NP	NP	NP	NP
--------------	----	----	----	----	----	----

Plastic Limit	18	46	NP	NP	NP	NP
---------------	----	----	----	----	----	----

Plasticity Index	6	37	NP	NP	NP	NP
------------------	---	----	----	----	----	----

USCS	SC-SM	MH	SM	SP-SM	SP-SM	SM
------	-------	----	----	-------	-------	----

AASHTO	A-2-4(0)	A-7-5(33)	A-2-4(0)	A-3(0)	A-3(0)	A-2-4(0)
--------	----------	-----------	----------	--------	--------	----------

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/15/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	TH-13	TH-13	TH-13	TH-13	TH-13	TH-24
Station	153+01.7	153+01.7	153+01.7	153+01.7	153+01.7	9014+62.1
Offset	RT 78.9	RT 78.9	RT 78.9	RT 78.9	RT 78.9	LT 4.9
Sample ID	SS-22	T-3	T-4	SS-26	SS-30	SS-2
Depth (ft)	93.5	108.5	118.5	123.5	143.5	1.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	97.4	100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	88.2	100.0	100.0	100.0	99.3	98.2
#10 SIEVE (2.00mm)	72.2	100.0	100.0	100.0	96.9	96.4
#20 SIEVE (0.85mm)	51.7	100.0	100.0	99.8	86.5	93.5
#40" SIEVE (425um)	26.1	99.8	99.5	99.2	51.1	78.0
#60 SIEVE (250um)	14.2	99.8	98.2	96.5	21.6	51.2
#100 SIEVE (150um)	9.0	99.5	93.8	74.2	11.9	30.2
#140 SIEVE (106um)	7.1	97.1	89.9	55.8	9.3	23.7
#200 SIEVE (75um)	5.7	93.4	86.3	42.1	7.6	19.9

Clay

Silt

Total Sand	82.5	6.6	13.7	57.9	91.7	78.4
------------	------	-----	------	------	------	------

Total Gravel	11.8	0.0	0.0	0.0	0.7	1.8
--------------	------	-----	-----	-----	-----	-----

ATTERBERG LIMITS

Liquid Limit	NP	67	54	22	NP	NP
Plastic Limit	NP	22	18	13	NP	NP
Plasticity Index	NP	45	36	9	NP	NP

USCS	SW-SM	CH	CH	SC	SP-SM	SM
AASHTO	A-1-b(0)	A-7-6(47)	A-7-6(32)	A-4(1)	A-3(0)	A-2-4(0)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	WHLA-01	WHLA-01	WHLA-01	WHLA-03	WHLA-03	WHLA-03
Station	497+92.5	497+92.5	497+92.5	509+17.5	509+17.5	509+17.5
Offset	LT 26.8	LT 26.8	LT 26.8	LT 5.8	LT 5.8	LT 5.8
Sample ID	ST-7	ST-8	SS-43	SS-2	SS-4	SS-9
Depth (ft)	218.5	238.5	258.5	1.5	4.5	28.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	93.7	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	91.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	100.0	100.0	84.6	100.0	100.0
#10 SIEVE (2.00mm)	100.0	100.0	100.0	75.5	99.3	100.0
#20 SIEVE (0.85mm)	100.0	99.6	99.9	75.5	98.4	100.0
#40" SIEVE (425um)	99.9	91.2	99.2	70.7	95.8	99.2
#60 SIEVE (250um)	99.3	67.4	91.1	58.8	82.8	31.6
#100 SIEVE (150um)	95.0	40.8	70.1	32.8	30.0	5.9
#140 SIEVE (106um)	89.8	31.1	55.6	23.8	14.9	4.2
#200 SIEVE (75um)	82.9	26.0	42.2	17.8	8.3	3.4

Clay	29.2	12.6				
Silt	53.7	13.4				
Total Sand	17.1	74.0	57.8	66.8	91.7	96.6
Total Gravel	0.0	0.0	0.0	15.4	0.0	0.0

ATTERBERG LIMITS

Liquid Limit	36	NP	NP	NP	NP	NP
Plastic Limit	16	NP	NP	NP	NP	NP
Plasticity Index	20	NP	NP	NP	NP	NP

USCS	CL	SM	SM	SM	SP-SM	SP
AASHTO	A-6(15)	A-2-4(0)	A-4(0)	A-2-4(0)	A-3(0)	A-3(0)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03
Station	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5
Offset	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8
Sample ID	SS-15	SS-17	SS-21	T-2	SS-22	SS-23
Depth (ft)	58.5	68.5	88.5	93.5	103.5	113.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0		100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0		100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0		100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0		100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0		100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0		100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0		100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0		100.0
#4 SIEVE (4.75mm)	100.0	98.8	99.5	100.0		100.0
#10 SIEVE (2.00mm)	100.0	90.1	97.2	99.8		99.8
#20 SIEVE (0.85mm)	98.7	69.8	91.7	99.8		98.9
#40" SIEVE (425um)	89.9	35.9	69.6	99.6		88.6
#60 SIEVE (250um)	49.7	17.7	25.7	99.2		63.0
#100 SIEVE (150um)	18.0	12.9	11.8	98.9		35.9
#140 SIEVE (106um)	13.2	11.6	8.8	98.7		27.0
#200 SIEVE (75um)	9.9	10.9	7.1	98.5	38.6	23.1
Clay				62.5		
Silt				36.0		
Total Sand	90.1	87.9	92.4	1.5		76.9
Total Gravel	0.0	1.2	0.5	0.0		0.0
ATTERBERG LIMITS						
Liquid Limit	NP	NP	NP	81	82	NP
Plastic Limit	NP	NP	NP	25	32	NP
Plasticity Index	NP	NP	NP	56	50	NP
USCS	SP-SM	SP-SM	SP-SM	CH	SC	SM
AASHTO	A-3(0)	A-1-b(0)	A-3(0)	A-7-6(65)	A-7-5(11)	A-2-4(0)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03
Station	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5
Offset	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8
Sample ID	SS-24	SS-25	SS-28	T-6	SS-30	T-8
Depth (ft)	118.5	123.5	138.5	143.5	158.5	166.0
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	94.7	100.0	100.0	99.7	100.0
#10 SIEVE (2.00mm)	99.9	86.9	100.0	100.0	98.1	100.0
#20 SIEVE (0.85mm)	99.1	82.2	99.7	99.8	95.3	99.8
#40" SIEVE (425um)	92.9	61.6	98.3	99.2	71.2	99.6
#60 SIEVE (250um)	77.1	33.2	96.5	98.7	41.4	99.2
#100 SIEVE (150um)	34.0	15.2	94.4	95.3	27.3	97.5
#140 SIEVE (106um)	19.4	10.8	92.0	93.9	17.7	91.2
#200 SIEVE (75um)	14.4	8.9	89.0	91.5	12.4	79.5

Clay				25.4		21.4
Silt				66.1		58.1
Total Sand	85.6	85.7	11.0	8.5	87.4	20.5
Total Gravel	0.0	5.3	0.0	0.0	0.3	0.0

ATTERBERG LIMITS

Liquid Limit	NP	NP	60	32	NP	48
Plastic Limit	NP	NP	18	16	NP	16
Plasticity Index	NP	NP	42	16	NP	32

USCS	SM	SP-SM	CH	CL	SM	CL
AASHTO	A-2-4(0)	A-3(0)	A-7-6(40)	A-6(14)	A-2-4(0)	A-7-6(25)

BMT-5

Client: ALDOT
 Project: I-10 Mobile River Bridge and Bayway
 ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
 Region: Southwest Region
 Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
 SOILS AND BASE COARSE ANALYSIS**

Boring No.	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03	WHLA-03
Station	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5	509+17.5
Offset	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8	LT 5.8
Sample ID	SS-32	SS-34	SS-36	T-9	T-11	SS-38
Depth (ft)	168.0	178.5	188.5	193.0	208.5	228.5
TOTAL PASSING (%)						
3" SIEVE (75mm)	100.0	100.0	100.0	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	99.5	100.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	100.0	99.0	100.0	100.0	100.0
#10 SIEVE (2.00mm)	99.9	100.0	97.9	100.0	100.0	100.0
#20 SIEVE (0.85mm)	99.8	99.9	90.4	99.8	99.7	99.9
#40" SIEVE (425um)	99.4	98.5	65.8	98.9	99.3	99.3
#60 SIEVE (250um)	98.9	96.3	25.7	97.0	97.6	94.8
#100 SIEVE (150um)	97.3	82.5	13.7	89.3	74.7	82.5
#140 SIEVE (106um)	95.5	64.6	10.1	76.5	62.3	73.3
#200 SIEVE (75um)	92.5	47.0	8.4	63.4	54.9	60.5

Clay				17.1	27.0	
Silt				46.3	27.9	
Total Sand	7.5	53.0	90.6	36.6	45.1	39.5
Total Gravel	0.0	0.0	1.0	0.0	0.0	0.0

ATTERBERG LIMITS

Liquid Limit	45	NP	NP	28	32	NP
Plastic Limit	19	NP	NP	20	11	NP
Plasticity Index	26	NP	NP	8	21	NP

USCS	CL	SM	SP-SM	CL	CL	ML
AASHTO	A-7-6(26)	A-4(0)	A-3(0)	A-4(3)	A-6(8)	A-4(0)

BMT-5

Client: ALDOT
Project: I-10 Mobile River Bridge and Bayway
ALDOT Project No.:15-1101-0228

Project No.: 15-1101-0228
Region: Southwest Region
Date: 01/16/2018

**ALABAMA DEPARTMENT OF TRANSPORTATION
SOILS AND BASE COARSE ANALYSIS**

Boring No.	WHLA-03	WHLA-03	WHLA-03
Station	509+17.5	509+17.5	509+17.5
Offset	LT 5.8	LT 5.8	LT 5.8
Sample ID	SS-40	SS-42	SS-44
Depth (ft)	248.5	268.5	288.5
TOTAL PASSING (%)			
3" SIEVE (75mm)	100.0	100.0	100.0
2 1/2" SIEVE (63mm)	100.0	100.0	100.0
2" SIEVE (50mm)	100.0	100.0	100.0
1 1/2" SIEVE (37.5mm)	100.0	100.0	100.0
1" SIEVE (25mm)	100.0	100.0	100.0
3/4" SIEVE (19mm)	100.0	100.0	100.0
1/2" SIEVE (12.5mm)	100.0	100.0	100.0
3/8" SIEVE (9.5mm)	100.0	100.0	100.0
#4 SIEVE (4.75mm)	100.0	100.0	100.0
#10 SIEVE (2.00mm)	100.0	99.9	99.9
#20 SIEVE (0.85mm)	99.9	99.2	97.6
#40" SIEVE (425um)	99.0	94.4	81.0
#60 SIEVE (250um)	90.1	64.7	37.4
#100 SIEVE (150um)	62.6	44.3	17.3
#140 SIEVE (106um)	45.1	29.0	13.5
#200 SIEVE (75um)	29.2	17.3	11.1

Clay

Silt

Total Sand	70.8	82.7	88.9
------------	------	------	------

Total Gravel	0.0	0.0	0.0
--------------	-----	-----	-----

ATTERBERG LIMITS



Liquid Limit	NP	NP	NP
--------------	----	----	----

Plastic Limit	NP	NP	NP
---------------	----	----	----

Plasticity Index	NP	NP	NP
------------------	----	----	----

USCS	SM	SM	SP-SM
------	----	----	-------

AASHTO	A-2-4(0)	A-2-4(0)	A-2-4(0)
--------	----------	----------	----------



Specimen No. 1	
Initial	Water Content, % 20.4
	Dry Density, pcf 109.4
	Saturation, % 105.0
	Void Ratio 0.5174
	Diameter, in. 2.838
	Height, in. 5.460
At Test	Water Content, % 19.5
	Dry Density, pcf 109.4
	Saturation, % 100.0
	Void Ratio 0.5174
	Diameter, in. 2.838
	Height, in. 5.460
Strain at peak, % 8.8	
Eff. Cell Pressure, psf 13092.5	
Fail. Stress, psf 7774.5	
Excess Pore Pr., psf 9758.0	
Strain, % 8.8	
Ult. Stress, psf 7774.5	
Excess Pore Pr., psf 9758.0	
Strain, % 8.8	
$\bar{\sigma}_1$ Failure, psf 11108.9	
$\bar{\sigma}_3$ Failure, psf 3334.5	

Type of Test:

CU with Pore Pressures

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY (CL,A-6(11))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge






Source of Sample: MB-2 **Depth:** 190.0-192.00

Sample Number: T-4

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
 Thompson Engineering
 Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 190.0-192.00

Sample Number: T-4

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1	2
Initial	Water Content, %	22.9	23.5
	Dry Density, pcf	104.5	101.9
	Saturation, %	103.4	101.6
	Void Ratio	0.5897	0.6050
	Diameter, in.	2.830	2.800
	Height, in.	5.490	5.400
At Test	Water Content, %	22.2	23.1
	Dry Density, pcf	104.5	101.9
	Saturation, %	100.0	100.0
	Void Ratio	0.5897	0.6050
	Diameter, in.	2.830	2.800
	Height, in.	5.490	5.400
Strain at peak, %		12.5	6.9
Eff. Cell Pressure, psf		14665.0	7884.0
Fail. Stress, psf		14613.3	9597.3
Excess Pore Pr., psf		8083.4	3868.6
Strain, %		12.5	6.9
Ult. Stress, psf		14613.3	
Excess Pore Pr., psf		8083.4	
Strain, %		12.5	
$\bar{\sigma}_1$ Failure, psf		21194.9	13612.7
$\bar{\sigma}_3$ Failure, psf		6581.6	4015.4

Type of Test:

CU with Pore Pressures

Sample Type: 3-in. Shelby Tube

Description: SILT with SAND (ML,A-4(3))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge






Source of Sample: MB-2 **Depth:** 228.5'-230.0'

Sample Number: T-6

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 228.5'-230.0'

Sample Number: T-6

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	35.1
	Dry Density, pcf	87.6
	Saturation, %	104.2
	Void Ratio	0.8962
	Diameter, in.	2.842
	Height, in.	5.743
At Test	Water Content, %	36.3
	Dry Density, pcf	87.6
	Saturation, %	107.6
	Void Ratio	0.8962
	Diameter, in.	2.842
	Height, in.	5.743
Strain at peak, %		4.2
Back Pressure, psf		0.0
Cell Pressure, psf		5496.5
Fail. Stress, psf		3667.8
Strain, %		4.2
Ult. Stress, psf		3667.8
Strain, %		4.2
σ_1 Failure, psf		9164.3
σ_3 Failure, psf		5496.5

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY(CH A-7-6(79))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8060






Depth: 108.0'-110.0'

Sample Number: HLA-12 T-1

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8060



Depth: 108.0'-110.0'

Sample Number: HLA-12 T-1

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	18.7
	Dry Density, pcf	113.4
	Saturation, %	107.1
	Void Ratio	0.4646
	Diameter, in.	2.742
	Height, in.	5.623
At Test	Water Content, %	18.4
	Dry Density, pcf	113.4
	Saturation, %	105.5
	Void Ratio	0.4646
	Diameter, in.	2.742
	Height, in.	5.623
Strain at peak, %		11.1
Back Pressure, psf		0.0
Cell Pressure, psf		9362.9
Fail. Stress, psf		10166.8
Strain, %		11.1
Ult. Stress, psf		10166.8
Strain, %		11.1
σ_1 Failure, psf		19529.7
σ_3 Failure, psf		9362.9

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: LEAN CLAY(CL A-6(11))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8060






Depth: 185.0'-190.0'

Sample Number: HLA-12 T-2

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8060



Depth: 185.0'-190.0'

Sample Number: HLA-12 T-2

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	17.2
	Dry Density, pcf	106.8
	Saturation, %	82.6
	Void Ratio	0.5543
	Diameter, in.	2.833
At Test	Height, in.	5.363
	Water Content, %	23.0
	Dry Density, pcf	106.8
	Saturation, %	110.6
	Void Ratio	0.5543
	Diameter, in.	2.833
	Height, in.	5.363
	Strain at peak, %	9.3
	Back Pressure, psf	0.0
	Cell Pressure, psf	1405.4
	Fail. Stress, psf	5000.6
	Strain, %	9.3
	Ult. Stress, psf	5000.6
	Strain, %	9.3
σ_1 Failure, psf		6406.0
σ_3 Failure, psf		1405.4

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SILTY SAND(SM A-2-4(0))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8068






Depth: 18.0'-20.0'

Sample Number: HLA-13 T-1

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8068



Depth: 18.0'-20.0'

Sample Number: HLA-13 T-1

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	29.6
	Dry Density, pcf	89.6
	Saturation, %	96.1
	Void Ratio	0.7945
	Diameter, in.	2.860
	Height, in.	5.071
At Test	Water Content, %	37.7
	Dry Density, pcf	89.6
	Saturation, %	122.2
	Void Ratio	0.7945
	Diameter, in.	2.860
	Height, in.	5.071
Strain at peak, %		7.8
Back Pressure, psf		0.0
Cell Pressure, psf		4315.7
Fail. Stress, psf		4080.5
Strain, %		7.8
Ult. Stress, psf		4080.5
Strain, %		7.8
σ_1 Failure, psf		8396.2
σ_3 Failure, psf		4315.7

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY (CH, A-7-6(29))

Specific Gravity= 2.577

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1

Depth: 90.5'-92.5'

Sample Number: T-1






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1



Depth: 90.5'-92.5'

Sample Number: T-1

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	36.6
	Dry Density, pcf	86.5
	Saturation, %	141.2
	Void Ratio	0.5620
	Diameter, in.	2.826
	Height, in.	5.512
At Test	Water Content, %	35.4
	Dry Density, pcf	86.5
	Saturation, %	136.5
	Void Ratio	0.5620
	Diameter, in.	2.826
	Height, in.	5.512
Strain at peak, %		3.8
Back Pressure, psf		0.0
Cell Pressure, psf		4747.7
Fail. Stress, psf		4226.6
Strain, %		3.8
Ult. Stress, psf		4226.6
Strain, %		3.8
σ_1 Failure, psf		8974.3
σ_3 Failure, psf		4747.7

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY (CH, A-7-6(71))

Specific Gravity= 2.165

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1

Depth: 98.5'-100.5'

Sample Number: T-2






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1



Depth: 98.5'-100.5'

Sample Number: T-2

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	18.6
	Dry Density, pcf	114.8
	Saturation, %	111.1
	Void Ratio	0.4461
	Diameter, in.	2.848
	Height, in.	5.635
At Test	Water Content, %	18.4
	Dry Density, pcf	114.8
	Saturation, %	109.8
	Void Ratio	0.4461
	Diameter, in.	2.848
	Height, in.	5.635
Strain at peak, %		14.6
Back Pressure, psf		0.0
Cell Pressure, psf		9076.3
Fail. Stress, psf		9058.9
Strain, %		14.6
Ult. Stress, psf		9058.9
Strain, %		14.6
σ_1 Failure, psf		18135.2
σ_3 Failure, psf		9076.3

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY (CL, A-6(6))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1

Depth: 188.5'-190.5'

Sample Number: T-4






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-1



Depth: 188.5'-190.5'

Sample Number: T-4

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	21.6
	Dry Density, pcf	107.6
	Saturation, %	105.5
	Void Ratio	0.5435
	Diameter, in.	2.835
	Height, in.	5.367
At Test	Water Content, %	21.8
	Dry Density, pcf	107.6
	Saturation, %	106.8
	Void Ratio	0.5435
	Diameter, in.	2.835
	Height, in.	5.367
Strain at peak, %		14.8
Back Pressure, psf		0.0
Cell Pressure, psf		8490.2
Fail. Stress, psf		3559.7
Strain, %		14.8
Ult. Stress, psf		3559.7
Strain, %		14.8
σ_1 Failure, psf		12050.0
σ_3 Failure, psf		8490.2

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SNADY LEAN CLAY (CL,A-6(11))

Assumed Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2

Depth: 140.0-141.5'

Sample Number: T-2






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 140.0-141.5'

Sample Number: T-2

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	19.2
	Dry Density, pcf	108.5
	Saturation, %	96.3
	Void Ratio	0.5308
	Diameter, in.	2.850
	Height, in.	5.552
At Test	Water Content, %	22.2
	Dry Density, pcf	108.5
	Saturation, %	111.4
	Void Ratio	0.5308
	Diameter, in.	2.850
	Height, in.	5.552
Strain at peak, %		10.3
Back Pressure, psf		0.0
Cell Pressure, psf		8762.4
Fail. Stress, psf		5472.8
Strain, %		10.3
Ult. Stress, psf		5472.8
Strain, %		10.3
σ_1 Failure, psf		14235.2
σ_3 Failure, psf		8762.4

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SILTY CLAY, with SAND (CL-ML,A-4(2))

Assumed Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2

Depth: 145.0-147.0'

Sample Number: T-3






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 145.0-147.0'

Sample Number: T-3

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	15.2
	Dry Density, pcf	119.1
	Saturation, %	102.3
	Void Ratio	0.3944
	Diameter, in.	2.856
	Height, in.	5.532
At Test	Water Content, %	15.7
	Dry Density, pcf	119.1
	Saturation, %	105.6
	Void Ratio	0.3944
	Diameter, in.	2.856
	Height, in.	5.532
Strain at peak, %		5.8
Back Pressure, psf		0.0
Cell Pressure, psf		12260.2
Fail. Stress, psf		10354.4
Strain, %		5.8
Ult. Stress, psf		10354.4
Strain, %		5.8
σ_1 Failure, psf		22614.6
σ_3 Failure, psf		12260.2

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY (CL,A-6(11))

Assumed Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2

Depth: 210.0-212.0'

Sample Number: T-5






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 210.0-212.0'

Sample Number: T-5

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No. 1	
Initial	Water Content, % 21.3
	Dry Density, pcf 105.4
	Saturation, % 98.6
	Void Ratio 0.5750
	Diameter, in. 2.809
	Height, in. 5.171
At Test	Water Content, % 20.1
	Dry Density, pcf 105.4
	Saturation, % 93.2
	Void Ratio 0.5750
	Diameter, in. 2.809
	Height, in. 5.171
Strain at peak, % 15.0	
Back Pressure, psf 0.0	
Cell Pressure, psf 15275.5	
Fail. Stress, psf 4816.9	
Strain, % 15.0	
Ult. Stress, psf 4816.9	
Strain, % 15.0	
σ_1 Failure, psf 20092.4	
σ_3 Failure, psf 15275.5	

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SILTY SAND (SM,A-4(0))

Assumed Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2

Depth: 270.0-272.0'

Sample Number: T-7






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2



Depth: 270.0-272.0'

Sample Number: T-7

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No. 1	
Initial	Water Content, % 26.4
	Dry Density, pcf 100.2
	Saturation, % 106.7
	Void Ratio 0.6578
	Diameter, in. 2.860
	Height, in. 5.661
At Test	Water Content, % 27.5
	Dry Density, pcf 100.2
	Saturation, % 111.1
	Void Ratio 0.6578
	Diameter, in. 2.860
	Height, in. 5.661
Strain at peak, % 4.7	
Back Pressure, psf 0.0	
Cell Pressure, psf 4478.4	
Fail. Stress, psf 4972.5	
Strain, % 4.7	
Ult. Stress, psf 4972.5	
Strain, % 4.7	
σ_1 Failure, psf 9450.9	
σ_3 Failure, psf 4478.4	

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY (CL,A-7-6(12))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A

Depth: 93.5'-95.5'

Sample Number: T-2






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A



Project No.: 1511010228

Depth: 93.5'-95.5'

Sample Number: T-2

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	20.6
	Dry Density, pcf	106.7
	Saturation, %	98.4
	Void Ratio	0.5570
	Diameter, in.	2.844
	Height, in.	5.657
At Test	Water Content, %	24.3
	Dry Density, pcf	106.7
	Saturation, %	116.2
	Void Ratio	0.5570
	Diameter, in.	2.844
	Height, in.	5.657
Strain at peak, %		8.3
Back Pressure, psf		0.0
Cell Pressure, psf		5879.5
Fail. Stress, psf		4874.8
Strain, %		8.3
Ult. Stress, psf		4874.8
Strain, %		8.3
σ_1 Failure, psf		10754.3
σ_3 Failure, psf		5879.5

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: LEAN CLAY (CL,A-6(18))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A

Depth: 123'-125'

Sample Number: T-3






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A



Project No.: 1511010228

Depth: 123'-125'

Sample Number: T-3

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	12.6
	Dry Density, pcf	110.3
	Saturation, %	66.6
	Void Ratio	0.5050
	Diameter, in.	2.741
	Height, in.	5.038
At Test	Water Content, %	27.6
	Dry Density, pcf	110.3
	Saturation, %	145.2
	Void Ratio	0.5050
	Diameter, in.	2.741
	Height, in.	5.038
Strain at peak, %		10.1
Back Pressure, psf		0.0
Cell Pressure, psf		6900.5
Fail. Stress, psf		2417.0
Strain, %		10.1
Ult. Stress, psf		2417.0
Strain, %		10.1
σ_1 Failure, psf		9317.5
σ_3 Failure, psf		6900.5

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: Gray, CLAY, with sand lense

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A

Depth: 143'-145'

Sample Number: T-5






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A



Project No.: 1511010228

Depth: 143'-145'

Sample Number: T-5

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	17.7
	Dry Density, pcf	114.4
	Saturation, %	104.0
	Void Ratio	0.4522
	Diameter, in.	2.739
	Height, in.	5.506
At Test	Water Content, %	16.8
	Dry Density, pcf	114.4
	Saturation, %	98.8
	Void Ratio	0.4522
	Diameter, in.	2.739
	Height, in.	5.506
Strain at peak, %		7.8
Back Pressure, psf		0.0
Cell Pressure, psf		9493.9
Fail. Stress, psf		14075.3
Strain, %		7.8
Ult. Stress, psf		14075.3
Strain, %		7.8
σ_1 Failure, psf		23569.2
σ_3 Failure, psf		9493.9

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: LEAN CLAY with SAND (CL,A-6(16))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A

Depth: 198'-200'

Sample Number: T-8






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: MB-2A



Project No.: 1511010228

Depth: 198'-200'

Sample Number: T-8

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	45.2
	Dry Density, pcf	76.0
	Saturation, %	101.5
	Void Ratio	1.1839
	Diameter, in.	2.837
	Height, in.	5.641
At Test	Water Content, %	46.5
	Dry Density, pcf	76.0
	Saturation, %	104.5
	Void Ratio	1.1839
	Diameter, in.	2.837
	Height, in.	5.641
Strain at peak, %		3.2
Back Pressure, psf		0.0
Cell Pressure, psf		6745.0
Fail. Stress, psf		3733.4
Strain, %		3.2
Ult. Stress, psf		3733.4
Strain, %		3.2
σ_1 Failure, psf		10478.4
σ_3 Failure, psf		6745.0

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY(CH A-7-6(47))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8063






Depth: 108.5'-110.5'

Sample Number: TH-13 T-3

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8063



Depth: 108.5'-110.5'

Sample Number: TH-13 T-3

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	30.3
	Dry Density, pcf	95.1
	Saturation, %	107.9
	Void Ratio	0.7465
	Diameter, in.	2.846
	Height, in.	5.592
At Test	Water Content, %	27.9
	Dry Density, pcf	95.1
	Saturation, %	99.4
	Void Ratio	0.7465
	Diameter, in.	2.846
	Height, in.	5.592
Strain at peak, %		4.3
Back Pressure, psf		0.0
Cell Pressure, psf		7181.3
Fail. Stress, psf		3972.2
Strain, %		4.3
Ult. Stress, psf		3972.2
Strain, %		4.3
σ_1 Failure, psf		11153.5
σ_3 Failure, psf		7181.3

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY(CH A-7-6(32))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8063






Depth: 118.5'-120.5'

Sample Number: TH-13 T-4

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: Lab #8063



Depth: 118.5'-120.5'

Sample Number: TH-13 T-4

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	41.0
	Dry Density, pcf	80.4
	Saturation, %	107.2
	Void Ratio	0.9722
	Diameter, in.	2.799
	Height, in.	5.669
At Test	Water Content, %	45.3
	Dry Density, pcf	80.4
	Saturation, %	118.5
	Void Ratio	0.9722
	Diameter, in.	2.799
	Height, in.	5.669
Strain at peak, %		4.3
Back Pressure, psf		0.0
Cell Pressure, psf		4455.4
Fail. Stress, psf		3811.0
Strain, %		4.3
Ult. Stress, psf		3811.0
Strain, %		4.3
σ_1 Failure, psf		8266.3
σ_3 Failure, psf		4455.4

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: FAT CLAY(CH A-7-6(65))

Specific Gravity= 2.54

Remarks: Compression Failure Mode: Internal
Conical

Figure _____

Client: ALDOT

Project: Mobile River Bridge






Source of Sample: WHLA **Depth:** 43.5'-45.5'

Sample Number: WHLA-3 T-2

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA



Depth: 43.5'-45.5'

Sample Number: WHLA-3 T-2

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	33.5
	Dry Density, pcf	92.6
	Saturation, %	113.1
	Void Ratio	0.7859
	Diameter, in.	2.855
At Test	Height, in.	5.498
	Water Content, %	28.4
	Dry Density, pcf	92.6
	Saturation, %	95.6
	Void Ratio	0.7859
	Diameter, in.	2.855
	Height, in.	5.498
	Strain at peak, %	11.3
	Back Pressure, psf	0.0
	Cell Pressure, psf	6884.6
	Fail. Stress, psf	6157.3
	Strain, %	11.3
	Ult. Stress, psf	6157.3
	Strain, %	11.3
σ_1 Failure, psf		13042.0
σ_3 Failure, psf		6884.6

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: LEAN CLAY(CL A-6(14))

Specific Gravity= 2.65

Remarks: Compression Failure Mode: Asymmetrical
Shear Plane

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA **Depth:** 143.5'-145.5'






Sample Number: WHLA-3 T-6

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama

Figure _____



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA



Depth: 143.5'-145.5'

Sample Number: WHLA-3 T-6

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No. 1	
Initial	Water Content, % 30.3
	Dry Density, pcf 94.2
	Saturation, % 104.4
	Void Ratio 0.7770
	Diameter, in. 2.853
	Height, in. 5.384
At Test	Water Content, % 27.8
	Dry Density, pcf 94.2
	Saturation, % 95.7
	Void Ratio 0.7770
	Diameter, in. 2.853
	Height, in. 5.384
Strain at peak, % 15.0	
Back Pressure, psf 0.0	
Cell Pressure, psf 7914.2	
Fail. Stress, psf 7151.9	
Strain, % 15.0	
Ult. Stress, psf 7151.9	
Strain, % 15.0	
σ_1 Failure, psf 15066.1	
σ_3 Failure, psf 7914.2	

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: LEAN CLAY with SAND(CL A-7-6(25))

Specific Gravity= 2.68

Remarks: Compression Failure Mode: Asymmetrical Shear Plane

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA **Depth:** 166.0'-168.0'






Sample Number: WHLA-3 T-8

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama

Figure _____



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA



Depth: 166.0'-168.0'

Sample Number: WHLA-3 T-8

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No.		1
Initial	Water Content, %	19.2
	Dry Density, pcf	112.2
	Saturation, %	107.3
	Void Ratio	0.4742
	Diameter, in.	2.798
	Height, in.	5.585
At Test	Water Content, %	19.6
	Dry Density, pcf	112.2
	Saturation, %	109.4
	Void Ratio	0.4742
	Diameter, in.	2.798
	Height, in.	5.585
Strain at peak, %		13.6
Back Pressure, psf		0.0
Cell Pressure, psf		9230.4
Fail. Stress, psf		10056.6
Strain, %		13.6
Ult. Stress, psf		10056.6
Strain, %		13.6
σ_1 Failure, psf		19287.0
σ_3 Failure, psf		9230.4

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY(CL A-4(3))

Specific Gravity= 2.65

Remarks: Compression Failure Mode: Symmetrical Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge






Source of Sample: WHLA **Depth:** 193.0'-195.0'

Sample Number: WHLA-3 T-9

Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT
Thompson Engineering
Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA



Depth: 193.0'-195.0'

Sample Number: WHLA-3 T-9

Project No.: 1511010228

Figure _____

Thompson Engineering



Specimen No. 1	
Initial	Water Content, %
	14.8
	Dry Density, pcf
	121.2
	Saturation, %
	106.5
At Test	Void Ratio
	0.3697
	Diameter, in.
	2.812
	Height, in.
	5.076
Strain at peak, %	
14.8	
Back Pressure, psf	
0.0	
Cell Pressure, psf	
9930.2	
Fail. Stress, psf	
6392.9	
Strain, %	
14.8	
Ult. Stress, psf	
6392.9	
Strain, %	
14.8	
σ_1 Failure, psf	
16323.1	
σ_3 Failure, psf	
9930.2	

Type of Test:

Unconsolidated Undrained

Sample Type: 3-in. Shelby Tube

Description: SANDY LEAN CLAY(CL A-6(8))

Specific Gravity= 2.66

Remarks: Compression Failure Mode: Symmetrical
Bulge

Figure _____

Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA

Depth: 208.5'-210.5'

Sample Number: WHLA-3 T-11






Proj. No.: 1511010228

Date Sampled:

TRIAXIAL SHEAR TEST REPORT

Thompson Engineering

Mobile, Alabama



Client: ALDOT

Project: Mobile River Bridge

Source of Sample: WHLA

Project No.: 1511010228

Depth: 208.5'-210.5'

Sample Number: WHLA-3 T-11



Figure _____

Thompson Engineering


Thompson Engineering

Direct Shear Test (ASTM D3080)

Peak: $\Phi = 30.7$ $C = 16.9$



Initial	Specimen			
	A	B	C	D
Moisture (%)	25.75	27.09	27.09	
Density (pcf)	94.08	94.76	95.09	
Void Ratio	0.725	0.713	0.707	
Saturation (%)	92.32	98.80	99.63	
Diameter (in)	2.500	2.500	2.500	
Height (in)	1.000	1.000	1.000	



Final	A	B	C	D
Moisture (%)	31.09	30.53	29.72	
Density (pcf)	94.59	96.41	97.51	
Void Ratio	0.716	0.684	0.664	
Saturation (%)	100.00	100.00	100.00	
Diameter (in)	2.500	2.500	2.500	
Height (in)	0.965	0.954	0.947	
Normal Stress (psi)	52.8	105.6	208.3	
Peak Stress (psi)	53.5	77.7	143.2	
Residual Stress (psi)				
Strain (%)	15.029	15.006	15.006	
Rate (in/min)	0.00857	0.00848	0.00716	

Project Date	
Date	8/24/17

Project:	Mobile River Bridge	 Failure Photographs
Location:	Soils Lab	
Project Number:	8013	
Boring Number:	MB-02A	
Sample Number:	T-6	
Depth:	158.0-160.0 ft.	
Sample Type:	Undisturbed	
Description:	POORLY GRADED SAND with SILT (SP-SM A-3(0))	
Test Type:	Direct Shear	
Remarks:		

Thompson Engineering
Direct Shear Test (ASTM D3080)

Date


Checked By

Date


Date

Tested
By

Delta h




Stress-Deformation



Thompson Engineering

Direct Shear Test


Specimen A Stress-Deformation



Thompson Engineering


Direct Shear Test

Specimen B Stress-Deformation




Thompson Engineering
Direct Shear Test

Specimen C Stress-Deformation




Consolidation Test Test Results




	Before	After	Liquid Limits:	0	Test Date:	11/1/17
Moisture (%):	25.69	25.99	Plastic Limits:	0		
Dry Density (pcf):	95.30	97.05	Plasticity Index (%):	0		
Saturation (%):	100.54	106.63				
Void Ratio:	0.6352	0.5911	Specific Gravity:	2.503	Measured	
Sample Description:	SILTY SAND(SM A-2-4(0))					
Project Number:	8068		Depth:	18.0-20.0 ft.		Remarks:
Sample Number:	T-1		Boring Number:	HLA-13		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	11/1/17
Moisture (%):	25.69	25.99	Plastic Limits:	0		
Dry Density (pcf):	95.30	97.05	Plasticity Index (%):	0		
Saturation (%):	100.54	106.63				
Void Ratio:	0.6352	0.5911	Specific Gravity:	2.503	Measured	
Soil Description:	SILTY SAND(SM A-2-4(0))					
Project Number:	8068	Depth:	18.0-20.0 ft.	Remarks:		
Sample Number:	T-1	Boring Number:	HLA-13			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	0	Test Date:	11/1/17
Moisture (%):	25.69	25.99	Plastic Limits:	0		
Dry Density (pcf):	95.30	97.05	Plasticity Index (%):	0		
Saturation (%):	100.54	106.63				
Void Ratio:	0.6352	0.5911	Specific Gravity:	2.503	Measured	
Soil Description:	SILTY SAND(SM A-2-4(0))					
Project Number:	8068		Depth:	18.0-20.0 ft.		Remarks:
Sample Number:	T-1		Boring Number:	HLA-13		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	11/1/17
Moisture (%):	25.69	25.99	Plastic Limits:	0		
Dry Density (pcf):	95.30	97.05	Plasticity Index (%):	0		
Saturation (%):	100.54	106.63				
Void Ratio:	0.6352	0.5911	Specific Gravity:	2.503	Measured	
Soil Description:	SILTY SAND(SM A-2-4(0))					
Project Number:	8068		Depth: 18.0-20.0 ft.		Remarks:	
Sample Number:	T-1		Boring Number: HLA-13			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	11/1/17
Moisture (%):	25.69	25.99	Plastic Limits:	0		
Dry Density (pcf):	95.30	97.05	Plasticity Index (%):	0		
Saturation (%):	100.54	106.63				
Void Ratio:	0.6352	0.5911	Specific Gravity:	2.503	Measured	
Soil Description:	SILTY SAND(SM A-2-4(0))					
Project Number:	8068		Depth: 18.0-20.0 ft.		Remarks:	
Sample Number:	T-1		Boring Number: HLA-13			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0145

Project Number: 8068

Sample Number: T-1
Boring Number: HLA-13
Depth: 18.0-20.0 ft.
Sample Type: Undisturbed

Sample Description: SILTY SAND(SM A-2-4(0))
Remarks:

Test Number:
Test Date: 11/1/17

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	1.0020	0.3898	0.00	0.6366	0.000	0.000	0.000	0.000
1	0.125	0.0031	0.9989	0.3866	0.31	0.6315	0.000	0.000	0.000	0.000
2	0.250	0.0068	0.9952	0.3829	0.68	0.6254	30.656	* 17.0312	24.997	10.453
3	0.500	0.0106	0.9914	0.3792	1.05	0.6194	0.622	* 0.3453	1223.750	511.733
4	1.000	0.0157	0.9863	0.3741	1.57	0.6110	0.622	* 0.3453	1211.113	506.449
5	2.000	0.0217	0.9803	0.3681	2.16	0.6012	34.273	* 19.0405	21.698	9.073
6	0.500	0.0188	0.9832	0.3709	1.88	0.6059	0.000	0.000	0.000	0.000
7	1.000	0.0200	0.9820	0.3698	1.99	0.6040	0.000	0.000	0.000	0.000
8	2.000	0.0231	0.9789	0.3667	2.31	0.5989	0.000	0.000	0.000	0.000
9	4.000	0.0299	0.9721	0.3598	2.99	0.5877	0.622	0.292	1176.351	582.508
10	8.000	0.0402	0.9618	0.3496	4.01	0.5709	0.622	0.234	1151.634	710.927
11	16.000	0.0553	0.9467	0.3344	5.52	0.5463	1.433	0.590	483.990	273.161
12	4.000	0.0468	0.9552	0.3430	4.67	0.5602	0.000	0.000	0.000	0.000
13	1.000	0.0411	0.9609	0.3487	4.10	0.5695	0.000	0.000	0.000	0.000
14	0.250	0.0270	0.9750	0.3628	2.69	0.5925	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0145

Project Number: 8068
Test Date: 11/1/17

Sample Number: T-1
Boring Number: HLA-13
Depth: 18.0-20.0 ft.
Sample Type: Undisturbed

Sample Description:
 SILTY SAND(SM A-2-4(0))
Remarks:


Test Number:
Liquid Limit: 0.0000 **Initial Void Ratio:** 0.6352 **Initial Height (in):** 1.0020
Plastic Limit: 0.0000 **Plasticity Index (%):** 0.0000 **Initial Diameter (in):** 2.5030
Specific Gravity: 2.5030 **Weight of Ring (g):** 111.0700
 Measured

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	123.25	282.54
Dry Soil + Container (g)	103.25	251.00
Weight of Container (g)	25.40	129.63
Moisture Content (%)	25.69	25.99
Void Ratio	0.6352	0.5911
Saturation (%)	100.54	106.63
Dry Density (pcf)	95.30	97.05

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	52	Test Date:	5/14/16
Moisture (%):	34.65	33.88	Plastic Limits:	22		
Dry Density (pcf):	83.97	88.16	Plasticity Index (%):	30		
Saturation (%):	97.50	105.85				
Void Ratio:	0.9166	0.7707	Specific Gravity:	2.577	Measured	
Sample Description: FAT CLAY with SAND (CH A-7-6(23))						
Project Number:	7716		Depth:	90.5-92.5 ft.	Remarks:	
Sample Number:	T-1		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	52	Test Date:	5/14/16
Moisture (%):	34.65	33.88	Plastic Limits:	22		
Dry Density (pcf):	83.97	88.16	Plasticity Index (%):	30		
Saturation (%):	97.50	105.85				
Void Ratio:	0.9166	0.7707	Specific Gravity:	2.577	Measured	
Soil Description:	FAT CLAY with SAND (CH A-7-6(23))					
Project Number:	7716	Depth:		90.5-92.5 ft. <th colspan="2" rowspan="5">Remarks:</th>	Remarks:	
Sample Number:	T-1	Boring Number:		MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	52	Test Date:	5/14/16
Moisture (%):	34.65	33.88	Plastic Limits:	22		
Dry Density (pcf):	83.97	88.16	Plasticity Index (%):	30		
Saturation (%):	97.50	105.85				
Void Ratio:	0.9166	0.7707	Specific Gravity:	2.577	Measured	
Soil Description:	FAT CLAY with SAND (CH A-7-6(23))					
Project Number:	7716	Depth:		90.5-92.5 ft. <th colspan="2" rowspan="5">Remarks:</th>	Remarks:	
Sample Number:	T-1	Boring Number:		MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	52	Test Date:	5/14/16
Moisture (%):	34.65	33.88	Plastic Limits:	22		
Dry Density (pcf):	83.97	88.16	Plasticity Index (%):	30		
Saturation (%):	97.50	105.85				
Void Ratio:	0.9166	0.7707	Specific Gravity:	2.577	Measured	
Soil Description:	FAT CLAY with SAND (CH A-7-6(23))					
Project Number:	7716		Depth:	90.5-92.5 ft.	Remarks:	
Sample Number:	T-1		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	52	Test Date:	5/14/16
Moisture (%):	34.65	33.88	Plastic Limits:	22		
Dry Density (pcf):	83.97	88.16	Plasticity Index (%):	30		
Saturation (%):	97.50	105.85				
Void Ratio:	0.9166	0.7707	Specific Gravity:	2.577	Measured	
Soil Description:	FAT CLAY with SAND (CH A-7-6(23))					
Project Number:	7716	Depth:		90.5-92.5 ft. <th rowspan="5">Remarks:</th> <td></td>	Remarks:	
Sample Number:	T-1	Boring Number:		MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 16-1101-0110

Project Number: 7716

Sample Number: T-1
Boring Number: MB-1
Depth: 90.5-92.5 ft.
Sample Type: Undisturbed

Sample Description: FAT CLAY with SAND (CH A-7-6(23))
Remarks:

Test Number:
Test Date: 5/14/16

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9980	0.4762	0.00	0.9124	0.000	0.000	0.000	0.000
1	0.125	0.0020	0.9960	0.4742	0.20	0.9086	0.000	0.000	0.000	0.000
2	0.250	0.0062	0.9918	0.4700	0.62	0.9006	21.386	2.900	35.594	60.981
3	0.500	0.0114	0.9866	0.4648	1.14	0.8906	0.764	6.987	986.125	25.043
4	1.000	0.0214	0.9766	0.4548	2.14	0.8715	53.823	3.941	13.713	43.512
5	2.000	0.0362	0.9618	0.4400	3.63	0.8431	1.433	4.350	499.639	38.231
6	4.000	0.0513	0.9467	0.4249	5.14	0.8142	5.006	2.117	138.564	76.127
7	8.000	0.0956	0.9024	0.3806	9.58	0.7293	40.610	17.356	15.517	8.435
8	16.000	0.1685	0.8295	0.3076	16.89	0.5895	100.033	16.990	5.322	7.280
9	4.000	0.1414	0.8566	0.3348	14.16	0.6416	0.000	0.000	0.000	0.000
10	1.000	0.1223	0.8757	0.3538	12.26	0.6781	0.000	0.000	0.000	0.000
11	0.250	0.0760	0.9220	0.4002	7.62	0.7668	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge **Project Number:** 7716
Location: Soils Lab
Job Number: 16-1101-0110 **Test Date:** 5/14/16

Sample Number: T-1 **Sample Description:**
Boring Number: MB-1 FAT CLAY with SAND (CH A-7-6(23))
Depth: 90.5-92.5 ft. **Remarks:**
Sample Type: Undisturbed


Test Number:
Liquid Limit: 52.0000 **Initial Void Ratio:** 0.9166 **Initial Height (in):** 0.9980
Plastic Limit: 22.0000 **Plasticity Index (%):** 30.0000 **Initial Diameter (in):** 2.4970
Specific Gravity: 2.5770 **Weight of Ring (g):** 110.7800
Measured

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	87.11	264.62
Dry Soil + Container (g)	72.82	229.35
Weight of Container (g)	31.58	125.26
Moisture Content (%)	34.65	33.88
Void Ratio	0.9166	0.7707
Saturation (%)	97.50	105.85
Dry Density (pcf)	83.97	88.16

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	89	Test Date:	5/18/16
Moisture (%):	41.43	40.62	Plastic Limits:	28		
Dry Density (pcf):	79.98	80.91	Plasticity Index (%):	61		
Saturation (%):	130.00	131.18				
Void Ratio:	0.6918	0.6697	Specific Gravity:	2.165	Measured	
Sample Description: FAT CLAY (CH A-7-6(71))						
Project Number:	7716		Depth:	98.5-100.5 ft.	Remarks:	
Sample Number:	T-2		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	89	Test Date:	5/18/16
Moisture (%):	41.43	40.62	Plastic Limits:	28		
Dry Density (pcf):	79.98	80.91	Plasticity Index (%):	61		
Saturation (%):	130.00	131.18				
Void Ratio:	0.6918	0.6697	Specific Gravity:	2.165	Measured	
Soil Description:	FAT CLAY (CH A-7-6(71))					
Project Number:	7716		Depth: 98.5-100.5 ft.	Remarks:		
Sample Number:	T-2		Boring Number: MB-1			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	89	Test Date:	5/18/16
Moisture (%):	41.43	40.62	Plastic Limits:	28		
Dry Density (pcf):	79.98	80.91	Plasticity Index (%):	61		
Saturation (%):	130.00	131.18				
Void Ratio:	0.6918	0.6697	Specific Gravity:	2.165	Measured	
Soil Description:	FAT CLAY (CH A-7-6(71))					
Project Number:	7716		Depth: 98.5-100.5 ft	Remarks:		
Sample Number:	T-2		Boring Number: MB-1			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	89	Test Date:	5/18/16
Moisture (%):	41.43	40.62	Plastic Limits:	28		
Dry Density (pcf):	79.98	80.91	Plasticity Index (%):	61		
Saturation (%):	130.00	131.18				
Void Ratio:	0.6918	0.6697	Specific Gravity:	2.165	Measured	
Soil Description:	FAT CLAY (CH A-7-6(71))					
Project Number:	7716		Depth:	98.5-100.5 ft	Remarks:	
Sample Number:	T-2		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	89	Test Date:	5/18/16
Moisture (%):	41.43	40.62	Plastic Limits:	28		
Dry Density (pcf):	79.98	80.91	Plasticity Index (%):	61		
Saturation (%):	130.00	131.18				
Void Ratio:	0.6918	0.6697	Specific Gravity:	2.165	Measured	
Soil Description:	FAT CLAY (CH A-7-6(71))					
Project Number:	7716		Depth: 98.5-100.5 ft	Remarks:		
Sample Number:	T-2		Boring Number: MB-1			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 16-1101-0110

Project Number: 7716

Sample Number: T-2
Boring Number: MB-1
Depth: 98.5-100.5 ft.
Sample Type: Undisturbed

Sample Description: FAT CLAY (CH A-7-6(71))
Remarks:

Test Number:
Test Date: 5/18/16

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9960	0.4056	0.00	0.6870	0.000	0.000	0.000	0.000
1	0.125	0.0020	0.9940	0.4036	0.20	0.6836	0.000	0.000	0.000	0.000
2	0.250	0.0002	0.9958	0.4054	0.02	0.6866	0.000	0.000	0.000	0.000
3	0.500	0.0011	0.9949	0.4045	0.11	0.6851	0.000	0.000	0.000	0.000
4	1.000	0.0017	0.9943	0.4039	0.17	0.6841	0.000	0.000	0.000	0.000
5	2.000	0.0111	0.9849	0.3945	1.12	0.6681	0.622	5.244	1207.744	33.250
6	4.000	0.0236	0.9724	0.3820	2.37	0.6470	2.419	17.128	302.463	9.924
7	8.000	0.0614	0.9346	0.3442	6.16	0.5830	4.202	28.962	160.856	5.422
8	16.000	0.1605	0.8355	0.2450	16.12	0.4150	303.739	40.325	1.778	3.112
9	4.000	0.1151	0.8809	0.2905	11.56	0.4920	0.000	0.000	0.000	0.000
10	1.000	0.0690	0.9270	0.3366	6.93	0.5701	0.000	0.000	0.000	0.000
11	0.250	0.0130	0.9830	0.3926	1.31	0.6649	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 16-1101-0110

Project Number: 7716
Test Date: 5/18/16

Sample Number: T-2
Boring Number: MB-1
Depth: 98.5-100.5 ft.
Sample Type: Undisturbed

Sample Description:
 FAT CLAY (CH A-7-6(71))
Remarks:


Test Number:			
Liquid Limit:	89.0000	Initial Void Ratio:	0.6918
Plastic Limit:	28.0000	Plasticity Index (%):	61.0000
Specific Gravity:	2.1650	Weight of Ring (g):	110.8000
	Measured		
		Initial Height (in):	0.9960
		Initial Diameter (in):	2.4950

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	101.13	268.27
Dry Soil + Container (g)	80.66	227.00
Weight of Container (g)	31.25	125.39
Moisture Content (%)	41.43	40.62
Void Ratio	0.6918	0.6697
Saturation (%)	130.00	131.18
Dry Density (pcf)	79.98	80.91

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	28	Test Date:	5/21/16
Moisture (%):	18.28	18.14	Plastic Limits:	14		
Dry Density (pcf):	110.49	114.19	Plasticity Index (%):	14		
Saturation (%):	96.46	105.97				
Void Ratio:	0.5019	0.4494	Specific Gravity:	2.663	Measured	
Sample Description: SANDY LEAN CLAY (CL A-6(6))						
Project Number:	7716		Depth:	188.5-190.5 ft	Remarks:	
Sample Number:	T-4		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	28	Test Date:	5/21/16
Moisture (%):	18.28	18.14	Plastic Limits:	14		
Dry Density (pcf):	110.49	114.19	Plasticity Index (%):	14		
Saturation (%):	96.46	105.97				
Void Ratio:	0.5019	0.4494	Specific Gravity:	2.663	Measured	
Soil Description:	SANDY LEAN CLAY (CL A-6(6))					
Project Number:	7716		Depth:	188.5-190.5 ft	Remarks:	
Sample Number:	T-4		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv

	Before	After	Liquid Limits:	28	Test Date:	5/21/16
Moisture (%):	18.28	18.14	Plastic Limits:	14		
Dry Density (pcf):	110.49	114.19	Plasticity Index (%):	14		
Saturation (%):	96.46	105.97				
Void Ratio:	0.5019	0.4494	Specific Gravity:	2.663	Measured	
Soil Description:	SANDY LEAN CLAY (CL A-6(6))					
Project Number:	7716		Depth:	188.5-190.5 ft	Remarks:	
Sample Number:	T-4		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—◆— t50 Cv

	Before	After	Liquid Limits:	28	Test Date:	5/21/16
Moisture (%):	18.28	18.14	Plastic Limits:	14		
Dry Density (pcf):	110.49	114.19	Plasticity Index (%):	14		
Saturation (%):	96.46	105.97				
Void Ratio:	0.5019	0.4494	Specific Gravity:	2.663	Measured	
Soil Description:	SANDY LEAN CLAY (CL A-6(6))					
Project Number:	7716		Depth:	188.5-190.5 ft		Remarks:
Sample Number:	T-4		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	28	Test Date:	5/21/16
Moisture (%):	18.28	18.14	Plastic Limits:	14		
Dry Density (pcf):	110.49	114.19	Plasticity Index (%):	14		
Saturation (%):	96.46	105.97				
Void Ratio:	0.5019	0.4494	Specific Gravity:	2.663	Measured	
Soil Description:	SANDY LEAN CLAY (CL A-6(6))					
Project Number:	7716		Depth:	188.5-190.5 ft		Remarks:
Sample Number:	T-4		Boring Number:	MB-1		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 16-1101-0110

Project Number: 7716

Sample Number: T-4
Boring Number: MB-1
Depth: 188.5-190.5 ft.
Sample Type: Undisturbed

Sample Description:
 SANDY LEAN CLAY (CL A-6(6))

Remarks:

Test Number:
Test Date: 5/21/16

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft ² /year)	t50 Cv (ft ² /year)
0	0.000	0.0000	1.0000	0.3342	0.00	0.5020	0.000	0.000	0.000	0.000
1	0.125	0.0041	0.9959	0.3301	0.41	0.4958	0.000	0.000	0.000	0.000
2	0.250	0.0088	0.9912	0.3254	0.88	0.4887	1.064	1.019	714.820	173.308
3	0.500	0.0146	0.9854	0.3196	1.46	0.4801	0.821	0.802	915.264	217.601
4	1.000	0.0222	0.9778	0.3120	2.22	0.4686	0.900	0.396	822.402	433.509
5	2.000	0.0308	0.9692	0.3034	3.08	0.4556	0.780	0.721	931.487	234.107
6	4.000	0.0394	0.9606	0.2948	3.94	0.4428	0.775	0.347	921.449	478.457
7	8.000	0.0539	0.9461	0.2803	5.39	0.4210	0.805	0.571	860.124	281.914
8	16.000	0.0730	0.9270	0.2612	7.30	0.3923	0.758	0.589	877.717	262.212
9	4.000	0.0654	0.9346	0.2688	6.54	0.4037	0.000	0.000	0.000	0.000
10	1.000	0.0588	0.9412	0.2754	5.88	0.4136	0.000	0.000	0.000	0.000
11	0.250	0.0350	0.9650	0.2992	3.50	0.4494	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge **Project Number:** 7716
Location: Soils Lab
Job Number: 16-1101-0110 **Test Date:** 5/21/16

Sample Number: T-4 **Sample Description:**
Boring Number: MB-1 SANDY LEAN CLAY (CL A-6(6))
Depth: 188.5-190.5 ft. **Remarks:**
Sample Type: Undisturbed


Test Number:
Liquid Limit: 28.0000 **Initial Void Ratio:** 0.5019 **Initial Height (in):** 1.0000
Plastic Limit: 14.0000 **Plasticity Index (%):** 14.0000 **Initial Diameter (in):** 2.5020
Specific Gravity: 2.6630 **Weight of Ring (g):** 98.6700
Measured

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	128.40	297.32
Dry Soil + Container (g)	113.55	271.53
Weight of Container (g)	32.33	129.33
Moisture Content (%)	18.28	18.14
Void Ratio	0.5019	0.4494
Saturation (%)	96.46	105.97
Dry Density (pcf)	110.49	114.19

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	21.17	21.68	Plastic Limits:	0		
Dry Density (pcf):	104.00	105.16	Plasticity Index (%):	0		
Saturation (%):	98.16	103.72	Specific Gravity:	2.600	Assumed	
Void Ratio:	0.5597	0.5379				
Sample Description: SILTY CLAY with SAND (CL-ML A-4(2))						
Project Number:		7559	Depth: 145.0 - 147.0		Remarks:	
Sample Number:		T-3	Boring Number: MB-2			
Project: Mobile River Bridge						
Client: ALDOT						
Location: Soils Lab						

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	21.17	21.68	Plastic Limits:	0		
Dry Density (pcf):	104.00	105.16	Plasticity Index (%):	0		
Saturation (%):	98.16	103.72				
Void Ratio:	0.5597	0.5379	Specific Gravity:	2.600	Assumed	
Soil Description:	SILTY CLAY with SAND (CL-ML A-4(2))					
Project Number:	7559	Depth:	145.0 - 147.0	Remarks:		
Sample Number:	T-3	Boring Number:	MB-2			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	21.17	21.68	Plastic Limits:	0		
Dry Density (pcf):	104.00	105.16	Plasticity Index (%):	0		
Saturation (%):	98.16	103.72				
Void Ratio:	0.5597	0.5379	Specific Gravity:	2.600	Assumed	
Soil Description:	SILTY CLAY with SAND (CL-ML A-4(2))					
Project Number:	7559		Depth:	145.0 - 147.0	Remarks:	
Sample Number:	T-3		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	21.17	21.68	Plastic Limits:	0		
Dry Density (pcf):	104.00	105.16	Plasticity Index (%):	0		
Saturation (%):	98.16	103.72				
Void Ratio:	0.5597	0.5379	Specific Gravity:	2.600	Assumed	
Soil Description:	SILTY CLAY with SAND (CL-ML A-4(2))					
Project Number:	7559		Depth:	145.0 - 147.0	Remarks:	
Sample Number:	T-3		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	21.17	21.68	Plastic Limits:	0		
Dry Density (pcf):	104.00	105.16	Plasticity Index (%):	0		
Saturation (%):	98.16	103.72				
Void Ratio:	0.5597	0.5379				
Soil Description:	SILTY CLAY with SAND (CL-ML A-4(2))					
Project Number:	7559	Depth: 145.0 - 147.0		Remarks:		
Sample Number:	T-3	Boring Number: MB-2				
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 15-1101-0228

Project Number: 7559

Sample Number: T-3
Boring Number: MB-2
Depth: 145.0 - 147.0 ft.
Sample Type: Undisturbed

Sample Description: SILTY CLAY with SAND (CL-ML A-4(2))
Remarks:

Test Number:
Test Date: 9/29/15

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	1.0040	0.3596	0.00	0.5580	0.000	0.000	0.000	0.000
1	0.125	0.0003	1.0037	0.3593	0.03	0.5575	0.000	0.000	0.000	0.000
2	0.250	0.0028	1.0012	0.3568	0.27	0.5537	0.599	0.195	1295.381	922.560
3	0.500	0.0068	0.9972	0.3528	0.68	0.5474	1.372	0.982	560.685	182.015
4	1.000	0.0145	0.9895	0.3450	1.45	0.5354	0.937	1.856	808.716	94.854
5	2.000	0.0245	0.9795	0.3351	2.44	0.5199	0.764	1.133	971.913	152.185
6	4.000	0.0359	0.9681	0.3237	3.57	0.5023	2.123	0.734	341.569	229.584
7	8.000	0.0531	0.9509	0.3065	5.29	0.4756	2.262	1.613	309.308	100.774
8	2.000	0.0439	0.9601	0.3157	4.37	0.4898	0.000	0.000	0.000	0.000
9	0.500	0.0330	0.9710	0.3265	3.29	0.5067	0.000	0.000	0.000	0.000
10	0.125	0.0140	0.9900	0.3456	1.39	0.5362	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By:

Checked By:

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge **Project Number:** 7559
Location: Soils Lab
Job Number: 15-1101-0228 **Test Date:** 9/29/15

Sample Number: T-3 **Sample Description:**
Boring Number: MB-2 SILTY CLAY with SAND (CL-ML A-4(2))
Depth: 145.0 - 147.0 ft. **Remarks:**
Sample Type: Undisturbed


Test Number:
Liquid Limit: 0.0000 **Initial Void Ratio:** 0.5597 **Initial Height (in):** 1.0040
Plastic Limit: 0.0000 **Plasticity Index (%):** 0.0000 **Initial Diameter (in):** 2.5020
Specific Gravity: 2.6000 **Weight of Ring (g):** 110.8400
Assumed

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	140.49	291.58
Dry Soil + Container (g)	121.61	262.52
Weight of Container (g)	32.42	128.49
Moisture Content (%)	21.17	21.68
Void Ratio	0.5597	0.5379
Saturation (%)	98.16	103.72
Dry Density (pcf)	104.00	105.16

Tested By:


Checked By:

Consolidation Test Test Results




	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	23.86	21.04	Plastic Limits:	0		
Dry Density (pcf):	100.11	109.07	Plasticity Index (%):	0		
Saturation (%):	99.83	112.05				
Void Ratio:	0.6175	0.4730	Specific Gravity:	2.600	Assumed	
Sample Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559	Depth:	190.0-190.33	Remarks:		
Sample Number:	T-4	Boring Number:	MB-2			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	23.86	21.04	Plastic Limits:	0		
Dry Density (pcf):	100.11	109.07	Plasticity Index (%):	0		
Saturation (%):	99.83	112.05	Specific Gravity:	2.600	Assumed	
Void Ratio:	0.6175	0.4730				
Soil Description: SANDY LEAN CLAY (CL A-6(11))						
Project Number:		7559	Depth: 190.0-190.33		Remarks:	
Sample Number:		T-4	Boring Number: MB-2			
Project:		Mobile River Bridge				
Client:		ALDOT				
Location:		Soils Lab				


Consolidation Test Test Results



—■— $t_{90} C_v$


	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	23.86	21.04	Plastic Limits:	0		
Dry Density (pcf):	100.11	109.07	Plasticity Index (%):	0		
Saturation (%):	99.83	112.05				
Void Ratio:	0.6175	0.4730	Specific Gravity:	2.600	Assumed	
Soil Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559		Depth:	190.0-190.33	Remarks:	
Sample Number:	T-4		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	23.86	21.04	Plastic Limits:	0		
Dry Density (pcf):	100.11	109.07	Plasticity Index (%):	0		
Saturation (%):	99.83	112.05	Specific Gravity:	2.600	Assumed	
Void Ratio:	0.6175	0.4730				
Soil Description: SANDY LEAN CLAY (CL A-6(11))						
Project Number:	7559		Depth:	190.0-190.33	Remarks:	
Sample Number:	T-4		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/29/15
Moisture (%):	23.86	21.04	Plastic Limits:	0		
Dry Density (pcf):	100.11	109.07	Plasticity Index (%):	0		
Saturation (%):	99.83	112.05	Specific Gravity:	2.600	Assumed	
Void Ratio:	0.6175	0.4730				
Soil Description: SANDY LEAN CLAY (CL A-6(11))						
Project Number:		7559	Depth: 190.0-190.33		Remarks:	
Sample Number:		T-4	Boring Number: MB-2			
Project:		Mobile River Bridge				
Client:		ALDOT				
Location:		Soils Lab				

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 15-1101-0228

Project Number: 7559

Sample Number: T-4
Boring Number: MB-2
Depth: 190.0-190.33 ft.
Sample Type: Undisturbed

Sample Description: SANDY LEAN CLAY (CL A-6(11))
Remarks:

Test Number:
Test Date: 9/29/15

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9960	0.3806	0.00	0.6185	0.000	0.000	0.000	0.000
1	0.125	0.0029	0.9931	0.3777	0.30	0.6137	0.000	0.000	0.000	0.000
2	0.250	0.0098	0.9862	0.3708	0.99	0.6025	* 4.7192	2.622	159.461	66.681
3	0.500	0.0231	0.9729	0.3575	2.32	0.5809	* 10.3175	5.732	70.988	29.684
4	1.000	0.0519	0.9441	0.3287	5.21	0.5342	* 11.7213	6.512	58.842	24.606
5	2.000	0.0946	0.9014	0.2860	9.50	0.4648	* 15.3923	8.551	40.847	17.081
6	4.000	0.1286	0.8674	0.2520	12.91	0.4095	* 16.9259	9.403	34.397	14.383
7	8.000	0.1694	0.8266	0.2112	17.01	0.3432	* 20.1672	11.204	26.215	10.962
8	2.000	0.1596	0.8364	0.2210	16.03	0.3591	0.000	0.000	0.000	0.000
9	0.500	0.1419	0.8541	0.2387	14.25	0.3878	0.000	0.000	0.000	0.000
10	0.125	0.0890	0.9070	0.2916	8.94	0.4739	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By:

Checked By:

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge

Project Number: 7559

Location: Soils Lab

Job Number: 15-1101-0228

Test Date: 9/29/15

Sample Number: T-4

Sample Description:

Boring Number: MB-2

SANDY LEAN CLAY (CL A-6(11))

Depth: 190.0-190.33 ft.

Remarks:

Sample Type: Undisturbed

Test Number:

Liquid Limit: 0.0000

Initial Void Ratio: 0.6175

Initial Height (in): 0.9960

Plastic Limit: 0.0000

Plasticity Index (%): 0.0000

Initial Diameter (in): 2.4990

Specific Gravity: 2.6000
Assumed


Weight of Ring (g): 98.6900

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	128.16	278.80
Dry Soil + Container (g)	109.65	252.03
Weight of Container (g)	32.08	124.77
Moisture Content (%)	23.86	21.04
Void Ratio	0.6175	0.4730
Saturation (%)	99.83	112.05
Dry Density (pcf)	100.11	109.07

Tested By:


Checked By:

Consolidation Test Test Results




	Before	After	Liquid Limits:	0	Test Date:	9/30/15
Moisture (%):	14.35	16.42	Plastic Limits:	0		
Dry Density (pcf):	120.70	118.78	Plasticity Index (%):	0		
Saturation (%):	108.23	116.47				
Void Ratio:	0.3431	0.3242	Specific Gravity:	2.600	Assumed	
Sample Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559	Depth:	210.0-212.0 f	Remarks:		
Sample Number:	T-5	Boring Number:	MB-2			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/30/15
Moisture (%):	14.35	16.42	Plastic Limits:	0		
Dry Density (pcf):	120.70	118.78	Plasticity Index (%):	0		
Saturation (%):	108.23	116.47				
Void Ratio:	0.3431	0.3242	Specific Gravity:	2.600	Assumed	
Soil Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559		Depth:	210.0-212.0 f	Remarks:	
Sample Number:	T-5		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— $t_{90} C_v$

	Before	After	Liquid Limits:	0	Test Date:	9/30/15
Moisture (%):	14.35	16.42	Plastic Limits:	0		
Dry Density (pcf):	120.70	118.78	Plasticity Index (%):	0		
Saturation (%):	108.23	116.47				
Void Ratio:	0.3431	0.3242	Specific Gravity:	2.600	Assumed	
Soil Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559		Depth: 210.0-212.0 ft		Remarks:	
Sample Number:	T-5		Boring Number: MB-2			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—◆— t50 Cv

	Before	After	Liquid Limits:	0	Test Date:	9/30/15
Moisture (%):	14.35	16.42	Plastic Limits:	0		
Dry Density (pcf):	120.70	118.78	Plasticity Index (%):	0		
Saturation (%):	108.23	116.47				
Void Ratio:	0.3431	0.3242	Specific Gravity:	2.600	Assumed	
Soil Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559		Depth:	210.0-212.0 f	Remarks:	
Sample Number:	T-5		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	0	Test Date:	9/30/15
Moisture (%):	14.35	16.42	Plastic Limits:	0		
Dry Density (pcf):	120.70	118.78	Plasticity Index (%):	0		
Saturation (%):	108.23	116.47				
Void Ratio:	0.3431	0.3242	Specific Gravity:	2.600	Assumed	
Soil Description:	SANDY LEAN CLAY (CL A-6(11))					
Project Number:	7559		Depth:	210.0-212.0 ft	Remarks:	
Sample Number:	T-5		Boring Number:	MB-2		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 15-1101-0228

Project Number: 7559

Sample Number: T-5
Boring Number: MB-2
Depth: 210.0-212.0 ft.
Sample Type: Undisturbed

Sample Description: SANDY LEAN CLAY (CL A-6(11))
Remarks:

Test Number:
Test Date: 9/30/15

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9940	0.2535	0.00	0.3423	0.000	0.000	0.000	0.000
1	0.125	-0.0006	0.9946	0.2541	-0.06	0.3431	0.000	0.000	0.000	0.000
2	0.250	-0.0015	0.9955	0.2550	-0.15	0.3444	0.000	0.000	0.000	0.000
3	0.500	-0.0026	0.9966	0.2561	-0.26	0.3458	0.000	0.000	0.000	0.000
4	1.000	0.0003	0.9937	0.2532	0.03	0.3420	24.262	* 13.4786	31.495	13.170
5	2.000	0.0068	0.9872	0.2467	0.69	0.3331	1.077	0.900	700.093	194.558
6	4.000	0.0167	0.9773	0.2368	1.69	0.3197	0.852	1.412	867.566	121.620
7	8.000	0.0320	0.9620	0.2215	3.22	0.2991	1.869	1.124	383.100	147.965
8	2.000	0.0211	0.9729	0.2324	2.12	0.3139	0.000	0.000	0.000	0.000
9	0.500	0.0068	0.9872	0.2467	0.69	0.3331	0.000	0.000	0.000	0.000
10	0.125	-0.0140	1.0080	0.2675	-1.41	0.3612	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By:

Checked By:

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge **Project Number:** 7559
Location: Soils Lab
Job Number: 15-1101-0228 **Test Date:** 9/30/15

Sample Number: T-5 **Sample Description:**
Boring Number: MB-2 SANDY LEAN CLAY (CL A-6(11))
Depth: 210.0-212.0 ft. **Remarks:**
Sample Type: Undisturbed


Test Number:
Liquid Limit: 0.0000 **Initial Void Ratio:** 0.3431 **Initial Height (in):** 0.9940
Plastic Limit: 0.0000 **Plasticity Index (%):** 0.0000 **Initial Diameter (in):** 2.5000
Specific Gravity: 2.6000 **Weight of Ring (g):** 98.7000
Assumed

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	125.59	303.85
Dry Soil + Container (g)	113.88	278.59
Weight of Container (g)	32.26	124.80
Moisture Content (%)	14.35	16.42
Void Ratio	0.3431	0.3242
Saturation (%)	108.23	116.47
Dry Density (pcf)	120.70	118.78

Tested By:


Checked By:

Consolidation Test Test Results




	Before	After	Liquid Limits:	35	Test Date:	8/23/17
Moisture (%):	23.29	24.06	Plastic Limits:	17		
Dry Density (pcf):	102.71	103.07	Plasticity Index (%):	0		
Saturation (%):	123.64	129.22				
Void Ratio:	0.4438	0.4351	Specific Gravity:	2.384	Measured	
Sample Description:	LEAN CLAY (CL A-6(18))					
Project Number:	8013		Depth:	123.0-125.0 ft	Remarks:	
Sample Number:	T-3		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	35	Test Date:	8/23/17
Moisture (%):	23.29	24.06	Plastic Limits:	17		
Dry Density (pcf):	102.71	103.07	Plasticity Index (%):	0		
Saturation (%):	123.64	129.22				
Void Ratio:	0.4438	0.4351	Specific Gravity:	2.384	Measured	
Soil Description:	LEAN CLAY (CL A-6(18))					
Project Number:	8013		Depth:	123.0-125.0 f		Remarks:
Sample Number:	T-3		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	35	Test Date:	8/23/17
Moisture (%):	23.29	24.06	Plastic Limits:	17		
Dry Density (pcf):	102.71	103.07	Plasticity Index (%):	0		
Saturation (%):	123.64	129.22				
Void Ratio:	0.4438	0.4351	Specific Gravity:	2.384	Measured	
Soil Description:	LEAN CLAY (CL A-6(18))					
Project Number:	8013		Depth:	123.0-125.0 ft		Remarks:
Sample Number:	T-3		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	35	Test Date:	8/23/17
Moisture (%):	23.29	24.06	Plastic Limits:	17		
Dry Density (pcf):	102.71	103.07	Plasticity Index (%):	0		
Saturation (%):	123.64	129.22	Specific Gravity:	2.384		
Void Ratio:	0.4438	0.4351		Measured		
Soil Description:	LEAN CLAY (CL A-6(18))					Remarks:
Project Number:	8013		Depth:	123.0-125.0 ft		
Sample Number:	T-3		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	35	Test Date:	8/23/17
Moisture (%):	23.29	24.06	Plastic Limits:	17		
Dry Density (pcf):	102.71	103.07	Plasticity Index (%):	0		
Saturation (%):	123.64	129.22				
Void Ratio:	0.4438	0.4351	Specific Gravity:	2.384	Measured	
Soil Description:	LEAN CLAY (CL A-6(18))					
Project Number:	8013		Depth:	123.0-125.0 ft		Remarks:
Sample Number:	T-3		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0067

Project Number: 8013

Sample Number: T-3
Boring Number: MB-02A
Depth: 123.0-125.0 ft.
Sample Type: Undisturbed

Sample Description: LEAN CLAY (CL A-6(18))
Remarks:

Test Number:
Test Date: 8/23/17

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9940	0.3068	0.00	0.4465	0.000	0.000	0.000	0.000
1	0.125	-0.0003	0.9943	0.3071	-0.03	0.4469	0.000	0.000	0.000	0.000
2	0.250	0.0006	0.9934	0.3063	0.06	0.4457	0.000	0.000	0.000	0.000
3	0.500	0.0034	0.9906	0.3034	0.34	0.4415	2.238	0.593	339.260	297.489
4	1.000	0.0088	0.9852	0.2980	0.89	0.4336	3.242	0.779	231.680	223.953
5	2.000	0.0185	0.9755	0.2883	1.86	0.4195	0.622	0.909	1184.685	188.094
6	0.500	0.0106	0.9834	0.2963	1.06	0.4311	0.000	0.000	0.000	0.000
7	1.000	0.0128	0.9812	0.2940	1.29	0.4278	2.625	0.810	283.829	213.569
8	2.000	0.0188	0.9752	0.2880	1.89	0.4191	0.622	1.323	1183.913	129.219
9	4.000	0.0302	0.9638	0.2766	3.04	0.4025	1.433	1.760	501.466	94.878
10	8.000	0.0462	0.9478	0.2606	4.65	0.3793	1.466	1.916	474.053	84.287
11	16.000	0.0750	0.9190	0.2318	7.54	0.3374	8.165	3.203	80.045	47.406
12	4.000	0.0607	0.9333	0.2461	6.11	0.3581	0.000	0.000	0.000	0.000
13	1.000	0.0436	0.9504	0.2632	4.39	0.3830	0.000	0.000	0.000	0.000
14	0.250	0.0060	0.9880	0.3008	0.60	0.4378	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information


Project: Mobile River Bridge	Project Number: 8013	
Location: Soils Lab		
Job Number: 17-1101-0067	Test Date: 8/23/17	
Sample Number: T-3	Sample Description:	
Boring Number: MB-02A	LEAN CLAY (CL A-6(18))	
Depth: 123.0-125.0 ft.	Remarks:	
Sample Type: Undisturbed		
Test Number:		
Liquid Limit: 35.0000	Initial Void Ratio: 0.4438	Initial Height (in): 0.9940
Plastic Limit: 17.0000	Plasticity Index (%): 0.0000	Initial Diameter (in): 2.5010
Specific Gravity: 2.3840	Weight of Ring (g): 98.6500	
Measured		

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	118.54	291.67
Dry Soil + Container (g)	102.19	260.21
Weight of Container (g)	32.00	129.44
Moisture Content (%)	23.29	24.06
Void Ratio	0.4438	0.4351
Saturation (%)	123.64	129.22
Dry Density (pcf)	102.71	103.07

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	39	Test Date:	8/25/17
Moisture (%):	16.73	18.16	Plastic Limits:	14		
Dry Density (pcf):	115.48	116.03	Plasticity Index (%):	0		
Saturation (%):	147.48	163.80				
Void Ratio:	0.2621	0.2508	Specific Gravity:	2.341	Measured	
Sample Description:	LEAN CLAY with SAND (CL A-6(16))					
Project Number:	8013		Depth:	198.0-200.0 ft	Remarks:	
Sample Number:	T-8		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	39	Test Date:	8/25/17
Moisture (%):	16.73	18.16	Plastic Limits:	14		
Dry Density (pcf):	115.48	116.03	Plasticity Index (%):	0		
Saturation (%):	147.48	163.80				
Void Ratio:	0.2621	0.2508	Specific Gravity:	2.341	Measured	
Soil Description:	LEAN CLAY with SAND (CL A-6(16))					Remarks:
Project Number:	8013		Depth:	198.0-200.0 ft		
Sample Number:	T-8		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					


Consolidation Test Test Results



—■— t90 Cv


	Before	After	Liquid Limits:	39	Test Date:	8/25/17
Moisture (%):	16.73	18.16	Plastic Limits:	14		
Dry Density (pcf):	115.48	116.03	Plasticity Index (%):	0		
Saturation (%):	147.48	163.80				
Void Ratio:	0.2621	0.2508	Specific Gravity:	2.341	Measured	
Soil Description:	LEAN CLAY with SAND (CL A-6(16))					
Project Number:	8013		Depth:	198.0-200.0 ft		Remarks:
Sample Number:	T-8		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	39	Test Date:	8/25/17
Moisture (%):	16.73	18.16	Plastic Limits:	14		
Dry Density (pcf):	115.48	116.03	Plasticity Index (%):	0		
Saturation (%):	147.48	163.80				
Void Ratio:	0.2621	0.2508	Specific Gravity:	2.341	Measured	
Soil Description:	LEAN CLAY with SAND (CL A-6(16))					
Project Number:	8013		Depth:	198.0-200.0 ft		Remarks:
Sample Number:	T-8		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results



	Before	After	Liquid Limits:	39	Test Date:	8/25/17
Moisture (%):	16.73	18.16	Plastic Limits:	14		
Dry Density (pcf):	115.48	116.03	Plasticity Index (%):	0		
Saturation (%):	147.48	163.80				
Void Ratio:	0.2621	0.2508	Specific Gravity:	2.341	Measured	
Soil Description:	LEAN CLAY with SAND (CL A-6(16))					
Project Number:	8013		Depth:	198.0-200.0 ft		Remarks:
Sample Number:	T-8		Boring Number:	MB-02A		
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Results

Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0067

Project Number: 8013

Sample Number: T-8
Boring Number: MB-02A
Depth: 198.0-200.0 ft.
Sample Type: Undisturbed

Sample Description: LEAN CLAY with SAND (CL A-6(16))
Remarks:

Test Number:
Test Date: 8/25/17

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9990	0.2082	0.00	0.2633	0.000	0.000	0.000	0.000
1	0.125	-0.0006	0.9996	0.2088	-0.06	0.2640	0.000	0.000	0.000	0.000
2	0.250	0.0000	0.9990	0.2082	0.00	0.2633	0.000	0.000	0.000	0.000
3	0.500	0.0006	0.9984	0.2077	0.06	0.2626	2.704	* 1.5024	285.227	119.275
4	1.000	0.0037	0.9953	0.2045	0.37	0.2586	5.361	3.514	142.985	50.683
5	2.000	0.0106	0.9884	0.1977	1.06	0.2500	0.764	3.057	989.773	57.448
6	0.500	0.0031	0.9959	0.2051	0.31	0.2593	0.000	0.000	0.000	0.000
7	1.000	0.0054	0.9936	0.2028	0.54	0.2565	65.513	* 36.3964	11.660	4.876
8	2.000	0.0108	0.9882	0.1974	1.08	0.2496	1.006	8.612	750.830	20.382
9	4.000	0.0202	0.9788	0.1880	2.03	0.2377	1.077	4.852	688.207	35.490
10	8.000	0.0339	0.9651	0.1743	3.40	0.2204	0.937	7.881	769.166	21.243
11	16.000	0.0533	0.9457	0.1549	5.34	0.1959	5.303	15.697	130.499	10.241
12	4.000	0.0382	0.9608	0.1700	3.82	0.2150	0.000	0.000	0.000	0.000
13	1.000	0.0208	0.9782	0.1874	2.08	0.2370	0.000	0.000	0.000	0.000
14	0.250	0.0090	0.9900	0.1992	0.90	0.2519	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge **Project Number:** 8013
Location: Soils Lab
Job Number: 17-1101-0067 **Test Date:** 8/25/17

Sample Number: T-8 **Sample Description:**
Boring Number: MB-02A LEAN CLAY with SAND (CL A-6(16))
Depth: 198.0-200.0 ft. **Remarks:**
Sample Type: Undisturbed


Test Number:
Liquid Limit: 39.0000 **Initial Void Ratio:** 0.2621 **Initial Height (in):** 0.9990
Plastic Limit: 14.0000 **Plasticity Index (%):** 0.0000 **Initial Diameter (in):** 2.5040
Specific Gravity: 2.3410 **Weight of Ring (g):** 111.0800
Measured

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	110.01	304.45
Dry Soil + Container (g)	98.87	277.59
Weight of Container (g)	32.27	129.65
Moisture Content (%)	16.73	18.16
Void Ratio	0.2621	0.2508
Saturation (%)	147.48	163.80
Dry Density (pcf)	115.48	116.03

Tested By: B. Hak


Checked By: C. Dugger

Consolidation Test Test Results




	Before	After	Liquid Limits:	83	Test Date:	10/23/17
Moisture (%):	109.67	76.38	Plastic Limits:	46		
Dry Density (pcf):	41.51	52.52	Plasticity Index (%):	0		
Saturation (%):	107.22	107.98				
Void Ratio:	2.1260	1.5693	Specific Gravity:	2.078	Measured	
Sample Description:	ELASTIC SILT with SAND(MH A-7-5(33))					
Project Number:	8063	Depth:	28.0-30.0 ft	Remarks:		
Sample Number:	T-2	Boring Number:	TH-13			
Project:	Mobile River Bridge					
Client:	ALDOT					
Location:	Soils Lab					

Consolidation Test Test Results




	Before	After	Liquid Limits:	83	Test Date:	10/23/17
Moisture (%):	109.67	76.38	Plastic Limits:	46		
Dry Density (pcf):	41.51	52.52	Plasticity Index (%):	0		
Saturation (%):	107.22	107.98				
Void Ratio:	2.1260	1.5693	Specific Gravity:	2.078	Measured	
Soil Description: ELASTIC SILT with SAND(MH A-7-5(33))						
Project Number:		8063		Depth: 28.0-30.0 ft		Remarks:
Sample Number:		T-2		Boring Number: TH-13		
Project: Mobile River Bridge						
Client: ALDOT						
Location: Soils Lab						

Consolidation Test Test Results




	Before	After	Liquid Limits:	83	Test Date:	10/23/17
Moisture (%):	109.67	76.38	Plastic Limits:	46		
Dry Density (pcf):	41.51	52.52	Plasticity Index (%):	0		
Saturation (%):	107.22	107.98				
Void Ratio:	2.1260	1.5693	Specific Gravity:	2.078	Measured	
Soil Description: ELASTIC SILT with SAND(MH A-7-5(33))						
Project Number:		8063	Depth: 28.0-30.0 ft		Remarks:	
Sample Number:		T-2	Boring Number: TH-13			
Project: Mobile River Bridge						
Client: ALDOT						
Location: Soils Lab						

Consolidation Test Test Results



	Before	After	Liquid Limits:	83	Test Date:	10/23/17
Moisture (%):	109.67	76.38	Plastic Limits:	46		
Dry Density (pcf):	41.51	52.52	Plasticity Index (%):	0		
Saturation (%):	107.22	107.98				
Void Ratio:	2.1260	1.5693	Specific Gravity:	2.078	Measured	
Soil Description: ELASTIC SILT with SAND(MH A-7-5(33))						
Project Number:		8063	Depth: 28.0-30.0 ft		Remarks:	
Sample Number:		T-2	Boring Number: TH-13			
Project: Mobile River Bridge						
Client: ALDOT						
Location: Soils Lab						

Consolidation Test Test Results



	Before	After	Liquid Limits:	83	Test Date:	10/23/17
Moisture (%):	109.67	76.38	Plastic Limits:	46		
Dry Density (pcf):	41.51	52.52	Plasticity Index (%):	0		
Saturation (%):	107.22	107.98				
Void Ratio:	2.1260	1.5693	Specific Gravity:	2.078	Measured	
Soil Description: ELASTIC SILT with SAND(MH A-7-5(33))						
Project Number:		8063	Depth: 28.0-30.0 ft		Remarks:	
Sample Number:		T-2	Boring Number: TH-13			
Project: Mobile River Bridge						
Client: ALDOT						
Location: Soils Lab						

Consolidation Test Results Summary

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0145

Project Number: 8063

Sample Number: T-2
Boring Number: TH-13
Depth: 28.0-30.0 ft
Sample Type: Undisturbed

Sample Description:
 ELASTIC SILT with SAND(MH A-7-5(33))

Remarks:

Test Number:
Test Date: 10/23/17

Index	Load Sequence (tsf)	Cummulative Change in Height (in)	Specimen Height (in)	Height of Void (in)	Vertical Strain (%)	Void Ratio	t90 Fitting Time (min)	t50 Fitting Time (min)	t90 Cv (ft2/year)	t50 Cv (ft2/year)
0	0.000	0.0000	0.9940	0.6754	0.00	2.1199	0.000	0.000	0.000	0.000
1	0.125	0.0017	0.9923	0.6737	0.17	2.1145	0.000	0.000	0.000	0.000
2	0.250	0.0037	0.9903	0.6717	0.37	2.1082	61.293	* 34.0515	12.381	5.177
3	0.500	0.0080	0.9860	0.6674	0.80	2.0948	8.288	2.792	90.774	62.604
4	1.000	0.0157	0.9783	0.6597	1.58	2.0706	2.120	3.508	349.327	49.044
5	2.000	0.0294	0.9646	0.6460	2.95	2.0277	1.086	4.600	662.752	36.360
6	0.500	0.0168	0.9772	0.6586	1.69	2.0671	0.000	0.000	0.000	0.000
7	1.000	0.0208	0.9732	0.6546	2.09	2.0545	0.622	1.631	1179.075	104.359
8	2.000	0.0302	0.9638	0.6452	3.04	2.0250	2.031	2.188	353.961	76.306
9	4.000	0.0721	0.9219	0.6033	7.26	1.8934	12.382	15.480	53.111	9.868
10	8.000	0.1882	0.8058	0.4872	18.93	1.5292	252.205	41.529	1.992	2.811
11	16.000	0.3111	0.6829	0.3643	31.30	1.1434	398.307	47.055	0.906	1.782
12	4.000	0.2652	0.7288	0.4102	26.68	1.2875	0.000	0.000	0.000	0.000
13	1.000	0.2033	0.7907	0.4721	20.45	1.4817	0.000	0.000	0.000	0.000
14	0.250	0.1770	0.8170	0.4984	17.81	1.5643	0.000	0.000	0.000	0.000

Predicted value indicated with *

Tested By: B. Hak

Checked By: C. Dugger

Consolidation Test

Consolidation Specimen Information

Project: Mobile River Bridge
Location: Soils Lab
Job Number: 17-1101-0145

Project Number: 8063

Test Date: 10/23/17

Sample Number: T-2
Boring Number: TH-13
Depth: 28.0-30.0 ft
Sample Type: Undisturbed

Sample Description:
 ELASTIC SILT with SAND(MH A-7-5(33))
Remarks:

Test Number:
Liquid Limit: 83.0000 **Initial Void Ratio:** 2.1260 **Initial Height (in):** 0.9940
Plastic Limit: 46.0000 **Plasticity Index (%):** 0.0000 **Initial Diameter (in):** 2.5020
Specific Gravity: 2.0780 **Weight of Ring (g):** 98.6400
 Measured

Parameters	Initial Specimen	Final Specimen
Moist Weight + Container (g)	107.13	230.18
Dry Soil + Container (g)	68.02	188.01
Weight of Container (g)	32.36	132.80
Moisture Content (%)	109.67	76.38
Void Ratio	2.1260	1.5693
Saturation (%)	107.22	107.98
Dry Density (pcf)	41.51	52.52

Tested By: B. Hak

Checked By: C. Dugger



September 28, 2017

PROJECT: Mobile River Bridge - Main Span Unit
CLIENT: Alabama Department of Transportation

JOB #: 17-1101-0145
LAB #: 7971
Technician: B. Hak

REPORT OF: Measurement of Soil Resistivity AASHTO T288

Location	Depth (ft)	Date Tested	Resisivity (Ohms-cm)
MB-1 - S-1A	3.0-5.0	9/17-9/21/2017	2,500
MB-1 - S-1B	5.0-7.0	9/17-9/21/2018	3,000
MB-1 - S-2A	8.0-10.0	9/17-9/21/2018	1,500
MB-1 - S-2B	10.0-12.0	9/17-9/21/2019	1,500
MB-1 - S-3A	18.0-22.0	9/17-9/21/2018	6,775
MB-1 - S-3B			
MB-1 - S-4A	28.0-32.0	9/17-9/21/2020	8,950
MB-1 - S-4B			
MB-2A - C-1	15.0-16.5	6/23/17	430
MB-2A - C-2	25.0-26.5	6/23/17	2,250
MB-2A - C-3	35.0-37.0	6/23/17	220
MB-2A - C-4	45.0-47.0	6/23/17	199
MB-2A - C-5	55.0-57.0	6/23/17	470
MB-2A - C-6	64.5-65.5	6/23/17	240
MB-2A - C-7	74.5-75.5	6/23/17	278
MB-2A - C-8	84.5-85.5	6/23/17	215
MB-2A - C-9	94.5-95.5	6/23/17	2,100
MB-2A - C-10	105.0-105.5	6/23/17	2,150
MB-2A - C-11	130.0-130.5	7/1/17	725
MB-2A - C-12	155.0-155.5	7/1/17	6,490

MATERIALS ENGINEERING LABORATORY

3707 Cottage Hill Road
Mobile, AL. 36609
251-666-2443 ph / 251-665-5491 fax
www.thompsonengineering.com



September 21, 2016

CLIENT: ALDOT

PROJECT: Mobile River Bridge High Level Approach

JOB #: 17-1101-0145

LAB #:

REPORT OF: Measurement of Soil Resistivity AASHTO T288

DATE
TESTED: 9-17 & 9-21

TECHNICIAN
Hak

Location	Depth (ft)	Resisivity (Ohms-cm)
WHLA-3	3.0 - 5.0 ft.	5000
WHLA-3	5.0 - 7.0 ft.	5900
WHLA-3	8.0 - 10.0 ft.	4900
WHLA-3	10.0 - 12.0 ft.	4900
WHLA-3	28.0 - 32.0 ft.	7200
WHLA-3	18.0 - 22.0 ft.	8850

Chris Dugger


MATERIALS ENGINEERING LABORATORY

3707 Cottage Hill Road
Mobile, AL. 36609
251-666-2443 ph / 251-665-5491 fax
www.thompsonengineering.com

APPENDIX C

Results of Statistical Analysis

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.16.3. bvkDK



- Notes:
1. Instances of refusal and N_{60} greater than 100 blows per foot (bpf) are interpreted as equal to 100 bpf.
 2. The data presented above are based on the following explorations near/along the Main Span alignment: TH-13, WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**N_{60} VS ELEVATION
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-1



Notes:

1. The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, TH-13, WHLA-03.
2. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-2

Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama


**ENERGY-CORRECTED SPT N
 VERSUS ELEVATION
 UPPER OVERBURDEN LAYER
 MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
 a joint venture

FIG. C-2



Statistical Summary:

count = 70 bpf
 mean = 7 bpf
 median = 6 bpf
 std = 6 bpf
 min = 1 bpf
 25% = 3 bpf
 50% = 6 bpf
 75% = 10 bpf
 max = 34 bpf

Notes:

- The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.
- Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusals are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-3

Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama


ENERGY-CORRECTED SPT N VERSUS ELEVATION LOWER OVERBURDEN LAYER MAIN SPAN ALIGNMENT

September 2023

110704-016

Kiewit | Massman | Traylor
 a joint venture

FIG. C-3



Statistical Summary:

count = 65 bpf
 mean = 48 bpf
 median = 42 bpf
 std = 31 bpf
 min = 13 bpf
 25% = 25 bpf
 50% = 42 bpf
 75% = 60 bpf
 max = 178 bpf

Notes:

- The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.
- Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-4

Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama


ENERGY-CORRECTED SPT N VERSUS ELEVATION UPPER SAND LAYER MAIN SPAN ALIGNMENT

September 2023

110704-016

Kiewit | Massman | Traylor
 a joint venture

FIG. C-4



Notes:

1. The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.
2. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-5

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**ENERGY-CORRECTED SPT N
VERSUS ELEVATION
LOWER SAND LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-5



Statistical Summary:

count = 52 bpf
 mean = 63 bpf
 median = 51 bpf
 std = 47 bpf
 min = 9 bpf
 25% = 38 bpf
 50% = 51 bpf
 75% = 78 bpf
 max = 222 bpf

Notes:

- The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, WHLA-03.
- Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-6

Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama


ENERGY-CORRECTED SPT N VERSUS ELEVATION CLAY/SILT LAYER MAIN SPAN ALIGNMENT

September 2023

110704-016

Kiewit | Massman | Traylor
 a joint venture

FIG. C-6



Statistical Summary:

count = 38 bpf
 mean = 85 bpf
 median = 47 bpf
 std = 75 bpf
 min = 10 bpf
 25% = 21 bpf
 50% = 47 bpf
 75% = 148 bpf
 max = 300 bpf

Notes:

- The data presented above are based on the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, WHLA-03.
- Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.

FIG. C-7

Alabama Department of Transportation
 I-10 Mobile River Bridge Project
 Mobile County, Alabama

ENERGY-CORRECTED SPT N VERSUS ELEVATION BASAL SILT/SAND LAYER MAIN SPAN ALIGNMENT




September 2023

110704-016

Kiewit | Massman | Traylor
 a joint venture

FIG. C-7

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 30. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
TH-13, WHLA-03, MB-01, MB-02, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N_{60} DATA
UPPER OVERBURDEN LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-8

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 70. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
TH-13, WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N_{60} DATA
LOWER OVERBURDEN LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-9

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N₆₀ equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 65. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
TH-13, WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N₆₀ DATA
UPPER SAND LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-10

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 63. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
TH-13, WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N_{60} DATA
LOWER SAND LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-11

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 52. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N_{60} DATA
CLAY/SILT LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-12

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvkDK



Notes:

1. Instances of: N_{60} equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 38. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
WHLA-03, MB-01, MB-02, MB-02A, HLA-12, and HLA-13.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N_{60} DATA
BASAL SILT/SAND LAYER
MAIN SPAN ALIGNMENT**




September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-13

P:\SEA\110000s\110704 I-10 Mobile Riv\Analyses\Statistics\Main Span ver0.163.bvk\DK



Notes:

1. Instances of: N₆₀ equal to 0 blows per foot (bpf) are interpreted as 1 bpf; and refusal are extrapolated to penetration lengths of 12 inches but are limited to 300 bpf.
2. The count of the data set is equal to 228. The distribution parameters presented in the legend above are described as follows:
 μ = mean of normal distribution; σ = standard deviation of normal distribution; shape = standard deviation of the log of the variate; loc = scaling term which sets the start of the distribution; scale = $\exp(\text{mean of the log of the variate})$; and CV = coefficient of variation of the distribution.
3. The histogram is normalized such that the total area of the histogram is equal to one.
4. The lognormal-based mean $\pm$ one standard deviation ($\mu \pm \sigma$) approximations account for a lognormal to arithmetic space transformation of the following form:
$$\mu \pm \sigma = \exp[\ln(\text{scale}) \pm \text{shape} + 0.5 \times \text{shape}^2]$$
5. The data presented above are based on the following explorations near/along the Main Span alignment:
TH-13, WHLA-03, MB-01, MB-02, HLA-12, HLA-13, and MB-02A.
6. The analyses disregards data in the strata underlying the Lower Sand Layer.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**NORMAL AND LOGNORMAL
DISTRIBUTIONS OF N₆₀ DATA
MAIN SPAN ALIGNMENT**


September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-14

FIG. C-15



Notes:

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 67.5 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, TH-13, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
UPPER OVERBURDEN LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-15

FIG. C-16**Notes:**

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 262.5 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
LOWER OVERBURDEN LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-16

FIG. C-17**Notes:**

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 322.0 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
UPPER SAND LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-17

FIG. C-18**Notes:**

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 363.2 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
LOWER SAND LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-18

FIG. C-19**Notes:**

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 488.2 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, MB-02A, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
CLAY/SILT LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-19

FIG. C-20**Notes:**

1. Individual bar segments across all USCS columns sum to 100 percent.
2. USCS = Unified Soil Classification System. Histogram is based on a total of 364.2 lineal feet of soil and derived from the following explorations: HLA-12, HLA-13, MB-01, MB-02, MB-02A, WHLA-03.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama


**USCS SUMMARY BY FOOTAGE
BASAL SILT/SAND LAYER
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. C-20

FIG. C-21**Notes:**

- Individual bar segments across all USCS columns sum to 100 percent.
- USCS = Unified Soil Classification System.
- Histogram is based on a total of 1015.2 linear feet of soil and derived from the following explorations:
HLA-12, HLA-13, MB-01, MB-02, MB-02A, TH-13, WHLA-03.
- Histogram disregards data in the strata underlying the Lower Sand Layer.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**USCS SUMMARY
BY FOOTAGE
MAIN SPAN ALIGNMENT**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture



FIG. C-21

APPENDIX D

Axial Resistance Plots

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
MB-01
(Reference Grade Elev. = 2.9 ft.)



NOTES:

1. The analyses were performed for a single pile based on results of load testing performed on test pile TP-WPA, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

ESTIMATED AXIAL RESISTANCE 72-INCH-DIAMETER PIPE PILE BORING MB-01

September 2023



110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. D-1

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
MB-02
(Reference Grade Elev. = 7.4 ft.)



NOTES:

1. The analyses were performed for a single pile based on results of load testing performed on test pile TP-WPA, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**ESTIMATED AXIAL RESISTANCE
72-INCH-DIAMETER PIPE PILE
BORING MB-02**

September 2023


110704-016

Kiewit | Massman | Traylor
a joint venture


FIG. D-2

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
MB-02A
(Reference Grade Elev. = -2 ft.)



Nominal Axial Resistance (kips)



NOTES:

1. The analyses were performed for a single pile based on results of load testing performed on test pile TP-WPA, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

ESTIMATED AXIAL RESISTANCE 72-INCH-DIAMETER PIPE PILE BORING MB-02A

September 2023



110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. D-3

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
WHLA-03
(Reference Grade Elev. = 7.1 ft.)



NOTES:

1. The analyses were performed for a single pile based on results of the existing Project load testing program, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**ESTIMATED AXIAL RESISTANCE
24-IN SQUARE PRESTRESSED
CONCRETE PILE
BORING WHLA-03**

September 2023


110704-016

Kiewit | Massman | Traylor
a joint venture


FIG. D-4

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
HLA-12
(Reference Grade Elev. = 16.3 ft.)



Nominal Axial Resistance (kips)



NOTES:

1. The analyses were performed for a single pile based on results of the existing Project load testing program, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**ESTIMATED AXIAL RESISTANCE
24-IN SQUARE PRESTRESSED
CONCRETE PILE
BORING HLA-12**

September 2023



110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. D-5

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
MB-02
(Reference Grade Elev. = 7.4 ft.)



NOTES:

1. The analyses were performed for a single pile based on results of the existing Project load testing program, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

ESTIMATED AXIAL RESISTANCE 24-IN SQUARE PRESTRESSED CONCRETE PILE BORING MB-02

September 2023


110704-016

Kiewit | Massman | Traylor
a joint venture


FIG. D-6

GENERALIZED SUBSURFACE PROFILE

Based on nearby explorations:
MB-02A
(Reference Grade Elev. = -2 ft.)



Nominal Axial Resistance (kips)



NOTES:

1. The analyses were performed for a single pile based on results of the existing Project load testing program, guidelines included in AASHTO, and our experience.
2. The factored total shaft resistance is determined by adding the unfactored side and base resistances, multiplied by appropriate resistance factors per AASHTO.

Alabama Department of Transportation
I-10 Mobile River Bridge Project
Mobile County, Alabama

**ESTIMATED AXIAL RESISTANCE
24-IN SQUARE PRESTRESSED
CONCRETE PILE
BORING MB-02A**

September 2023

110704-016

Kiewit | Massman | Traylor
a joint venture

FIG. D-7